

## PFD 101 U

Built-under dishwasher, ADA compliant,  
for large loads of dishware in households, offices and utility areas.



- Wash performance: 13 place settings in just 17 min\*
- 13% less energy consumption
- Everything completely dry – AutoOpen assisted drying
- Intuitive to operate thanks to clear fascia panel design
- Flexible loading of wash items for the best cleaning results

\* Depending on site conditions (temperature of incoming water / power connection) values given may vary.

EAN: 4002516366850 / Material number: 11605420 /  
Old Material Number: 61010102USA

<b>Construction type and design</b>	
Model	Built-under dishwasher
Range	ProfiLine
Wash system	Fresh water front loader
Number of levels	2
Front	Stainless steel
Side walls	Galvanised
Control panel color	Clean Touch Steel
<b>Application</b>	
Suitable for retirement and care homes	•
Suitable for hospitals	•
Suitable for Bed & Breakfast	•
Suitable for child care facilities	•
Suitable for universities and schools	•
Suitable for offices	•
Suitable for domestic use	•
Suitable for small businesses	•
Suitable for sports clubs	•
<b>Performance data</b>	
Tested virucidal efficacy	•
Certified hygiene	•
Circulation pump, Qmax in gal/min (l/min)	19.8 (75)
Shortest program duration in min.	52
Maximum final rinse temperature in °F (°C)	180 (82)
Cleaning performance, place settings/cycle	13
Service life in wash cycles	12500
<b>Miele MOVE</b>	
Network-enabled with Miele MOVE	•
<b>Control</b>	
Control system	Electronic controls
Program selection	Program selectors
Max. delay start in h	24
Countdown indicator	•
Dishwashing programs [number]	8
Adjustable final rinse temperature	•
Program sequence indicator	•
Choice of display language	•
Check filter indicator	•
<b>Standard electrical connection</b>	
Electrical connection	AC 120V 60HZ
Heater rating in kW	1.30
Total connected load in kW	1.40
Fuse rating in A	15
Length of power cord in ft (m)	5 (1.70)
NEMA plug: 5-15	•
<b>Possible voltage variant 1</b>	
Electrical connection	2N AC 120/208-240V, 60HZ

## PFD 101 U

Built-under dishwasher, ADA compliant,  
for large loads of dishware in households, offices and utility areas.



EAN: 4002516366850 / Material number: 11605420 /  
Old Material Number: 61010102USA

Heater rating in kW	3.50-3.80
Total connected load in kW	3.70-4.00
Fuse rating in A	30
<b>Water connection/drainage</b>	
Cold or hot water [number]	1
Required flow pressure in bar	1.00-10.00
Drain hose [DN]	22
Maximum delivery head for drain pump in inches (cm)	39 3/8 (100)
Integrated water softener	•
Maximum water hardness in gpg (mmol/l)	38.02 (6.50)
Water protection system	Waterproof system
Length of water inlet hose in inches (cm)	59 1/8 (150)
Length of water drain hose in inches (cm)	59 1/8 (150)
<b>Dimensions and weight</b>	
External dimensions, net height in inches	31 3/4 (805)
External dimensions, net width in inches	23 9/16 (598)
External dimensions, net depth in inches	22 1/2 (570)
External dimensions, gross height in inches	38 1/4 (970)
External dimensions, gross width in inches	26 7/16 (670)
External dimensions, gross depth in inches	27 3/16 (690)
Usable space in wash cabinet, width in inches (mm)	21 5/16 (540)
Usable space in wash cabinet, height in inches (mm)	20 1/8 (510)
Usable space in wash cabinet, depth of upper basket in inches (mm)	17 3/4 (450)
Usable space in wash cabinet, depth of lower basket in inches (mm)	17 3/4 (450)
In-feed height above floor in inches (mm)	8 5/16 (210)
Required niche width in mm	23 5/8 (600)
Net weight [kg]	104 (47)
Gross weight in lbs.	122 (55)
Maximum floor load in N/m <sup>2</sup>	1000
<b>Emission values</b>	
Emission sound pressure level in workplace (LpA)	33 dB(A) re 20 µPa
Sound power (LwA) in dB(A) re 1 pW	48.0
<b>Programs</b>	
Normal Plus	•
Normal	•
SaniWash	•
Cold/Pre-wash	•
Glasses	•
Plastic	•
EnergySave/Economy	•
Intensive	•
<b>Baskets</b>	
ExtraComfort P baskets	•
Flexible FlexLine basket design	•
FlexCare glass holder [number]	2
FlexCare cup rack [number]	1
Cutlery basket	•

## PFD 101 U

Built-under dishwasher, ADA compliant,  
for large loads of dishware in households, offices and utility areas.



EAN: 4002516366850 / Material number: 11605420 /  
Old Material Number: 61010102USA

Height-adjustable upper basket	•
Combinable with APFD 210 bottle basket	•
<b>Features</b>	
Commercial-grade electrical connection	•
Drying	Additional drying, AutoOpen assisted drying, Active condensation drying
1 Combi dispenser/door for powder and liquid media	•
EcoFeedback	•
Child lock	•
Brilliant GlassCare	•
Wash cabinet made from high-quality stainless steel	•
Optical interface	•
SmartStart	•
FlexiTimer with EcoStart	•
<b>Connection options</b>	
Wi-Fi	•
<b>Standards, test certificates, and symbols</b>	
CE	•
Complies with Machinery Directive 2006/42/EC	•
VDE	•
EMC radio suppressed	•
DIN EN 17735	•
EN 1717	•
UL	•