


Key Features

Streamlined Desktop Display Solution | Enhanced Productivity with Dual Monitor Setup | Reduce Clutter with Single-Cable Solution | A More Comfortable Workspace | Command and Control Made Easy



Product Description

Designed to boost productivity and maximize output, the ViewSonic® VG2756-4K is a 27" 4K Ultra HD docking monitor that transforms your desktop into a streamlined and efficient workspace. Enjoy reliable and flexible network connectivity with the integrated gigabit Ethernet port, while the latest USB Type-C connectivity makes setup a breeze. That's not all, the integrated USB hub also provides single-cable simplicity for connecting and charging your peripherals and accessories. A best-in-class ergonomic design features 40-degree tilt and bi-directional pivot so your screen and workspace are as comfortable as you need. In addition, the included vDisplay software gives you quick and easy OSD control, as well as customized screen templates for easy multi-tasking. This monitor is also shipped in eco-friendly biodegradable packaging, along with an easy-to-install quick release stand that makes for quick deployment and a lower total cost of ownership.



27"
DISPLAY



IPS
PANEL



3840 x 2160
RESOLUTION

Contact Sales

-  call: 888.881.8781
-  email: salesinfo@viewsonic.com
-  visit: viewsonic.com

Display:

Display Size (in.):	27
Viewable Area (in.):	27
Panel Type:	IPS
Resolution:	3840 x 2160
Resolution Type:	4K (3840x2160)
Static Contrast Ratio:	1,000:1
Dynamic Contrast Ratio:	50,000,000:1
Light Source:	LED
Brightness:	350 cd/m2
Colors:	1.07B
Color Space Support:	8+2 bits
Aspect Ratio:	16:9
Response Time (Typical GTG):	14ms
Response Time (GTG w/OD):	5ms
Backlight Life (Hours):	30,000
Panel Surface:	Anti-glare, Hard coating (3H)

Compatibility:

PC Resolution (max):	3840 x 2160
Mac® Resolution (max):	3840 x 2160

Connector:

USB 3.2 Gen 1 Type A(2), USB 3.2 Gen 1 Type B(1), Ethernet LAN (RJ45)(1), HDMI 2.0 In(1), Display Port(1)

Audio:

Internal Speakers:	2W (x2)
--------------------	---------

Power:

Eco Mode (Conserve):	16.8W
Eco Mode (optimized):	21.2W
Consumption (typical):	30.7W
Consumption (max):	70.0W
Voltage:	AC 100-240V (universal), 50-60Hz
Stand-by:	0.5W
Power Supply:	Internal

Additional Hardware:

Kensington Lock Slot:	1
-----------------------	---

Controls:

Physical Controls:	1,2,3,4,5,6 (Power)
On Screen Display:	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)

Operating Conditions:

Temperature:	32-104° F (0 - 40° C)
Humidity (non-condensing):	20-90%

Mount:

VESA Compatible:	100 x 100 mm
------------------	--------------

Video Signal:

Frequency Horizontal:	15 ~ 150 KHz
Frequency Vertical:	24 ~ 75 Hz

Video Input:

Digital Sync:	TMDs for HDMI (v2.0), PCI-E for DisplayPort (v1.2), Micro-Packet for USB Type C
---------------	---

Ergonomics:

Height Adjust:	130 mm / 5.1 in
Swivel:	120°
Pivot (Right/Left):	90° / 90°
Tilt (Forward/Back):	40° / 5°

Weight (imperial):

Net (lbs):	16.5
Net Without Stand (lbs):	11.2
Gross (lbs):	23.6

Weight (metric):

Net (kg):	7.5
Net Without Stand (kg):	5.1
Gross (kg):	10.7

Dimensions (imperial) (WxHxD):

Packaging (in.):	27.2 x 8.6 x 16.9
Physical (in.):	24.1 x 16.0 x 8.0
Physical Without Stand (in.):	24.1 x 14.3 x 2.0

Dimensions (metric) (WxHxD):

Packaging (mm):	692.0 x 218.0 x 430.0
Physical (mm):	613.0 x 406.0 x 202.0
Physical Without Stand (mm):	613.0 x 363.0 x 52.0

General:

Regulations: cTUVus, FCC-B, ICES003, Energy Star Certified, EPEAT Certified, MX-CoC, Mexico Energy
PACKAGE CONTENTS: VG2756-4K, Power Cable, DP to DP Cable, USB Type C cable, USB Type B Uplink Cable, Quick Start Guide

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

Warranty: Three-year limited warranty on parts, labor and backlight

UPC: 766907008555