

OVERVIEW



1. HDMI	6. USB-C 3.2 Gen 1
2. HDMI	7. USB 3.2 Gen 1
3. DisplayPort	8. USB 3.2 Gen 1
4. USB-C 3.2 Gen 2 (data upstream)	9. Combo audio jack
5. Power connector	

PERFORMANCE

Panel

Panel

4-side NearEdgeless, In-Plane Switching

Backlight

WLED

Display Size

27 inches

Max View Area

WxH: 596.7 x 335.7 mm

Resolution

3840 x 2160

Aspect Ratio

16:9

Pixel Pitch

0.1554 x 0.1554 mm

Dot / Pixel Per Inch

164 dpi

Brightness

- Peak: 400 cd/m²
- Typical: 320 cd/m²

Contrast Ratio

- Contrast Ratio: 1300:1
- Dynamic Contrast Ratio (Typical): 3000000:1

View Angle (H / V)

Horizontal: 178°, Vertical: 178°

Response Time

- Level 1: 8 ms
- Level 2: 6 ms
- Level 3: 5 ms
- Level 4: 4 ms

Refresh Rate

60Hz

Color Gamut

- 99% sRGB
- 98% DCI-P3

Color Support

1.07 Billion

Color Depth

10-bit (8-bit+FRC)

Screen Surface Treatment

Anti-glare

Operating System

Operating System

- Windows® 11 Support
- Windows® 10 Support
- Windows® 7 Support

Multi-Media

Speakers

Panel built-in Smart Crystal sound speakers

Power Supply

Power Consumption

- Typical / Max: 40W / 180W
- Sleep / Off mode: <0.5W
- Switch-off Mode: <0.3W

Voltage Required

AC 100 to 240 V (50-60Hz)

Special Features

Special Features

- DisplayHDR™ 400
- Factory Calibration: Avg. Delta E<2
- AMD FreeSync™
AMD FreeSync™ technology only can work with AMD Radeon™ series graphics card.
- Lenovo® Artery (Lenovo® Accessories and Display Manager) Support
Lenovo® Artery supports Windows® 10 & 11, Mac OS, and Windows® On Arm (functions vary across systems).
Lenovo® Accessories and Display Manager is formerly Lenovo® Display Control Center.
- Smart Power
The Smart Power function intelligently detects overall power consumption and dynamically manages the power delivery to each device

DESIGN

Mechanical

Bezel Width

- Side: 2mm
- Top / Bottom: 2mm / 2mm

Cable Management

Support

Case Color

Iron grey

Dimensions (WxDxH)^[1]

Models	Dimensions
Highest Position	608.6 x 182.0 x 476.4 mm (23.96 x 7.17 x 18.75 inches)
Lowest Position	608.6 x 182.0 x 476.4 mm (23.96 x 7.17 x 18.75 inches)
Unpacked Head Only	608.6 x 44.0 x 351.0 mm (23.96 x 1.73 x 13.82 inches)

Packaging Dimensions (WxDxH)

695 x 139 x 423 mm (27.36 x 5.47 x 16.65 inches)

Weight^[2]

Models	Weight
Monitor With Stand	6.2 kg (13.67 lbs)
Monitor Head Only	4.81 kg (10.6 lbs)

Packaging Weight

8.84 kg (19.46 lbs)

Stand

Supports -5° to +22° tilt

In the Box

- Monitor with Stand
- 1x DP Cable (1.8m)
- 1x HDMI® Cable (1.8m)
- 1x USB-C® to USB-C® Cable (1.5m)
- 1x Power Cable (1m)

- 1x Power Adapter
- 1x Screw Driver
- 2x Screws
- Factory Calibration Report
- Quick Setup Guide
- Warranty Booklet

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Ports^[1]

Rear Ports^[2]

- 1x USB-C® 3.2 Gen 1, USB downstream
- 1x USB-C® 3.2 Gen 2 (DP 1.4 Alt Mode and up to 80w PD), USB upstream
- 2x USB 3.2 Gen 1, USB downstream
- 2x HDMI® 2.0
- 1x DisplayPort™ 1.4
- 1x audio-out (3.5mm)

Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB4® 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

USB4® 40Gbps (USB 40Gbps): 40 Gbit/s;

Thunderbolt™ 3/4: 40 Gbit/s.

[2] Up to 80W power delivery to compatible devices by USB-C®. Listed as maximum capacity of power delivery. Actual capacity of power delivery may vary depending upon devices connected or monitor configuration, and may decline with downstream USB ports connected or higher brightness setting.

SECURITY & PRIVACY

Security

Physical Locks

Kensington® Security Slot™

SERVICE

Warranty

Base Warranty**

- 1-year courier or carry-in service
- 3-year limited warranty

CERTIFICATIONS

Green Certifications^[1]

Green Certifications

RoHS compliant

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit <https://compliance.lenovo.com>.

Other Certifications

Other Certifications

TÜV Rheinland® Eye Comfort Certification

- Feature with ** means that only one option listed under the feature can be configured on selected models. Please refer to the model configuration for specific information.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS," WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.

