

Picture


Video & Audio	Image Sensor	1/2.8" CMOS Sensor
	Video Resolution	3840X2160(8Megapixels)@20FPS
	Lens	f=2.8-8mm Max: F1.6
	Video Format	H.265
	Field of View	Horizontal: 94° ~ 50° Vertical: 53° ~ 30°
	Day & Night	IR-cut filter with auto-switching
	Infrared Night Vision	Up to 12 Meters (40ft); LED: 12pcs/1.6W/850nm
	Color Night Vision	4pcs/2.7W/6500K/180Lumens
	Audio	Two-way Audio
Power	DC Power	DC 12.0V~1A, <12W
	Power	DC power port
Interface	System	Reset Button
	Ethernet	One 10M/100Mbps RJ45
	Storage	MicroSD card slot (Max. 256GB)
	Audio	Built-in Microphone and Speaker
	Audio	Built-in Microphone and Speaker
Pan&Tilt	Pan &Tilt Range	Pan: 355°, Tilt: 0°~50°
	Auto Tracking	Support
Wi-Fi	Wireless Standard	IEEE 802.11a/ac/ax/ b/g/n
	Operating Frequency	2.4 GHz/5 GHz
	Wireless Security	WPA/WPA2/WPA3
Software Features	Frame Rate	Main Stream: 2fps - 25fps(default: 20fps) Sub Stream: 4fps - 15fps(default: 10fps)
	Code Rate	Main Stream: 4096Kbps - 8192Kbps(default: 5120Kbps) Sub Stream: 64Kbps - 512Kbps(default: 256Kbps)
	Browser Supported	Edge, Chrome, Firefox, Safari
	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
	Smart Alarm	Motion detection/Human Detection/Vehicle Detection/Pet Detection
	Record Mode	Motion Record/Schedule Record (Default: Motion Record)
	Protocols & Standards	HTTPS, SSL, TCP/IP, UDP, IPv4, UPnP, RTSP, RTMP, ONVIF, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P
	Maximal User Access	Support up to 12 simultaneous video streams (10 substreams & 2 mainstreams) 20 Users (1 admin account & 19 user accounts);
Work with	Google Assistant	
Working Environment	Temperature	Operating Temperature: -10°C~+50°C (14°F~122°F)
	Humidity	Operating Humidity: 10% ~ 90%
	Waterproof	IP64
Size & Weight	Dimension	Φ85x118mm
	Weight	415g
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/