

camera	Picture		
	Video & Audio	Image Sensor	1/2.7" CMOS Sensor
		Video Resolution	UP To: 3840 x 2160 (8 Megapixels) at 15 frames/sec
		Lens	f=2.8mm@ F=1.6 , f=8mm@ F=1.6
		Video Format	H.264, H.265
		Field of View	Horizontal : 105° Vertical : 55°
		Zoom Mode	10X hybrid zoom
		Day & Night	IR-cut filter with auto-switching
		Infrared Night Vision	Up to 10 Meters (33ft)(LED: 6pcs/850nm)
		Color Night Vision	Spotlight: 2pcs/6500K/
	Power	Audio	Two-way Audio
		Battery	6000mAh rechargeable battery (Battery life varies based on settings, usage & temperature)
		Solar	Reolink Solar Panel 2
	Interface	DC Power	5V/2A
		Power	USB Type-C port
		System	Reset Button
		Storage	Supports up to 128GB micro SD card(Included 64GB microSD Card)
	Wi-Fi	Audio	Built-in Microphone and Speaker
		Wi-Fi Standard	IEEE 802.11a/b/g/n
		Operating Frequency	2.4GHz/5GHz
	Software Features	Wi-Fi Security	WPA-PSK/WPA2-PSK
		Frame Rate	Main Stream: 10fps - 15fps Sub Stream: 10fps - 15fps
			Main Stream: 1024Kbps - 2048Kbps
		Code Rate	Main Stream: 1024Kbps - 2048Kbps
		OS Supported	PC: Windows, Mac OS; Smart phone: iOS, Android
		Smart Alarm	PIR Detection/ Human Detection/Vehicle Detection/ Pet Detection
		Record Mode	Motion Triggered Recording
		Protocols & Standards	SSL, TCP/IP, UDP, UPNP, SMTP, NTP, P2P
		Maximal User Access	Support up to 12 simultaneous video streams (10 substreams & 2 main streams)
	Working Environment	Work with	Google Assistant, Reolink Cloud
		Temperature	Operating Temperature: -10°C~+55 °C
		Humidity	Operating Humidity: 20% ~ 85%
	Size & Weight	Waterproof	Support
		Dimensions	127*80*56mm
	Warranty	Weight	335g
		Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/
Solar Panel	Electrical Parameters	Max Voltage	6.0V
		Max Current	960mA
		Max Power	5.8W
	Size & Weight	Dimensions	185.4x120.4x6.5(mm)
		Cable Length	210.6 x 174.6 x 15.4 (mm)
		Weight	4 meters
		Interface	USB Type-C Port
	Other Parameters	Working Temperature	-10°C to 55°C (14 °F to 131° F)
		Working Humidity	10%~90%
		Weather Resistance	IP65
	Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/