# 22" (21.5" viewable) Full HD 1080p Optical Touch Monitor



Intuitive Dual-Point Touch Design

**TD2220** 



Interact with your monitor as if it were a smartphone or iPad. Great for commercial kiosks, interactive POS display, and educational applications, as well as in-home gaming and photography, the ViewSonic® TD2220 22" dual-point touch Full HD LED monitor lets users execute two-finger pinches, taps and swipes for fast, intuitive navigation. 20M:1 MEGA dynamic contrast ratio, 1080p resolution and integrated speakers engage and delight with sharp images, outstanding color accuracy and crystal clear sound. Whether enjoyed at home or deployed in a high-traffic commercial setting, its scratch-resistant surface stands up to heavy use and safeguards its high quality touch experience.

# **Key Features:**

Full HD 1080p resolution and 20M:1 MEGA Dynamic Contrast Ratio

**Dual-point optical touch and Windows 7** compatible

8H scratch-resistant surface hardness

DVI, VGA, and dual-port USB hub

**Dual speakers with SRS Premium Sound** 

# **Designed for:**

**Public display** 

**Education** 

Home

**Business** 

# 22" (21.5" viewable) Full HD 1080p Optical Touch Monitor



**TD2220** 



### **Specifications**

<b>PANEL</b>	Type Display Area Optimum Resolution Brightness Contrast Ratio Iynamic Contrast Ratio Viewing Angles Response Time Backlight Life Panel Surface	22" (21.5" viewable) Wide Color TFT Active Matrix LED 18.8" horizontal x 10.6" vertical; 21.5" diagonal 1920x1080 200 cd/m² (typ.) 1000:1 (typ.) 20,000,000:1 170° horizontal, 160° vertical 5ms (typ.) White-light LED 40,000 hours (min.) 8H Scratch Resistant Surface Hardness
VIDEO INPUT	Analog Digital Frequency Sync	RGB analog (0.7 / 1.0 Vp-p, 75 ohms) DVI (TMDS, 100 ohms) Fh: 24~83kHz, Fv: 50~76Hz Separate Sync
AUDIO OUTPUT	Speakers	2-watt (x2)
COMPATIBILITY	PC Mac®	PC compatibles (Windows® 7 Operating System) n/a
CONNECTOR	Video Analog Video Digital Audio USB Power	15-pin mini D-sub (VGA) DVI-D (with HDCP) Audio In (3.5mm mini-jack) USB 2.0 (x2) Internal power board, 3-pin plug (CEE22)
POWER	Voltage Consumption Optimize Conserve	AC 100–240V (universal), 50 / 60Hz 26W (typ.) / 43W (max.) 21W (typ.) 18W (typ.)

CONTROLS Front Panel Buttons OSD	1, 2, Down, Up, Power Auto Image Adjust, Contrast/Brightness, Input Select (D-SUB, DVI-D), Audio Adjust (Volume, Mute), Color Adjust (sRGB, Bluish, Cool, Native, Warm, User Color [R,G,B]), Information, Manual Image Adjust (H/V Position, Horizontal Size, Fine Tune, Sharpness, Dynamic Contrast, Response Time, Aspect Ratio, Eco-mode), Setup Menu (Language Select, Resolution Notice, OSD Position, OSD Timeout, OSD Background, Auto Power Off, Power Indicator), Memory Recall
ERGONOMICS Tilt	Forward 5° / Back 20°
OPERATING Temperature CONDITIONS Humidity	32–104° F (0–40° C) 20–90% (non-condensing)
DIMENSIONS Physical with Stand (W x H x D) Physical without Stand Packaging	20.11 x 14.37 x 9.45 in. / 511 x 635 x 240 mm 20.11 x 12.22 x 2.61 in. / 511 x 310 x 66 mm 22.44 x 16.81 x 8.43 in. / 570 x 427 x 214 mm
WEIGHT Net with Stand Net without Stand Gross	10.85 lb. / 4.92 kg 8.73 lb. / 3.96 kg 14.22 lb. / 6.45 kg
WALL MOUNT VESA	100mm x 100mm
REGULATIONS	CE,CB, BSMI, PSB, SASO, C-tick, e-standby, KC, UL/cUL, FCC-B (including ICES003), UL CoC, Mexico Energy, GOST-R/Hygienic, UkrSEPRO, TCO 5.2, Erp, CCC, China Energy, ENERGY STAR®, EPEAT Silver, WEEE, RoHS, SVHC list
RECYCLE / DISPOSAL	Please dispose of in accordance with local, state or federal laws.
	ENERGY STAR® standards
POWER MANAGEMENT	LIVEROT OTAL Standards

## **Optional Accessories**

DVI-D to DVI-D Cable, 6FT	CB-00008187
Desktop Display Wall Mount Kit	LCD-WMK-001
DisplayPort to DVI Adapter	LCD-CABLE-001

## What's in the box?

TD2220 display, power cable, audio cable, AC/DC adapter, VGA cable, DVI cable, Quick Start Guide, ViewSonic Wizard CD (available in some countries only)















