

MARINER MX DATA SHEET

MX56

TECHNICAL SPECIFICATIONS

MX56

SKU 93607 - White | 93606 - Black

UOM Pair

Tweeter 0.75" (19mm) ceramic dome, Ferrofluid-cooled, acoustic back chamber

Woofer 5.25" (130mm) Kevlar / Nomex cone, rubber surround

Dispersion Technology Sinusoidal Textured Waveguide

Frequency Response 60Hz-20Hz +/-3dB

Impedance 8 ohms nominal; 6 ohms minimum

Power Handling 5 Watts minimum; 100 Watts maximum

Sensitivity 88dB SPL (2.83V/1 meter)

Environmental Mill Spec 810 for humidity, salt spray, temperature, UV; IP66 waterproof rating


Environmental Temp -13° to 149°F (-25°C to 65°C)

Grille Material Perforated aluminum

Dimensions (WxHxD) 6.36" x 10.08" x 5.68" (162mm x 256mm x 144mm)

Shipping Weight 13 lbs (6 kg) pair


DIMENSIONAL DRAWINGS




6.36" (162mm)

Front View


5.68" (144mm) **Side View**



4.527" (115mm)



6.181" (157mm)



6.575" (167mm)

Bracket Back View

Bracket Side View

Bracket Back View

LIMITED FIVE (5) YEAR WARRANTY Sonance warrants to the first end-user purchaser that this Sonance-brand product ("Product"), when purchased from an authorized Sonance Dealer/Distributor, will be free from defective workmanship and materials for the period stated above. Sonance will at its option and expense during the warranty period, either repair the defect or replace the Product with a new or remanufactured Product or a reasonable equivalent. For more details please refer to the product manual.

©2024 Sonance. All rights reserved. Sonance is a registered trademarks of Dana Innovations. Due to continuous product improvement, all features and specifications are subject to change without notice. For the latest Sonance product specification information visit our website at www.sonance.com.