
Polaroid Flip Instant Camera + Color Film Bundle (8 Photos)











Technical Specifications

Product		Polaroid Flip Instant Camera + Color Film Bundle (8 photos)					
Color		PRD	EAN	GTIN			
	Black White		9120134283139 9120134283092	19120134283136 19120134283099			
Launch Date		TBD					
RRP		\$214.99, €224.99, £204.99					
HS or HTS Code		9006409000 (US) 9006400000 (EU)					
Country of Origin		China (CN)					
Packaging Contents		Polaroid Flip Camera Single Pack Color Film for i-Type Neck Strap Quick Start Guide Safety & Compliance Leaflet					
Product Box							
Product Box Weight							
Shipper							
Shipper Weight							
Units per Shipper		6					
Product Dimensions		163.5 x 117.2 x 89.7 mm (lid closed) 163.5 x 117.2 x 121.6 mm (lid open)					
Product Weight		648 grams 22.86 ounces					
Compatible With		i-Type Film 600 Film					
App Enabled		App Enabled Fully control your camera remotely For iOS & Android					
Battery		Lithium-lon Polymer Soft-Pack Battery. Use serviceable					
Battery Report		Av aila bl	е				

Outer Shell	ABS, PC, PN	MMA, Mylar	, Stainless S	Steel		
Shutter System	Fastest shutter speed 1/200, exposure time range is 1/200~30s., and Bulb mode (up to 99hrs.)					
Aperture	Maximum f8.5 practical aperture, available apertures: f8.5 - f66.6 (depending on selected zone)					
Lens	Two-lens structure with 4 zones. Auto- switching hyperfocal optical system.					
Field of View	Horizontal: 39.4º Vertical: 40.8º					
Focal Length	Close-up Lens 1	Near Field Lens 2	Mid Field Lens 3	Far Field Lens 4		
	94.17 mm	97.75 mm	101.4 mm	106.99 mm		
Zonerange	0.4 m - 0.77 m	0.77 m – 1.03 m	1.03 m - 1.68 m	1.68 m - Infinity		
Best focus	.65 m	.85 m	1.2 m	2.5 m		
Ranging system	Ultrasonic sensor (0.4 m – 4 m)					
Light meter	40.8° vertical, 39.4° horizontal. Center- weighted single-zone metering (80% coverage of optical FOV)					
Flash System	Vacuum discharge tube strobe range 4.5m @f8 / 14.76' @f8					
Device Interface Ports	USB Type-C charging input x1					
Display	LED display for modes, film count, battery level.					
Other	Bluetooth Viewfinder scene analysis LED warning Tripod mount Built in lens filter snap/click mount					