

MAG Series

LCD Monitor

MAG 32C6 (3DD4) MAG 32C6X (3DD4)

User Guide

Contents

Getting Started	3
Package Contents	3
Installing the Monitor Stand	4
Adjusting the Monitor	6
Monitor Overview	7
Connecting the Monitor to PC	9
OSD Setup	10
Navi Key	10
Hot Key	10
OSD Menus	11
Gaming	12
Professional	14
Image	15
Input Source	15
Navi Key	16
Settings	16
Specifications	18
Preset Display Modes	20
Standard Default Mode	20
DP OverClocking Mode	21
PIP Mode (Not Support HDR)	22
PBP Mode (Not Support HDR)	23
Troubleshooting	24
Safety Instructions	25
TÜV Rheinland Certification	27
Regulatory Notices	28

Revision

V1.1, 2024/11

Getting Started

This chapter provides you with the information on hardware setup procedures. While connecting devices, be careful in holding the devices and use a grounded wrist strap to avoid static electricity.

Package Contents

Monitor	MAG 32C6	
	MAG 32C6X	
Documentation	Quick Start Guide	
Accessories	Stand	
	Stand Base	
	Screw(s) for Wall Mount Bracket(s)	
	Power Cord	
Cables	DisplayPort Cable (Optional)	




Important

- Contact your place of purchase or local distributor if any of the items is damaged or missing.
- Package contents may vary by country and model.
- The included power cord is exclusively for this monitor and should not be used with other products.

Installing the Monitor Stand

- 1. Leave the monitor in its protective packaging. Align and gently push the stand bracket towards the monitor groove until it locks in place.
- 2. Align and gently push the cable organizer towards the stand until it locks in place.
- 3. Align and gently push the base towards the stand until it locks in place.
- **4.** Make sure the stand assembly is properly installed before setting the monitor upright.





- Place the monitor on a soft, protected surface to avoid scratching the display panel.
- Do not use any sharp objects on the panel.
- The groove for installing the stand bracket can also be used for wall mount. Please contact your dealer for proper wall mount kit.
- This product comes with NO protective film to be removed by the user! Any mechanical damages to the product including removal of the polarizing film may affect the warranty!




Adjusting the Monitor


This monitor is designed to maximize your viewing comfort with its adjustment capabilities.



Avoid touching the display panel when adjusting the monitor.



Monitor Overview





Lit in white after the monitor is turned on. If no signal input, the LED will turn into orange. Lit in orange when the monitor is in Stand-by mode.

- 2 Power Button
- 3 Kensington Lock
- 4 Power Jack
- 5 HDMI™ Connector HDMI™ (for MAG 32C6)

Supports HDMI™ CEC, 1920x1080@180Hz as specified in HDMI™ 2.0b.



Important

To ensure optimal performance and compatibility, please use only $HDMI^{TM}$ cables certified with the official $HDMI^{TM}$ logo when connecting this monitor. For more information, please visit https://www.hdmi.org/resource/cables.

6 HDMI™ Connector H□∏™ (for MAG 32C6)

Supports 1920x1080@180Hz as specified in HDMI™ 2.0b.



Important

To ensure optimal performance and compatibility, please use only HDMI™ cables certified with the official HDMI™ logo when connecting this monitor. For more information, please visit https://www.hdmi.org/resource/cables.

The HDMI™ Connector Harmon INTERACE (for MAG 32C6X)

Supports HDMITM CEC, 1920x1080@240Hz as specified in HDMITM 2.0b.



Important

To ensure optimal performance and compatibility, please use only HDMI™ cables certified with the official HDMI™ logo when connecting this monitor. For more information, please visit https://www.hdmi.org/resource/cables.

8 HDMITM Connector Hamilton MITTERAGE (for MAG 32C6X)

Supports 1920x1080@240Hz as specified in HDMI™ 2.0b.



Important

To ensure optimal performance and compatibility, please use only $HDMI^{TM}$ cables certified with the official $HDMI^{TM}$ logo when connecting this monitor. For more information, please visit $\frac{https://www.hdmi.org/resource/cables}{https://www.hdmi.org/resource/cables}$.


DisplayPort (for MAG 32C6)

DisplayPort (for MAG 32C6X)

- $Supports\ 1920x1080@180Hz\ as\ specified\ in\ DisplayPort\ 1.4.$
- Supports 1920x1080@250Hz as specified in DisplayPort 1.4.
- 11 Headphone Jack

Connecting the Monitor to PC

- **1.** Turn off your computer.
- 2. Connect the video cable from the monitor to your computer.
- **3.** Connect the power cord to the monitor power jack. (Figure A)
- 4. Plug the power cord into the electrical outlet. (Figure B)
- **5.** Turn on the monitor. (Figure C)
- **6.** Power on the computer and the monitor will auto detect the signal source.



OSD Setup


This chapter provides you with essential information on OSD Setup.



All information is subject to change without prior notice.

Navi Key

The monitor comes with a Navi Key, a multi-directional control that helps navigate the On-Screen Display (OSD) menu.



Up/ Down/ Left/ Right:

- selecting function menus and items
- adjusting function values
- entering into/exiting from function menus

Press (OK):


- launching the On-Screen Display (OSD)
- · entering submenus
- confirming a selection or setting

Hot Key


- Users may enter into preset function menus by moving the Navi Key up, down, left or right when the OSD menu is inactive.
- Users may customize their own Hot Keys to enter into different function menus.

OSD Menus

MAG 32C6



MAG 32C6X





The following settings will be grayed out when HDR signals are received:

- Night Vision
- MPRT
- Low Blue Light
- HDCR

- Brightness
- Contrast
- Color Temperature
- Al Vision

Gaming

1st Level Menu	2nd/3rd Lev	el Menu	Description		
Game Mode	User			Use Up or Down Button to select and preview	
	FPS		mode effects.	to an Common describe	
	Racing		 Press the OK Button your mode type. 	to confirm and apply	
	RTS				
	RPG				
Night Vision	OFF		This function optimiz		
	Normal		brightness and is red games.	commended for FPS	
	Strong				
	Strongest				
	A.I.				
Al Vision	OFF		Al Vision enhances in		
	ON		optimizing the contra background brightne		
			Activating Al Vision v		
			Affected Function	Function Status	
			» Night Vision		
			» HDCR	Unable to select	
			» Brightness » MPRT	Set to OFF	
-					
Response Time	Normal		Setting to Fastest will reach the shortest response time and help improve blurred images when playing very fast games.		
	Fast				
	Fastest		MDDT: "III		
MPRT	OFF		MPRT is available when the refresh rate is over 85 Hz. Activating MPRT will affect:		
	ON				
			Affected Function	Function Status	
			» Brightness	Unable to select	
			» Response Time » HDCR		
			» Adaptive-Sync	Set to OFF	
D (1 D)	1			· 00014 D - 11	
Refresh Rate	Right Top Left Bottom		Location is adjustable in OSD Menu. Press the OK Button to confirm and apply your Refresh Rate Location. This monitor follows and works at the Operating System's preset Screen Refresh		
		Right Bottom	Rate.		
	055	Customize			
	ON				

		el Menu	Description	
Alarm Clock	Location	Left Top		, press the OK Button to
		Right Top	activate the timer. • Users have to manually restore their pre	Uv rostoro thoir procet
		Left Bottom	Alarm Clock after any	
		Right Bottom	reconnection.	
		Customize		
	0FF			
	15:00	00:01 ~ 99:59		
	30:00			
	45:00			
	60:00			
Screen Assistance	None		Users can adjust Scre	en Assistance in any
(for MAG 32C6)	гја г	7	mode.	
	L ⁺ J L	*_		
		-		
	нан н	⋄ н		
	t .	t ,		
		•<		
	A .	•		
	(-)	<u>.</u>)		
Screen Assistance	Icon	None		
(for MAG 32C6X)				
		[+] [+]		
		!!		
		1 1		
		HÎH HÎH		
		>< ><		
		^ ^		
		<u> </u>		
		(-) (-)		
	Position			
	Reset			
Adaptive-Sync	0FF		Adaptive-Sync preven	-
	ON		Activating Adaptive-S	
			» MPRT	Function Status Set to OFF
			L» MLLI	Jet to OFF

Professional

1st Level Menu	2nd Level Menu	Description	
Pro Mode	Eco User Anti-Blue Movie Office sRGB	Use Up or Down Button to select and preview mode effects. Press the OK Button to confirm and apply your mod type.	
Low Blue Light	OFF ON	Low Blue Light protects your eyes against blue light. When enabled, Low Blue Light adjusts the screen colo temperature to a more yellow glow. When Pro Mode is set to Anti-Blue, it is mandatory to enable Low Blue Light.	
HDCR	OFF ON	HDCR enhances image quality by increasing the contrast of images. Activating HDCR will affect:	
		Affected Function » Brightness » MPRT	Function Status Unable to select Set to OFF
MPRT	OFF	MPRT is available wh Activating MPRT will a	
		Affected Function » Brightness » Response Time	Unable to select
	ON	» HDCR » Adaptive-Sync	Set to OFF
Image Enhancement	OFF Weak Medium Strong	Image Enhancement enhances image edges to their acutance.	
	Strongest]	

Image

1st Level Menu	2nd/3rd Level Menu		Description
Brightness	0-100		Properly adjust Brightness according to the surrounding lighting.
Contrast	0-100		Properly adjust Contrast to relax your eyes.
Sharpness	0-5		Sharpness improves clarity and details of images.
Color Temperature	Cool		Use Up or Down Button to select and
	Normal		preview mode effects.
	Warm		 Press the OK Button to confirm and apply your mode type.
	Customization	R (0-100)	Users can adjust Color Temperature in
		G (0-100)	- Customization mode.
		B (0-100)	
Screen Size	Auto		Users can adjust Screen Size in any mode,
	4:3		any resolution and any screen refresh rate.
	16:9		

Input Source

1st Level Menu	2nd Level Menu	Description	
HDMI™1		Users can adjust Input Source in any mode.	
HDMI™2			
DP			
Auto Scan	OFF	Users can use the Navi Key to select Input Source at	
	ON	below status:	
	OIV	 While "Auto Scan" is set to "OFF" with the monitor at power saving mode; 	
		While "No Signal" message box is shown on the monitor.	

Navi Key

1st Level Menu	2nd Level Menu	Description
Up	OFF	All Navi Key items can be adjusted via OSD Menus.
Down	Brightness	
Left Right	Game Mode	
Right	Screen Assistance	
	Alarm Clock	
	Input Source	
	PIP/PBP	
	(for MAG 32C6X)	
	Refresh Rate	
	Info. On Screen	
	Night Vision	

Settings

1st Level Menu	2nd/3rd Level Menu	Description
Language	繁體中文	Users have to press the OK Button to confirm and
	English	apply the Language setting. • Language is an independent setting. Users' own
	Français	language setting will override the factory. When
	Deutsch	users set Reset to Yes, Language will not be changed.
	Italiano	
	Español	
	한국어	
	日本語	
	Русский	
	Português	
	简体中文	
	Bahasa Indonesia	
	Türkçe	
	(More languages coming soon)	
Transparency	0~5	Users can adjust Transparency in any mode.
OSD Time Out	5~30s	Users can adjust OSD Time Out in any mode.
Power Button	OFF	When set to OFF, users can press the power button to turn off the monitor.
	Standby	When set to Standby, users can press the power button to turn off the panel and backlight.

1st Level Menu	2nd/3rd Level Menu	Description
Info. On Screen	OFF	The information of the monitor status will be shown
	ON	on the right side of the screen.
DP OverClocking	OFF	The information of the monitor status will be shown
(for MAG 32C6X)	ON	on the right side of the screen.
HDMI™ CEC	OFF	HDMI™ CEC (Consumer Electronics Control)
	ON	 supports Sony PlayStation®, Nintendo® Switch™, Xbox Series X S consoles and various audio-visual devices that are CEC-capable.
		If HDMI™ CEC is set to 0N:
		The monitor will automatically power on when the CEC device is turned on.
		The CEC device will enter power saving mode when the monitor is turned off.
		 When Sony PlayStation®, Nintendo® Switch™, or Xbox Series XIS console is connected, Game Mode and Pro Mode will be automatically set to default modes and can be adjusted to users' preferred modes later.
Reset	YES	Users can Reset and restore settings to original OSD
	NO NO	Default in any mode.

Specifications

Monitor	MAG 32C6	MAG 32C6X	
Size	31.5 inch		
Curvature	Curve 1500R		
Panel Type	Rapid VA		
Resolution	1920x1080 (FHD)		
Aspect Ratio	16:9		
Brightness	Typical SDR: 250 nits		
	• Peak HDR: 250 nits		
Contrast Ratio	3000:1		
Refresh Rate	180Hz	250Hz	
Response Time	1ms (MRPT)	,	
	4ms (GTG)		
1/0	DisplayPort x1		
	• HDMI™ Connector x2		
	• Headphone Jack x1		
View Angles	178°(H), 178°(V)		
DCI-P3*/ sRGB	78% / 101%		
Surface Treatment	Anti-glare Anti-glare		
Display Colors	1.07B, 10bits (8bits + FRC)		
Monitor Power Options	100~240Vac, 50/60Hz, 1.5A		
Power Consumption	Power On < 26W		
(Typical)	Standby < 0.5W		
	Power Off < 0.3W		
Adjustment (Tilt)	-5° ~ 20°	-5° ~ 20°	
Kensington Lock	Yes		
VESA Mounting	• Plate Type: 100 x 100 mm		
	• Screw Type: M4 x 10 mm		
	• Thread Diameter: 4 mm		
	Thread Pitch: 0.7 mm		
	Thread Length: 10 mm		
Dimension (W x H x D)	709.4 x 507.2 x 249.8 mm		
Weight Net	5.29 kg	5.35 kg	
Gross	8.39 kg	8.47 kg	

Monitor		MAG 32C6 MAG 32C6X	
Environment	Operating	• Temperature: 0°C to 40°C	
		Humidity: 20% to 90%, non-condensing	
		• Altitude: 0 ~ 5000m	
	Storage	• Temperature: -20°C to 60°C	
		Humidity: 10% to 90%, non-condensing	

^{*} Based on CIE1976 test standards.

Preset Display Modes



All information is subject to change without prior notice.

Standard Default Mode

	Resolution		MAG 32C6 MAG 32C6X	
Standard				
			HDMI™	DP
VGA	640x480	@60Hz	V	V
		@67Hz	٧	V
		@72Hz	٧	V
		@75Hz	V	V
SVGA	800x600	@56Hz	٧	V
		@60Hz	٧	V
		@72Hz	٧	V
		@75Hz	٧	V
XGA	1024x768	@60Hz	٧	V
		@70Hz	٧	V
		@75Hz	٧	V
SXGA	1280x1024	@60Hz	٧	V
		@75Hz	٧	V
WXGA+	1440x900	@60Hz	٧	V
WSXGA+	1680x1050	@60Hz	٧	V
Full HD	1920x1080	@60Hz	٧	V
		@85Hz	٧	V
		(for MAG 32C6X)		
		@120Hz		V
		(for MAG 32C6)		
		@144Hz	V	V
		(for MAG 32C6)		
		@165Hz	٧	V
		@180Hz	V	V
		(for MAG 32C6)		
		@240Hz	٧	V
		(for MAG 32C6X)		

Standard	Resolution		MAG 32C6 MAG 32C6X	
			HDMI™	DP
Video Timing Resolution	480P		V	V
	576P		٧	V
	720P		٧	V
	1080P	@50Hz	٧	V
		@60Hz	٧	V
		@120Hz	٧	
	HDMI™ VRR Function		٧	

DP OverClocking Mode

Standard	Resolution		MAG 32C6X	
Standard			HDMI™	DP
VGA	640x480	@60Hz		V
		@67Hz		V
		@72Hz		V
		@75Hz		V
SVGA	800x600	@56Hz		V
		@60Hz		V
		@72Hz		V
		@75Hz		V
XGA	1024x768	@60Hz		V
		@70Hz		V
		@75Hz		V
SXGA	1280x1024	@60Hz		V
		@75Hz		V
WXGA+	1440x900	@60Hz		V
WSXGA+	1680x1050	@60Hz		V
Full HD	1920x1080	@60Hz		V
		@85Hz		V
		@165Hz		V
		@240Hz		V
		@250Hz		V

Standard	Resolution		MAG 32C6X	
Stallual u			HDMI™	DP
Video Timing	480P			V
Resolution	576P			V
	720P			V
	1080P	@50Hz		V
		@60Hz		V
		@120Hz		V

PIP Mode (Not Support HDR)

Standard	Resolution		MAG 32C6X	MAG 32C6X	
Standard			НДМІ™	DP	
VGA	640x480	@60Hz	V	V	
		@67Hz	V	V	
		@72Hz	V	V	
		@75Hz	V	V	
SVGA	800x600	@56Hz	V	V	
		@60Hz	V	V	
		@72Hz	V	V	
		@75Hz	V	V	
XGA	1024x768	@60Hz	V	V	
		@70Hz	V	V	
		@75Hz	V	V	
SXGA	1280x1024	@60Hz	V	V	
		@75Hz	V	V	
WXGA+	1440x900	@60Hz	V	V	
WSXGA+	1680x1050	@60Hz	V	V	
	1920 x 1080	@60Hz	V	V	
Video Timing	480P		V	V	
Resolution	576P		V	V	
	720P		V	V	
	1080P	@60Hz	V	V	

PBP Mode (Not Support HDR)

Class Is and	Resolution		MAG 32C6X	
Standard			HDMI™	DP
VGA	640x480	@60Hz	V	V
		@67Hz	V	V
		@72Hz	V	V
		@75Hz	V	V
SVGA	800x600	@56Hz	V	V
		@60Hz	V	V
		@72Hz	V	V
		@75Hz	V	V
XGA	1024x768	@60Hz	V	V
		@70Hz	V	V
		@75Hz	V	V
SXGA	1280x1024	@60Hz	V	V
		@75Hz	V	V
WXGA+	1440x900	@60Hz	V	V
WSXGA+	1680x1050	@60Hz	V	V
Video Timing Resolution	480P		V	V
	576P		V	V
	720P		V	V
PBP Full Screen Timing	960x1080	@60Hz	V	V

^{*} HDMITM VRR (Variable Refresh Rate) synchronizes with Adaptive-Sync (ON/ OFF).

^{*} Users have to set DP OverClocking to ON. This is the highest refresh rate supported by DP OverClocking. If any monitor error occurs during overclocking, please downscale the refresh rate. (for MAG 32C6X)

Troubleshooting

The power LED is off.

- Press the monitor power button again.
- Check if the monitor power cable is properly connected.

No image.

- Check if the computer graphics card is properly installed.
- Check if the computer and monitor are connected to electrical outlets and are turned on.
- Check if the monitor signal cable is properly connected.
- The computer may be in Standby mode. Press any key to activate the monitor.

The screen image is not properly sized or centered.

 Refer to Preset Display Modes to set the computer to a setting suitable for the monitor to display.

No Plug & Play.

- Check if the monitor power cable is properly connected.
- Check if the monitor signal cable is properly connected.
- Check if the computer and graphics card are Plug & Play compatible.

The icons, font or screen are fuzzy, blurry or have color problems.

- · Avoid using any video extension cables.
- · Adjust brightness and contrast.
- Adjust RGB color or tune color temperature.
- Check if the monitor signal cable is properly connected.
- Check for bent pins on the signal cable connector.

The monitor starts flickering or shows waves.

- Change the refresh rate to match the capabilities of your monitor.
- Update your graphics card drivers.
- Keep the monitor away from electrical devices that may cause electromagnetic interference (EMI).

Safety Instructions

- Read the safety instructions carefully and thoroughly.
- All cautions and warnings on the device or User Guide should be noted.
- Refer servicing to qualified personnel only.

Power

- Make sure that the power voltage is within its safety range and has been adjusted properly to the value of 100~240V before connecting the device to the power outlet.
- If the power cord comes with a 3-pin plug, do not disable the protective earth pin from the plug. The device must be connected to an earthed mains socket-outlet.
- Please confirm the power distribution system in the installation site shall provide the circuit breaker rated 120/240V, 20A (maximum).
- Always disconnect the power cord or switch the wall socket off if the device would be left unused for a certain time to achieve zero energy consumption.
- Place the power cord in a way that people are unlikely to step on it. Do not place anything on the power cord.
- If this device comes with an adapter, use only the MSI provided AC adapter approved for use with this device.

Environment

- To reduce the possibility of heat-related injuries or of overheating the device, do not place the device on a soft, unsteady surface or obstruct its air ventilators.
- Use this device only on a hard, flat and steady surface.
- To prevent the device from tipping over, secure the device to a desk, wall or fixed object with an anti-tip fastener that helps to properly support the device and keep it safe in place.
- To prevent fire or shock hazard, keep this device away from humidity and high temperature.
- Do not leave the device in an unconditioned environment with a storage temperature above 60°C or below -20°C, which may damage the device.
- The maximum operating temperature is around 40°C.
- When cleaning the device, be sure to remove the power plug. Use a piece of soft cloth rather than industrial chemical to clean the device. Never pour any liquid into the opening; that could damage the device or cause electric shock.
- Always keep strong magnetic or electrical objects away from the device.

- If any of the following situations arises, get the device checked by service personnel:
 - The power cord or plug is damaged.
 - Liquid has penetrated into the device.
 - The device has been exposed to moisture.
 - The device does not work well or you can not get it working according to the User Guide.
 - The device has dropped and damaged.
 - The device has obvious sign of breakage.

TÜV Rheinland Certification

TÜV Rheinland Low Blue Light Certification

Blue light has been shown to cause eye fatigue and discomfort. MSI now offers monitors with TÜV Rheinland Low Blue Light certification to ensure users' eye comfort and well-being. Please follow the instructions below to reduce the symptoms from extended exposure to the screen and blue light.



- Place the screen 20 28 inches (50 70 cm) away from your eyes and a little below eye level.
- Consciously blinking the eyes every now and then will help to reduce eye strain after extended screen time.
- Take breaks for 20 minutes every 2 hours.
- Look away from the screen and gaze at a distant object for at least 20 seconds during breaks.
- Make stretches to relieve body fatigue or pain during breaks.
- Turn on the optional Low Blue Light function.

TÜV Rheinland Flicker Free Certification

 TÜV Rheinland has tested this product to ascertain whether the display produces visible and invisible flicker for the human eye and therefore strains the eyes of users.



- TÜV Rheinland has defined a catalogue of tests, which sets out minimum standards at various frequency ranges. The test catalogue is based on internationally applicable standards or standards common within the industry and exceeds these requirements.
- The product has been tested in the laboratory according to these criteria.
- The keyword "Flicker Free" confirms that the device has no visible and invisible flicker defined in this standard within the range of 0 3000 Hz under various brightness settings.
- The display will not support Flicker Free when Anti Motion Blur/MPRT is enabled.
 (The availability of Anti Motion Blur/MPRT varies by products.)

Regulatory Notices

CE Conformity

This device complies with the requirements set out in the Council Directive on the Approximation of the Laws of the Member States relating to Electromagnetic Compatibility [2014/30/EU], Low-voltage Directive [2014/35/EU], ErP Directive [2009/125/EC] and RoHS directive [2011/65/EU]. This product has been tested and found to comply with the harmonized standards for Information Technology Equipment published under Directives of Official Journal of the European Union.

FCC-B Radio Frequency Interference Statement

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the measures listed below:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected
- Consult the dealer or an experienced radio/television technician for help.

Notice 1

The changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Notice 2

Shielded interface cables and AC power cord, if any, must be used in order to comply with the emission limits.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- 1. This device may not cause harmful interference, and
- 2. This device must accept any interference received, including interference that may cause undesired operation.

MSI Computer Corp.

901 Canada Court, City of Industry, CA 91748, USA (626) 913-0828

www.msi.com

WEEE Statement

Under the European Union ("EU") Directive on Waste Electrical and Electronic Equipment, Directive 2012/19/EU, products of "electrical and electronic equipment" cannot be discarded as municipal waste anymore and manufacturers of covered electronic equipment will be obligated to take back such products at the end of their useful life.



Chemical Substances Information

In compliance with chemical substances regulations, such as the EU REACH Regulation (Regulation EC No. 1907/2006 of the European Parliament and the Council), MSI provides the information of chemical substances in products at: https://csr.msi.com/global/index

RoHS Statement

Japan JIS C 0950 Material Declaration

A Japanese regulatory requirement, defined by specification JIS C 0950, mandates that manufacturers provide material declarations for certain categories of electronic products offered for sale after July 1, 2006.

https://csr.msi.com/global/Japan-JIS-C-0950-Material-Declarations

India RoHS

This product complies with the "India E-waste (Management and Handling) Rule 2016" and prohibits use of lead, mercury, hexavalent chromium, polybrominated biphenyls or polybrominated diphenyl ethers in concentrations exceeding 0.1 weight % and 0.01 weight % for cadmium, except for the exemptions set in Schedule 2 of the Rule.

Turkey EEE Regulation

Conforms to the EEE Regulations of the Republic Of Turkey

Ukraine Restriction of Hazardous Substances

The equipment complies with requirements of the Technical Regulation, approved by the Resolution of Cabinet of Ministry of Ukraine as of 10 March 2017, \mathbb{N}^2 139, in terms of restrictions for the use of certain dangerous substances in electrical and electronic equipment.

Vietnam RoHS


As from December 1, 2012, all products manufactured by MSI comply with Circular 30/2011/TT-BCT temporarily regulating the permitted limits for a number of hazardous substances in electronic and electric products.

Green Product Features

- Reduced energy consumption during use and stand-by
- Limited use of substances harmful to the environment and health
- · Easily dismantled and recycled
- Reduced use of natural resources by encouraging recycling
- · Extended product lifetime through easy upgrades
- Reduced solid waste production through take-back policy

Environmental Policy

- The product has been designed to enable proper reuse of parts and recycling and should not be thrown away at its end of life.
- Users should contact the local authorized point of collection for recycling and disposing of their end-of-life products.





 Users may also reach us at gpcontdev@msi.com for information regarding proper disposal, take-back, recycling, and disassembly of MSI products.

Warning!

Overuse of screens is likely to affect eyesight.

Recommendations:

- 1. Take a 10-minute break for every 30 minutes of screen time.
- 2. Children under 2 years of age should have no screen time. For children aged 2 years and over, screen time should be limited to less than one hour per day.

Copyright and Trademarks Notice

msi MsI 微星





Copyright © Micro-Star Int'l Co., Ltd. All rights reserved. The MSI logo used is a registered trademark of Micro-Star Int'l Co., Ltd. All other marks and names mentioned may be trademarks of their respective owners. No warranty as to accuracy or completeness is expressed or implied. MSI reserves the right to make changes to this document without prior notice.



The terms HDMI™, HDMI™ High-Definition Multimedia Interface, HDMI™ Trade dress and the HDMI™ Logos are trademarks or registered trademarks of HDMI™ Licensing Administrator, Inc.

Technical Support

If a problem arises with your product and no solution can be obtained from the user's manual, please contact your place of purchase or local distributor. Alternatively, please visit https://www.msi.com/support/ for further guidance.