

Pre-Launch

NEXT GENERATION 4K ULTRA HIGH DEFINITION HOME THEATER PROJECTOR

UHD60

Optoma

Bring the Ultimate 4K Experience Home with the Optoma UHD60



Native 4K UHD 3840x2160 2160p resolution, bright 3000 lumens, and cinematic color



HDR-Compatible - HDR10 produces the brightest whites, deepest blacks, and life-like color that is beautiful and striking, all courtesy of the REC.2020 wide color gamut and DCI-P3 color gamut coverage



Dynamic Black delivers 1,000,000:1 contrast ratio for exceptional black levels



HDMI 2.0 and HDCP 2.2 deliver a full 18Gbps for the best 4K UHD video bandwidth, image quality and device compatibility



Vertical Lens Shift and 1.6x zoom provide an intuitive and flexible installation



UltraDetail allows fine adjustments to image clarity and sharpness resulting in a clear and highly detailed image



2 x 4W Stereo Speakers and Optical output to AV Receiver deliver crisp and sharp audio

TRUE 4K

4K
ULTRA HD

2160P

HDR
COMPATIBLE

HDMI™
HIGH DEFINITION MULTIMEDIA INTERFACE

HDCP 2.2

WIDESCREEN
16:9
ENHANCED



UHD60 is a state of the art 4K Ultra High Definition (UHD) Projector for home cinema and home theater capable of delivering ultra sharp images with a high level of detail and breathtaking color. With 4 times the pixels of 1080p, an Ultra High Resolution of 3840x2160, 3000 lumens, 1,000,000:1 contrast ratio, High Dynamic Range in the form of HDR10, vertical lens shift and a massive 1.6x Zoom, the Optoma UHD60 has been engineered to deliver the ultimate 4K UHD home viewing experience. The Optoma UHD60 is powered by a revolutionary Texas Instruments 4K DLP UHD Chipset with a high performance DMD utilizing XPR video processing technology with fast switching to display 8.3 million "distinct" pixels as mandated by the Consumer Technology Association's 4K UHD 2160p specification.

The UHD60 can project 4K UHD images up to 140 inches, allowing viewers to be in optimum viewing area to enjoy all 4K UHD pixels, from a distance of up to 11 feet. The average 55-75 inch 4K UHD TV simply cannot match this, as viewers typically sit further away from their TV than the optimum viewing area of 4-6 feet. High Dynamic Range, also known as HDR is the true star of the 4K UHD show. HDR leverages REC.2020 wide color gamut and DCI-P3 color gamut coverage to deliver super luminous levels of white, the deepest black levels, and beautifully striking like-life real world color that was previously only possible in the Cinema.

A generous 15% vertical lens shift and 1.6x optical zoom provide a great deal of flexibility in terms of installation location within any home, while dual 4W stereo speakers generate audio that is loud and crisp. The lamp life on the UHD60 is a robust 10,000 hours in ECO mode and 15,000 hours in Dynamic mode.

CONNECTIVITY (May require optional accessories)



4K UHD Blu-ray Player



4K Game Console



4K Media Streaming



Computers

4K ULTRA HIGH DEFINITION HOME THEATER PROJECTION – UHD60

OPTICAL/TECHNICAL SPECIFICATIONS

Display Technology	"Single 0.66" TRP S610 4K UHD DMD DLP® Technology by Texas Instruments™
Color Wheel	RGBCY 5 Segment color wheel
Native Resolution	4K UHD 3840x2160 @ 60Hz with XPR Technology
Maximum Resolution	4K 4096x2160 @ 60Hz with XPR Technology
4K UHD Upscale Conversion	Upscales non-4K UHD resolutions (WXGA, 720p, 1080p, WUXGA, 1440p) and frame rates to 2160p 60Hz (4K UHD)
Brightness	3000 Lumens
Contrast Ratio	Up to 1,000,000:1 with Dynamic Black
REC.709 Color Gamut	REC.709 color gamut provides rich accurate color based on the HDTV Broadcast Specification. REC.709 will be used with all non-HDR content.
HDR (High Dynamic Range)	HDR Compatible (decode HDR10 metadata) / 4 Picture Modes: Normal, Bright, Detail, Film
HDR Wide Color Gamuts (REC.2020 and DCI-P3)	The RGB primaries (real color) utilized in REC.2020 (BR.2020) wide color gamut and DCI-P3 color gamut coverage is the equivalent to those used in the CIE 1931 color space (CIE 1931 color space defines links between "pure physical colors" and "perceived" colors of human vision). REC.2020 will be used anytime the source content contains HDR metadata.
HDR Compatibility	HDR Source: 4K UHD Blu-Ray Player (such as the Samsung UBD-K8500 Ultra), 4K UHD Streaming Media Device (such as the Roku 4K Ultra), Xbox One S (4K UHD Blu-ray, 4K Media Streaming, & Games), or PS4 Pro (4K Media Streaming and Games only) HDR Content: HDR 4K UHD Blu-ray Disc, HDR Xbox One S Game, HDR PS4 Pro Game, or 4K HDR Media Streaming Service such as Amazon 4K UHD HDR Video, Netflix 4K UHD HDR Video, or Hulu 4K UHD HDR Video
SDR to HDR (HDR Emulation, apply HDR to non-HDR content)	HDR Effects for non-HDR Content / 4 Effects: Normal, Bright, Detail, Film
UltraDetail	Enhances image quality by improving image depth and clarity. 3 level to choose from.
Color Depth	3840x2160 @30Hz YUV 4:4:4 (8bit, 10bit, 12bit), YUV 4:2:2 (8bit, 10bit, 12bit), YUV 4:2:0 (8bit, 10bit, 12bit) 3840x2160 @60Hz YUV 4:4:4 (8bit), YUV 4:2:2 (8bit), YUV 4:2:0 (8bit, 10bit, 12bit)
Lamp Life and Type*	4000/10000/15000 (Bright/ECO/Dynamic)
Projection Method	Front, rear, ceiling mount, table top
Vertical Lens Shift	15% offset (with tolerance +/- 5%)
Uniformity	65%
Offset	100% (see Vertical Lens Shift above)
Aspect Ratio	16:9 (native), 4:3, Auto, LBX (2160p and 1080p)
Throw Ratio	1.39 - 2.22 (with tolerance +/- 5%)
Projection Distance	4.2' - 30.5'
Image Size	26.45" - 302.2" (26.45" to 140" optimal image size)
Projection Lens	F=2.5~ 3.26, f=20.91 ~ 32.62 mm manual focus
Optical Zoom	1.6x
Digital Zoom	0.8 - 2.0
Audio	2x4W Stereo Speakers
Noise Level	28/25dB (Bright/ECO)
Remote Control	Full Function Home Remote Control
Operating Temperature	41–104°F (5–40°C), 85% max humidity
Power Supply	AC input 100–240V, 50–60Hz, auto-switching
Power Consumption	317W Typical (Bright mode), 348W Max (Bright mode), 259W Typical (Eco+ mode), 285W Max (Eco+ mode)
High Altitude	Operating Temp @ Sea Level to 10000 feet = 23C (max); must manually switch to high altitude mode @ 5000 feet & above (using OSD)


COMPATIBILITY SPECIFICATIONS

Computer Compatibility	UHD 2160p, WUXGA, HDTV 1080p, UXGA, SXGA, WXGA+, WXGA (1366x768), WUXGA, HDTV (720p), XGA, SVGA, VGA, PC and Mac compatible
Video Compatibility	UHD 2160p (24/50/60Hz), 1080p (24/50/60Hz), 1080i (50/60Hz), 720p (50/60Hz), 480i/p, 576i/p
Vertical Scan Rate	24Hz to 120Hz
Horizontal Scan Rate	31.000 to 135.000KHz
User Controls	Complete on-screen menu adjustment in 10 languages
I/O Connection Ports	1xHDMI 1.4a, 1xHDMI 2.0 (w/ HDCP 2.2, MHL 2.1 and Full 18Gbps), VGA-In, Audio-In (3.5mm), Audio-Out, SDPIF Out (Optical), USB 2.0 Port (Service), USB-A Power, RJ45, RS232C
Loop Through (Audio)	Audio Pass Thru via HDMI to 3.5mm Audio Out and Optical Out (AC3 Dolby Digital, Dolby Digital Plus, DTS)

PHYSICAL SPECIFICATIONS

Security	Kensington® lock port, password (OSD)
Weight	16lbs
Dimensions (W x H x D)	19.6" x 13" x 6"

*Light source life is dependent upon many factors, including brightness mode, display mode, usage, environmental conditions and more. Light source brightness can decrease over time.



Warranty

2 Year Limited Warranty/90 Days Lamp

What's in the Box

UHD60, lens cap, AC power cord, HDMI cable, remote control, batteries for remote, multilingual CD-ROM, user's manual, quick start card, and warranty card

Optional Accessories

Mount

Accessory Part Numbers

Lamp: BL-FP240D

Remote: SP.8ZE01GC01

Mount: BM-5001U, OCM815B, OCM818B-RU

UPC 796435 81 264 5

www.OptomaUSA.com

Optoma

Copyright © 2017 Optoma Technology, Inc. DLP® and the DLP logo are registered trademarks of Texas Instruments™. All other trademarks are the property of their respective owners. All specifications subject to change at any time. 08205015