

## G 5008 SCU Active

Built-under dishwashers

in tried-and-tested Miele quality at an affordable entry-level price.



- QuickIntenseWash, superior cleaning and drying in under 60 min
- Save up to 50% electricity with the Miele hot water connection
- Flexible basket design perfect for everyday use – Comfort baskets
- Very easy door opening and closing – ComfortClose
- More flexibility and space for your dishware – height-adjustable upper basket

EAN: 4002516523550 / Material number: 11966810 /  
Old Material Number: 21500837USA

<b>Type</b>	
Pre-finished	•
24 inch dishwasher	•
<b>Design</b>	
Fascia color	Clean Touch Steel
Fascia panel version	Straight fascia
Control type	Programme selector button
Control panel	3-digit 7-segment display
Display color	Yellow
<b>Convenience</b>	
Door closing aid	AutoClose
Operating noise dB(A) re 1 pW	44
Countdown indicator	•
Delay start up to 24 hours	•
In-operation indication	Display
<b>Efficiency and sustainability</b>	
Noise emissions in dB(A)	44
EcoPower Technology	•
Proven hygiene	•
Hot water connection	•
Half load	•
Energy Star	•
<b>Quality of results</b>	
Fresh water dishwasher	•
<b>Wash programs</b>	
QuickIntenseWash	•
Normal	•
Pots & Pans	•
SaniWash	•
Rinse & Hold	•
<b>Dishwashing options</b>	
Short	•
Extra Clean	•
Extra dry	•
<b>Baskets</b>	
Cutlery loading	Cutlery Tray
FlexCare cup rack	1
Basket design	Comfort
<b>Safety</b>	
Waterproof system	•
Child Safety lock	•
<b>Technical data</b>	
Niche width min in in.(mm)	23 5/8 (600)
Niche width max in in.(mm)	23 5/8 (600)
Niche height min in in.(mm)	33 3/4 (855)
Niche height max in in.(mm)	36 1/4 (920)
Niche depth in in.(mm)	22 1/2 (570)
Appliance width in in.(mm)	23 5/8 (598)

## G 5008 SCU Active

Built-under dishwashers

in tried-and-tested Miele quality at an affordable entry-level price.



EAN: 4002516523550 / Material number: 11966810 /  
Old Material Number: 21500837USA

Appliance height in in.(mm)	33 3/4 (855)
Appliance depth in in.(mm)	22 1/2 (570)
Appliance depth with door open in in.(cm)	47 1/2 (120.5)
Net weight in lbs. (kg)	102 (46.0)
Total connected load in kW	1.40
Voltage in V	120
Fuse rating in A	15
Number of phases	1
Electrical frequency standard	60
Length of water inlet hose in ft (m)	5 (1.50)
Length of water drain hose in ft (m)	5 (1.50)
Length of electrical wire in ft (m)	4 (1.20)

### Standard accessories

Voucher for 1 x box of UltraTabs (20 tabs) or 3 boxes (60 tabs in each) at a reduced price

•