



CPS175PSU Mobile Power Inverter

Offering household power on the go.

The CyberPower 175 Power Inverter (CPS175PSU) converts power from your vehicle's 12V DC power outlet to simultaneously power up to three devices (175 watt peak) with its two household AC outlets and one 2.1-Amp USB port. Use the AC outlets to power portable electronics while you're traveling. The 2.1-Amp USB port quickly charges a tablet, smartphone or any other USB-powered device. The slim design makes it easy to carry and is a perfect power accessory for your next road trip.

Safety features such as a 15-Amp fuse, surge protection, and automatic shutdown protect your connected devices from power surges and automotive battery from power drain. The CyberPower 175, which comes with a two-foot power cord and a DC power plug, is ideal for powering mobile devices and office electronics while you're traveling.

A Two-Year Warranty ensures that this product has passed our highest quality standards in design, assembly, material and workmanship.

Typical Applications

- Tablets
- Laptops
- Smartphones

Features

- 175W Power Inverter
- Quick Charge Technology
- Built-in Surge Protection
- (1) USB 2.1 Amp Charging Port
- (1) 120Vac Outlet
- Soft Start Technology
- 2-Year Warranty

CPS175PSU Mobile Power Inverter

Offering household power on the go.

GENERAL	
Product Type	Power Inverter
INPUT	
Voltage	11.0Vdc - 15.0Vdc
Plug Type	12Vdc Auto Power Port
Cord Length	2'
OUTPUT	
Watts - Continuous	120
Watts - Peak	175
On Battery Voltage	120Vac
On Battery Frequency	60Hz
On Battery Waveform	Simulated Sine Wave
Outlets - Total	2
Outlet Type	NEMA 5-15R
USB Charge Port - Total	1
USB Charging Amperage	2.1A
PROTECTION FEATURES	
Low Battery Voltage Shutdown	<11Vdc
High Battery Voltage Shutdown	>15Vdc
High Temp Shutdown	Yes
Overload Shutdown	Yes
INDICATORS	
Power	Green
Fault	Red
PHYSICAL	
Color	Black/Gray/Red
Enclosure Construction	ABS
Dimensions (WxHxD) (in.)	3.54 x 1.36 x 4.32
ENVIRONMENTAL	
Operating Temperature	32°F to 104°F / 0°C to 40°C
Storage Temperature	23°F to 122°F / 0°C to 50°C
CERTIFICATIONS	
Environmental	RoHS Compliant
WARRANTY	
Product Warranty	2 Years Limited