



Healthcare Display

HCU7030 series and HCF8000 Series

Foster a comfortable, patient-centric experience

Modern day hospitals are turning to premium entertainment and infotainment technologies that focus on the patient experience, as well as workflow efficiencies for nursing staff. Samsung's HCU7030 and HCF8000 healthcare series allows for patient-staff connectivity, and gives patients and visitors an experience that makes them feel at home. Equipped with an integrated pillow speaker interface, allowing patients to enjoy clear audio and control of the TV right at their bedside. The displays are UL-certified for safe usage in any hospital or healthcare facility. WebRTC enabled to facilitate secure, real-time communications over the network.

Key features



Crystal Processor 4K

Powerful 4K upscaling delivers any content in up to 4K resolution.



Pro:Idiom™ DRM HD Content Decryption

The HCU7030 and HCF8000 series is equipped with Pro:Idiom MPEG4 technology to offer your patients premium HDTV content from cable, satellite or video-on-demand services with no optional cards or external box needed.



Universal Pillow Speaker Interface

An easy-to-use interface is built right into the TV, to utilize with multiple brands and models of pillow speakers.



UL-Listed for Hospital Use

The Samsung Healthcare Series displays are specifically engineered to meet the stringent requirements for use in hospital environments. They are manufactured in accordance with UL's published and nationally recognized Standards for Safety.



Improved Tizen Enterprise Platform for more streamlined operations.

Samsung's latest Tizen Enterprise Platform allows for greater flexibility for Interactive Patient Care Platform (IPC) solutions, and allows System Integrators to implement the platform without the need for a set-top box.



Samsung's LYNK Cloud Device and Content Management Solution

The HCU7030 and HCF800 are natively compatible with Samsung's LYNK Cloud Solution, allowing IT Managers to control their fleet of displays from virtually anywhere. Premier content management services make it easy to create, schedule and deploy your hospital's information to patients and visitors.

Display Paper Pa	Specifications		HCF8000 HCU7030						
Pelant Engine		Model	32"	43"	50"	55"	65"	75"	
Picture Carby Picture Carb	Display							Crystal UHD 3,840 x 2,160	
MOR	Video	Film Mode	Yes	Yes	Yes	Yes	Yes	Quantum Processor 4K Lite Yes Yes	
Colored Mespa Contract Mespa Contr		HDR (High Dynamic Range) HDR10+	HDR N/A	HDR Support	HDR Support	HDR Support	HDR Support	HDR Support	
Westing Angle (MAY)		Contrast	Mega Contrast 100% Color Volume	Mega Contrast	Mega Contrast	Mega Contrast	Mega Contrast	Yes Mega Contrast Pur Color	
Audio Obest Tooking Stand		Viewing Angle (H/V)	178/178	178/178	178/178	178/178	178/178	178/178 Yes	
Posset P	Audio	Dolby Decoder Object Tracking Sound	Yes N/A	MS12 2CH OTS Lite	MS12 2CH OTS Lite	MS12 2CH OTS Lite	MS12 2CH OTS Lite	MS12 2CH OTS Lite 20W	
Vesa	Audio	Speaker Type Bluetooth Audio	2CH Yes	2CH Yes	2CH Yes	2CH Yes	2CH Yes	2CH Yes	
Mobile to TV. Minroring (DIA)	Vesa	VESA Screw Size	M4	M8	M8	M8	M8	400 x 400 mm M8 20-22	
Voice Guide	Smart Feature	Mobile to TV - Mirroring, DLNA Sound Mirroring	Yes Yes	Yes Yes	Yes Yes	Yes Yes	Yes Yes	Yes Yes	
Caption (Subtitle)		Voice Guide	Voice Guide US English, Mexico Spanish, Canada French, Finnish, German, Greek, Hungarian, Italian, Norwegian, Polish, Portugal Portuguese, Romanian, Slovak, Swedish, Czech, Danish, Dutch, Korear						
FPG CSD Language English, Spanish, French French Fuglish, Spanish, Fuglish Fuglish, Spanish, French Fuglish, Spanish, Fuglish Fuglish, S	General Feature	Caption (Subtitle)	Yes	Yes	Yes	Yes	Yes	Yes Yes Yes	
PyeS Support Pyes		EPG OSD Language	Yes English, Spanish, French	Yes English, Spanish, French	Yes English, Spanish, French	Yes English, Spanish, French	Yes English, Spanish, French	Yes English, Spanish, French	
Samusing LYNK-William Ves	Custom	IPv6 Support	Yes	Yes	Yes	Yes	Yes	Yes Yes ATSC/ClearQAM	
Hospitality PlugAFIndy (Easy Set-up)	Hospitality	Samsung LYNK™ Cloud	Yes	Yes	Yes	Yes	Yes	Yes Yes Yes	
Channel Menu Display		Hospitality Plug&Play (Easy Set-up) Power On Mode	Yes Yes	Yes Yes	Yes Yes	Yes Yes	Yes Yes	Yes Yes Yes	
Hospitality Feature		Channel Menu Display Mixed Channel List (ATSC, DVB-T/						Yes Yes	
Multi-code IR		My Channel	Yes	Yes	Yes	Yes	Yes	Yes Yes	
Make-up Timer (Alarm)			(Extra Accessory RCU Needed)	(Extra Accessory RCU Needed)	(Extra Accessory RCU Needed)	(Extra Accessory RCU Needed)	(Extra Accessory RCU Needed)	Ready (Extra Accessory RCU Needed) Yes	
UL Certification For Hospital Usage Yes Ye		Wake-up Timer (Alarm) Samsung LYNK™ DRM	Yes	Yes	Yes	Yes	Yes	Yes Yes	
Linput and Output		UL Certification For Hospital Usage	Yes	Yes			Yes	Yes Yes Yes	
RF in (Terrestrial/Cable Input/ Satellite Input)	Input and Output	USB Ethernet (LAN)	2	2	2	2	2	2	
RS232 Adapter RS23 Ada		RF In (Terrestrial/Cable Input/						1 1/1 (Common Use For Terrestrial)/0	
Anymet+ (HDMI-CEC) Yes Yes Yes Yes 1/8 (3.5mm) 3-conductor stereo phone pin Yes Yes Yes Yes Yes Yes 1/8 (3.5mm) 3-conductor stereo phone pin Yes			RS232 Adapter	RS232 Adapter	RS232 Adapter	RS232 Adapter	RS232 Adapter	Supports Stereo Jack to RS232 Adapter eARC/ARC	
Stereo phone pin Stereo phon		Anynet+ (HDMI-CEC)	Yes	Yes	Yes	Yes	Yes	Yes (WiFi5) Yes 1/8 (3.5mm) 3-conductor	
Design Bezel Type VNB 3 Bezel-less 4 Beze		RJ12/IR Pass Through	stereo phone pin Yes	stereo phone pin Yes	stereo phone pin Yes	stereo phone pin Yes	stereo phone pin Yes	stereo phone pin Yes	
Power Onsumption (Max) 70 W 125 W 140 W 145 W 195 W 0.5 W 0.	-	Bezel Type	VNB	3 Bezel-less	3 Bezel-less	3 Bezel-less	3 Bezel-less	Titan Gray 3 Bezel-less Yes	
Power Consumption (Typical) 31W 52 W 63 W 68.9 W 81.9 W 723.3 x 477.7 x154.2 mm / 963.9 x 558.9 x 59.6 mm / 1,116.8 x 644.2 x 59.9 mm / 1,230.5 x 707.2 x 59.9 mm / 1,449.4 x 830.3 x 59.9 mm / 1,673.2 x 95.0 mm / 28.5 x 18.8 x 61 in. 37.9 x 22 x 2.3 in. 44 x 25.4 x 2.4 in. 48.4 x 27.8 x 2.4 in. 57 x 32.7 x 2.4 in. 65.9 x 32.7 x 2.4 in.		Power Supply (V) Power Consumption (Max)	AC110-120V 50/60Hz 70 W	AC110-120V 50/60Hz 125 W	AC110-120V 50/60Hz 140 W	AC110-120V 50/60Hz 145 W	AC110-120V 50/60Hz 195 W	AC110-120V 50/60Hz 250 W 0.5 W	
		Power Consumption (Typical)	31W 723.3 x 477.7 x 154.2 mm /	52 W 963.9 x 558.9 x 59.6 mm /	63 W 1,116.8 x 644.2 x 59.9 mm /	68.9 W 1,230.5 x 707.2 x 59.9 mm /	81.9 W 1,449.4 x 830.3 x 59.9 mm /	94 W 1,673.2 x 958.2 x 59.9 mm / 65.9 x 37.7 x 2.4 in.	
Package Dimension (Wx Hx D)	Dimension		811 x 530 x 120 mm / 32 x 20.9 x 4.7 in.	1,081 x 670 x 143 mm / 42.6 x 26.4 x 5.6 in.	1,264 x 780 x 150 mm / 49.8 x 30.7 x 5.9 in.	1,386 x 843 x 158 mm / 54.6 x 33.2 x 6.2 in.	1,606 x 963 x 184 mm / 63.2 x 37.9 x 7.2 in.	1,840 x 1,118 x 198 mm / 72.4 x 44 x 7.8 in.	
Weight Package Weight 7.6 kg / 16.8 lbs. 11.6 kg / 25.6 lbs. 15.8 kg / 34.8 lbs. 19.2 kg / 42.3 lbs. 28.3 kg / 62.4 lbs. 41.5 kg Remote Controller Model TM2140A TM2140A <t< td=""><td>Weight</td><td>Package Weight Remote Controller Model</td><td>7.6 kg / 16.8 lbs. TM2140A</td><td>11.6 kg / 25.6 lbs. TM2140A</td><td>15.8 kg / 34.8. lbs. TM2140A</td><td>19.2 kg / 42.3 lbs. TM2140A</td><td>28.3 kg / 62.4 lbs. TM2140A</td><td>30.4 kg / 67 lbs. 41.5 kg / 91.5 lbs. TM2140A</td></t<>	Weight	Package Weight Remote Controller Model	7.6 kg / 16.8 lbs. TM2140A	11.6 kg / 25.6 lbs. TM2140A	15.8 kg / 34.8. lbs. TM2140A	19.2 kg / 42.3 lbs. TM2140A	28.3 kg / 62.4 lbs. TM2140A	30.4 kg / 67 lbs. 41.5 kg / 91.5 lbs. TM2140A	
Accessory Quick Install Guide Yes Yes Yes Yes Yes	Accessory	Quick Install Guide	Yes	Yes	Yes	Yes	Yes	Yes Yes Yes	

1-800-304-7955 | BestBuy.com/CommercialHealthcare | in BestBuyBusiness & Education

BEST BUY, the BEST BUY logo, the tag design, BEST BUY BUSINESS and the BEST BUY BUSINESS logo are trademarks of Best Buy and its affiliated companies. @ 2023 Best Buy, All rights reserved.