

Key Features

SuperColor: Amazing Color Accuracy | 4000 Lumen Brightness | Energy Efficient SuperEco | Network Capable | Convenient Mounting Flexibility



Product Description

The ViewSonic® PG707W projector features 4,000 lumens, WXGA 1280 x 800 native resolution, an intuitive, user-friendly design, and a sleek white chassis. Exclusive SuperColor™ technology offers a wide color gamut for beautiful image production in nearly any environment. An energy-saving SuperEco™ feature reduces power consumption and extends the lamp life by up to 20,000 hours. A 10W speaker delivers incredibly clear and audible sound, while a top lamp door enables easy access for lamp maintenance. The PG707W is the ideal high brightness projector for use in both classroom and corporate settings.



1. Control Panel
2. Elevation Foot
3. Zoom Ring
4. IR Remote Sensor



5. Projection Lens
6. VGA In
7. HDMI (x2)
8. Audio In/Out




9. USB 2.0 Type A
10. AC In
11. Monitor Out
12. RCA Video In
13. LAN
14. Kensington® Lock Slot
15. RS232



1280 x 800
RESOLUTION



4,000 ANSI
LUMENS



1.21-1.57
THROW RATIO

Contact Sales

- call: 888.881.8781
- email: salesinfo@viewsonic.com
- visit: viewsonic.com

Display:

Type:	DLP Lamp
Resolution Type:	WXGA (1280x800)
Resolution:	1280 x 800
Brightness (Lumens):	4,000 ANSI
Display Size (in.):	30 - 300 in. / 0.76 - 7.62 m
Throw Distance:	2.6 - 33.1 ft / .8 - 10.1 m
Throw Ratio:	1.21-1.57
Keystone:	Vertical ($\pm 40^\circ$) / Horizontal ($\pm 40^\circ$)
Lens:	1.3x optical zoom
Light Source (watt):	203
Light Source Life, Normal (hours):	6000
Light Source Life, Dynamic Eco-Mode (hours):	20000
Color Depth:	1.07 Billion Colors
Dynamic Contrast Ratio:	22,000:1
Aspect Ratio:	16:10

Video Signal:

Frequency Horizontal:	15K~105KHz
-----------------------	------------

Compatibility:

PC Resolution (max):	1920 x 1080
PC Resolution (min):	640 x 480
Mac® Resolution (max):	1920 x 1080
Mac® Resolution (min):	640 x 480

Connector:

USB 2.0 Type A(1), Ethernet LAN (RJ45)(1), 3.5mm Audio Out(1), 3.5mm Audio In(1), Control (RS232)(1),
HDMI 1.4 (with HDCP 1.4)(2), VGA In(1), VGA Out(1), Composite RCA Video In(1)

Audio:

Internal Speakers:	10W (x1)
--------------------	----------

Power:

Voltage:	100-240V+/- 10%, 50/60Hz AC
Consumption (typical):	280W
Stand-by:	<0.5W

Controls:

Physical Controls:	Keypad, Power key
On Screen Display:	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)

Operating Conditions:

Temperature:	32-104° F (0 - 40° C)
--------------	-----------------------

Additional Hardware:

Kensington Lock Slot:	1
Net (lbs):	5.1
Gross (lbs):	7.8

Weight (metric):

Net (kg):	2.3
Gross (kg):	3.5

Dimensions (imperial) (WxHxD):

Packaging (in.):	16.3 x 6.6 x 11.7
Physical (in.):	11.6 x 4.3 x 8.6

Dimensions (metric) (WxHxD):

Packaging (mm):	415.0 x 168.0 x 297.0
Physical (mm):	294.0 x 110.0 x 218.0

General:

Regulations: cTUVus
PACKAGE CONTENTS: PG707W projector, power cable, VGA cable, remote control, Quick Start Guide
Warranty: Three-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).
Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.
UPC: 766907006186

Accessories:

IFP2410, PJ-SCW-1001W, PJ-WMK-006, PJ-WMK-007, PM-FCP, TD2455, VC10, VCB10