



BARRACUDA
COMPUTE

 SEAGATE

3.5 HDD DATA SHEET

**Amazing Versatility.
Unmatched Dependability.**



Seagate brings over 20 years of trusted performance and reliability to the Seagate® BarraCuda® 3.5-inch HDD—now available in capacities up to 8TB.



Best-Fit Applications

- Desktop or all-in-one PCs
- Home servers
- Entry-level direct-attached storage devices (DAS)

Key Advantages

Versatile HDDs for all your PC needs bring you industry-leading excellence in personal computing.

For over 20 years the BarraCuda family has delivered super-reliable storage for the hard drive industry.

Capacities up to 8TB for desktops, BarraCuda leads the market with the widest range of storage options available.

Advanced Power modes help save energy without sacrificing performance.¹

SATA 6Gb/s interface optimizes burst performance.¹

¹ Performance may vary depending on user's hardware configuration and operating system.

² Seagate Secure models are not available in all countries. May require TCG-compliant host or controller support.

³ Refer to specifications table for further information and feature options.



Specifications					3TB
Standard Model Numbers					ST3000DMA08
	—	—	—	—	
Bytes per Sector	4096	4096	4096	4096	4096
Heads/Disks	8/4	6/3	4/2	3/2	6/3
Performance					
Interface	SATA 6Gb/s				
SATA Transfer Rates Supported (Gb/s)	6.0/3.0/1.5	6.0/3.0/1.5	6.0/3.0/1.5	6.0/3.0/1.5	6.0/3.0/1.5
Max. Sustained Transfer Rate OD (MB/s)	190MB/s	185MB/s	190MB/s	185MB/s	210MB/s
Cache, Multisegmented (MB)	256	256	256	256	64
Reliability/Data Integrity					
Load/Unload Cycles	300,000	300,000	300,000	300,000	300,000
Nonrecoverable Read Errors per Bits Read, Max	1 per 10E14				
Power-On Hours per Year (24x7)	2400	2400	2400	2400	2400
Workload Rate Limit (TB/Year)	55	55	55	55	55
Limited Warranty (years)	2	2	2	2	2
Power Management					
Startup Power (A)	2.0	2.0	2.0	2.0	2.5
Operating Mode, Typical (W)	5.3	5.3	3.7	3.7	8
Idle Average (W)	3.4W	3.4W	2.5W	2.5W	5.40W
Standby Mode/Sleep Mode, Typical (W)	0.25/0.25	0.25/0.25	0.25/0.25	0.25/0.25	0.75/0.75
Voltage Tolerance, Inc. Noise (5V)	±5%	±5%	±5%	±5%	±5%
Voltage Tolerance, Inc. Noise (12V)	±10%	±10%	±10%	±10%	±10%
Environmental/Temperature					
Operating (ambient, min)	0°C	0°C	0°C	0°C	0°C
Operating (drive case, max)	60°C	60°C	60°C	60°C	60°C
Nonoperating (ambient)	-40°C – 70°C				
Halogen Free	Yes	Yes	Yes	Yes	Yes
RoHS Compliance	Yes	Yes	Yes	Yes	Yes
Physical					
Height (mm/in, max)	26.11mm/1.028in	26.11mm/1.028in	20.20mm/0.795in	20.20mm/0.795in	26.11mm/1.028in
Width (mm/in, max)	101.85mm/4.010in	101.85mm/4.010in	101.85mm/4.010in	101.85mm/4.010in	101.85mm/4.010in
Depth (mm/in, max)	146.99mm/5.787in	146.99mm/5.787in	146.99mm/5.787in	146.99mm/5.787in	146.99mm/5.787in
Weight (g/lb)	630g/1.389lb	610g/1.345lb	490g/1.08lb	490g/1.08lb	626g/1.38lb
Carton Unit Quantity	20	20	25	25	20
Cartons per Pallet/Cartons per Layer	40 / 8	40 / 8	40 / 8	40 / 8	40 / 8



Specifications	2TB	1TB	
Standard Model Numbers	ST2000DMA06	ST1000DMA10	—
Bytes per Sector	4096	4096	4096
Heads/Disks	6/3 or 4/2	2/1	2/1
Performance			
Interface	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s
SATA Transfer Rates Supported (Gb/s)	6.0/3.0/1.5	6.0/3.0/1.5	6.0/3.0/1.5
Max. Sustained Transfer Rate OD (MB/s)	210MB/s	210MB/s	210MB/s
Cache, Multisegmented (MB)	64	64	32
Reliability/Data Integrity			
Load/Unload Cycles	300,000	—	—
Nonrecoverable Read Errors per Bits Read, Max	1 per 10E14	1 per 10E14	1 per 10E14
Power-On Hours per Year (24x7)	2400	2400	2400
Workload Rate Limit (TB/Year)	55	55	55
Limited Warranty (years)	2	2	2
Power Management			
Startup Power (A)	2.5	2.0	2.0
Operating Mode, Typical (W)	8	5.3	5.3
Idle Average (W)	5.40W	4.60W	4.60W
Standby Mode/Sleep Mode, Typical (W)	0.75/0.75	0.94/0.94	0.94/0.94
Voltage Tolerance, Inc. Noise (5V)	±5%	±5%	±5%
Voltage Tolerance, Inc. Noise (12V)	±10%	±10%	±10%
Environmental/Temperature			
Operating (ambient, min)	0°C	0°C	0°C
Operating (drive case, max)	60°C	60°C	60°C
Nonoperating (ambient)	-40°C – 70°C	-40°C – 70°C	-40°C – 70°C
Halogen Free	Yes	Yes	Yes
RoHS Compliance	Yes	Yes	Yes
Physical			
Height (mm/in, max)	26.11mm/1.028in	19.99mm/0.787in	19.99mm/0.787in
Width (mm/in, max)	101.85mm/4.010in	101.85mm/4.010in	101.85mm/4.010in
Depth (mm/in, max)	146.99mm/5.787in	146.99mm/5.787in	146.99mm/5.787in
Weight (g/lb)	626g/1.38lb	400g/0.88lb	400g/0.88lb
Carton Unit Quantity	20	25	25
Cartons per Pallet/Cartons per Layer	40 / 8	40 / 8	40 / 8