




Lexmark MB3442adw

Productivity. Reliability. Security.



Google
Cloud Print 2.0 Ready



Works with
Apple AirPrint

Lexmark MB3442adw

Light, compact, and fast, the MB3442adw multifunction supports output up to 42 pages per minute*, plus double-side automatic scanning, copying, faxing, and touch-screen convenience. Connect via USB, Ethernet, or Wi-Fi and add an optional 550-sheet paper tray or available Extra High Yield Unison™ toner offering up to 6,000 pages** for longer print runs.

Compact monochrome versatility

- Get monochrome output at up to 42 pages per minute* with a first page as fast as 5.9 seconds.
- Capture documents with double-side automatic scanning at up to 96 letter-size images per minute.
- Tackle your workload with the power of a 1-GHz dual-core processor and 512 MB of memory.
- Compact dimensions of 13.3 inches high x 16.2 inches wide x 14.4 inches deep (339 mm high x 411 mm wide x 366 mm deep) help it fit almost anywhere.



Connect and command

- Connect via Wi-Fi, Ethernet and USB.
- Simplify mobile printing via Lexmark Mobile Print app, as well as Google Cloud Print, Mopria® and AirPrint technologies.
- Take command of printing, copying, faxing, and automatic two-sided scanning with a 2.8-inch (7.2 cm) color touch screen.
- Built-in cloud connectors help you save scans to and retrieve

files from popular cloud services Box, DropBox, Google Drive, and Microsoft OneDrive.

Sustained output, enduring quality

- Available Extra High Yield Unison™ toner provides up to 6,000 pages** of output for more printing and less downtime.
- Optional paper tray increases total input capacity to 900 sheets to support longer print runs and enhanced media flexibility.
- Steel frame and lifetime imaging components mean long life and minimal maintenance.

Robust, built-in security

- Lexmark's full-spectrum security architecture helps keep your information safe—in the document, on the device, over the network, and everywhere in between.
- A range of embedded features harden the device against attacks.
- Standard Confidential Print feature helps ensure output security via simple PIN.

Save paper, save energy

- Automatic two-sided printing is standard.
- Built-in energy-saving modes help support ratings of EPEAT® Silver and ENERGY STAR® certified.
- The Lexmark Cartridge Collection Program (LCCP) and Lexmark Equipment Collection Program (LECP) minimize waste and support recycling (availability varies by country).

* Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.

** Average continuous mono declared yield in one-sided (simplex) mode up to this number of pages in accordance with ISO/IEC 19752. Actual yield will vary considerably based upon many factors. See www.lexmark.com/yields for more information.

Lexmark MB3442adw



1 Multifunction product with 2.8-inch (7.2 cm) touch screen
13.3 x 16.2 x 14.4 in.
339 x 411 x 366 mm

2 100-Sheet multipurpose feeder
Dimensions included as part of base model

3 250-Sheet tray
Dimensions included as part of base model

4 550-Sheet Tray
4.2 x 14.6 x 14.9 in.
107 x 370 x 378 mm

 Standard
 Optional

Supports one optional 550-sheet tray.

All measurements are shown as height x width x depth. For more information about supported configurations, refer to the Printer, Option and Stand Compatibility Guide at http://www.lexmark.com/publications/furniture_safety/

Product Specifications		Lexmark MB3442adw
Printing		
Display		2.8 inch (7.2 cm) LCD touch panel
Print Speed		Up to: Black: 42 ppm ¹ (Letter)
Time to First Page		As fast as: Black: 5.9 seconds
Print Resolution		Black: 2400 Image Quality, 600 x 600 dpi
Memory		Standard: 512 MB / Maximum: 512 MB
Hard Disk		Not Available
Recommended Monthly Page Volume		800 - 8000 pages ²
Maximum Monthly Duty Cycle		Up to: 80000 pages per month ³
Copying		
Copy Speed		Up to: Black: 42 cpm ¹ (Letter)
Time to First Copy		As fast as: Black: 5.9 seconds
Scanning		
Scanner Type / ADF Scan		Flatbed scanner with ADF / DADF (single pass Duplex)
A4/Ltr Duplex Scan Speed		Up to: Black: 92 / 96 sides per minute / Color: 40 / 42 sides per minute
A4/Ltr Simplex Scan Speed		Up to: Black: 42 / 45 sides per minute / Color: 20 / 22 sides per minute
ADF Paper Input Capacity		Up to: 50 pages 20 lb or 75 gsm bond
Faxing		
Modem Speed		ITU T.30, V.34 Half-Duplex, 33.6 Kbps
Supplies⁴		
Laser Cartridge Yields		up to: 6,000 ⁵ 5-page Black Extra High Yield Cartridge / up to: 1,500 ⁵ 5-page Cartridge / up to: 3,000 ⁵ 5-page Black High Yield Cartridge
Imaging Unit Estimated Yield		Up to: 40000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage ⁶
Cartridge(s) Shipping with Product		3,000 ⁵ 5-page Black Starter Return Program Toner Cartridge
Paper Handling		
Included Paper Handling		100-Sheet Multipurpose Feeder, Integrated Duplex, 150-Sheet Output Bin, 250-Sheet Input
Optional Paper Handling		550-Sheet Tray
Paper Input Capacity		Up to: Standard: 350 pages 20 lb or 75 gsm bond / Maximum: 900 pages 20 lb or 75 gsm bond
Paper Output Capacity		Up to: Standard: 150 pages 20 lb or 75 gsm bond / Maximum: 150 pages 20 lb or 75 gsm bond
Media Types Supported		Paper Labels, Card Stock, Plain Paper, Envelopes, Refer to the Paper & Specialty Media Guide
Media Sizes Supported		A6, Oficio, 7 3/4 Envelope, 9 Envelope, JIS-B5, A4, Legal, A5, Letter, Statement, Executive, Universal, DL Envelope, Folio, 10 Envelope
General Information⁷		
Standard Ports		USB Compatible with USB 2.0 Specification (Type B), Ethernet 10/100BaseTX (RJ-45)
Noise Level		Operating: 53 dBA (Print) / 54 dBA (Copy) / 55 dBA (Scan)
Specified Operating Environment		Humidity: 8 to 80% Relative Humidity / Temperature: 10 to 32°C (50 to 90°F) / Altitude: 0 - 2896 Meters (9,500 Feet)
Limited Warranty		See Statement of Limited Warranty: 1-Year Advanced Exchange, Next Business Day
Size / Weight		H x W x D: 13.3 x 16.2 x 14.4 in. / 28.2 lb.
ENERGY STAR Typical Electricity Consumption		TEC: 0.54 kilowatt-hours per week

All information is subject to change without notice. Lexmark is not liable for any errors or omissions.

¹ Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.

² "Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. ³ "Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. ⁴ Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details. ⁵ Average standard page yield value declared in accordance with ISO/IEC 19752. ⁶ Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity. ⁷ Printers are sold subject to certain license/agreement conditions. See www.lexmark.com/printerlicense for details.

© 2020 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries.

Apple and AirPrint are trademarks of Apple Inc., registered in the U.S. and other countries. Google Cloud Print is a trademark of Google, LLC. MOPRIA®, the Mopria® Logo™ and the Mopria® Alliance logos are registered trademarks and service marks of Mopria Alliance, Inc. in the United States and other countries. Unauthorized use is strictly prohibited. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. EPEAT® is a trademark of the Green Electronics Council in the United States and other countries. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (<http://www.openssl.org/>).



lexmark.com