

## KM 7740 FR

36-inch induction cooktop, operated with its own controls  
with 5 round cooking zones



- Intuitive quick selection via number sequences – Smart Select
- Versatile – 5 cooking zones, 1 extra large with diameter of 11 in
- With a width of 36 1/8 (915) in (mm) and stainless steel frame for proud-mounting
- Shortest heating-up times – TwinBooster
- Communication with the ventilation hood – automatic Con@ctivity function

EAN: 4002516611509 / Material number: 12074220 /  
Old Material Number: 26774000USA

<b>Heating type</b>	
Fuel type	Induction
<b>Design</b>	
Independent of oven	•
<b>Design</b>	
Elegant glass ceramic surface	•
Surface-mounted/flush-fit	–/–
Ceramic surface color	Black
All-round stainless-steel frame	•
Proud installation	•
<b>Cooking zone details</b>	
No. of rings	5
Number of cooking areas	0
Maximum number of pans	5
<b>1st cooking zone/cooking area</b>	
Position	front left
Type	Variable cooking zone
Size in mm	Ø 100-160
Max. Booster power rating in W	1700
Max. rating in W	1400
Max. TwinBooster power rating in W	2200
<b>2nd cooking zone/cooking area</b>	
Position	rear left
Type	Variable cooking zone
Size in mm	Ø 160-230
Max. Booster power rating in W	3000
Max. rating in W	2300
Max. TwinBooster power rating in W	3700
<b>3rd cooking zone/cooking area</b>	
Position	Centered
Type	Variable cooking zone
Size in mm	Ø 180-280
Max. Booster power rating in W	3000
Max. rating in W	2600
Max. TwinBooster power rating in W	3700
<b>4th cooking zone/cooking area</b>	
Position	rear right
Type	Variable cooking zone
Size in mm	Ø 140-190
Max. Booster power rating in W	2500
Max. rating in W	1850
Max. TwinBooster power rating in W	3000
<b>5th cooking zone/cooking area</b>	
Position	front right
Type	Variable cooking zone
Size in mm	Ø 140-190
Max. rating in W	1850
Max. booster rating in W	2500

## KM 7740 FR

36-inch induction cooktop, operated with its own controls  
with 5 round cooking zones



EAN: 4002516611509 / Material number: 12074220 /  
Old Material Number: 26774000USA

Max. TwinBooster rating in W 3000

### User convenience

Networking with Miele@home	•
Automatic function	Con@ctivity 3.0
Pan and pan size recognition	•
Operation via touchpad sensors	Smart Select
Display color	Yellow
Permanent pan recognition	•
Stop & Go function	•
Wipe protection	•
Recall function	•
Minute minder	•
Automatic switch-off for all rings	•
AutoBoost	•
Keep-warm function	•
Individual setting options (e.g. acoustic signal tones)	•

### Cleaning convenience

Easy to clean ceramic glass	•
-----------------------------	---

### Safety

Safety cut-out	•
Lock function	•
System lock	•
Integrated cooling blower	•
Overheating protection	•
Residual heat indicator	•

### Technical data


Dimensions (width) in in. (mm)	36 1/8 (915)
Dimensions (height) in in. (mm)	3 1/8 (78)
Dimensions in mm (depth)	21 1/2 (544)
Cutout dimensions (width) in in. (mm)	34 1/2 in (876 mm)
Cutout dimensions (depth) in in. (mm)	20 1/2 in (518 mm)
Casing height incl. connection box in mm	2 7/8 (71)
Weight in lbs. (kg)	46 (21)
Total connected load in kW	9.90-11.50
Power cord length in in. (m)	3 (1.2)
Voltage in V	208-240
Frequency in Hz	50-60

### Standard accessories

Power cord	Yes
------------	-----

## KM 7740 FR

36-inch induction cooktop, operated with its own controls  
with 5 round cooking zones



KM7740FR – with frame, surface mounted overlying  
installation (\*footnote) – drawing

① Front, ② Flexible metal hose with power cords, L = 4'  
(1,200 mm)