ONKYO

TX-RZ3100

11.2-Channel Network A/V

















































For Multidimensional Sound Without Compromise

Our flagship receiver's robust high-current power and instantaneous full-scale dynamics make it the ultimate driving force for 7.2.4-channel home-theater layouts with floorstanding speakers, dual subwoofers, and in-ceiling height speakers. Sound quality is accurate, lush, and exuberant, capable of transporting your audience out of this world and into the one created by the film's director. As well as completely transforming the cinematic and stereo-listening experience, the TX-RZ3100 serves entertainment seamlessly across the home, with wired or wireless* multi-zone digital/analog audio, Zone 2 UltraHD HDMI®, and a suite of casting technologies to share app-based audio. Designed for easy custom home integration, the TX-RZ3100 is crafted with passion for the passionate home theater enthusiast. *Requires optional FireConnect**-compatible speakers sold separately.

HIGHLIGHTS

- 200 W per Channel
- THX® Select2™ Plus Certification
- Native DTS:X[™] and Dolby Atmos® to 7.2.4 Channels
- DTS Neural:X[™] Upmixing for Legacy
- Multichannel Formats
- Chromecast built-in, AirPlay®, Wi-Fi®, and Bluetooth® App Streaming
- AccuEQ Room Calibration with AccuReflex Technology
- FireConnect™ Multi-Room Wireless Technology
- HDMI® 8 In (1 Front), Main Out, Zone 2 Out (HDCP 2.2/HDR*1)

ADVANCED FEATURES

- THX® Select2™ Plus Theater-Reference Audio Performance
- 7.2.4-channel DTS:X™ and Dolby Atmos® Object-based
- Audio Decoding

 DTS Neural:X™ Upmixes Standard 5.1 and 7.1 formats to 3D Sound HDMI Supports 4K/60 Hz, High Dynamic Range, 4:4:4 Color Space, and HDCP 2.2-protected Video*
- Chromecast built-in²², AirPlay[®], Wi-Fi[®], Bluetooth^{®±3}, Tuneln Radio, Pandora[®], Spotify, TIDAL^{®±2}, and Deezer^{®±2} for App-based Audio
- Streaming⁵⁶
 Network/USB Audio (DSD 11.2 MHz [Stereo], 192/24 PCM, Dolby⁶
 TrueHD, FLAC, WAV, ALAC, AAC, MP3, WMA)
 Powered Zone 2 and Powered Zone 3 Outputs for Multi-room
 Analog and Digital (HDMI/Network/OPT/COAX) Audio with
 Independent Volume/Tone Controls
 Whole House Mode Function
 Acquisit Collisions with Acquis effort for Sompler Object based

- AccuEQ Calibration with AccuReflex for Seamless Object-based, Multichannel, and Stereo Sound (Setup Mic Included)

- FireConnect m*2 Wireless Multi-room Digital/Analog Audio Distribution to Compatible Speakers (Sold Separately)
- 11.2 Multichannel Pre-Outs for User Setup Customization
- Ouality Banana-plug Speaker Posts with Transparent Knobs
- * Quanty bariaria-piug Speaker Fosts with i Fransparent Knobs ** Remote App for iPhone® (PhOd touch® and Android **) Devices**6 ** I 66 Wideo/HDCP 2.2 supported on HDMI inputs I 5, Main Out, and Zore 2 Out. **) Services enable do firmware update. Details TBA. ** 3 Bluetooth specification Version 4.1 (compatible orphic AZDP v I.2, AWCP v I.3) dos supporting Advanced Music Optimizer ** 4 healibility of framer update. Audiobility of framer ports enables of the properties of services depends on region. Some services may require a pold subscription and firmware update. Availability of third-party services advertised here is accurate at the time of publication, but may be subject to change without notice. "S Compatible with iPod touch (5th generation or later) and iPhone 4GS or later. "6 Requires Android 4.0.3 or later.

AMPLIFIER FEATURES

- 200 W/Ch (6 Ohms, I kHz, 0.9% THD, I Channel Driven, FTC); I40 W/Ch (8 Ohms, I kHz, 0.08% THD, 2 Channels Driven, FTC)
- Onkyo High-Current Digital Amplification for Smooth Low-Distortion Power Customized High-Output Transformer, Custom
 Audio-Grade Capacitors, Separate Transformer for Standby
- Separated Digital and Analog Circuitry to Reduce Interference
- · Extruded Metal Heat Sink with Polycarbonate Cooling Fan
- $\bullet \ \mathsf{VLSC}^{\tiny{\texttt{TM}}} \ \mathsf{(Vector\ Linear\ Shaping\ Circuitry)}\ \mathsf{Noise-free\ Signal\ Processing}$ for All Channels
- PLL (Phase Locked Loop) Jitter-Cleaning Circuitry for S/PDIF Audio

PROCESSING FEATURES

- HDMI Support for 4K/60 Hz, 3D,Audio Return Channel, DeepColor", x.v.Color", LipSync, Dolby Atmos®, Dolby® TrueHD, Dolby® Digital Plus, Dolby® Surround, DTS:X", DTS-HD Master Audio", DTS 96/24, DTS-ES, DTS Express, DTS Neuralx", THX® Cinemal/Music/Game, DVD-Audio, Super Audio CD, Multichannel PCM, and CEC

- Dolby Atmos®, DTS:X°, Dolby® TrueHD, and DTS-HD Master Audio™ Decoding
 Separate 384 kHz/32-bit AK4490 Stereo DAC (Front L/R),
 2 x 768 kHz/32-bit AK4458 Multichannel DACs (Surround Channels)

- Discrete 192 kHz/24-bit AK4388 Stereo DACs (x2) for Zone 2 and Zone 3
- Multiple 32-bit Digital Signal Processing Engines
- · 4 DSP Modes for Gaming: Rock, Sports, Action, and RPG
- Theater-Dimensional Virtual Surround Function · Direct Mode and Pure Audio Mode

CONNECTION FEATURES

- 8 HDMI Inputs (I Front/7 Rear), Main, and Zone 2 Outputs
- Component Video Switching (2 Inputs and 1 Output) and 2 Composite Video Inputs
- 5 Digital Audio Inputs (3 Optical and 2 Coaxial) and 7 Analog Audio Inputs
 Phono Input (MM) for Turntable Connection
- Mass Storage Class USB Memory Playback Capability (Rear Input)
- Zone 2 and Zone 3 Powered Speaker Outputs
- 11.2 Multichannel Pre-Outs and Zone 2/3 Pre-/Line Outs · Dual Subwoofer Pre-Outs
- 12 V Trigger Out (Assignable) with IR Input; Supports IP and RS232
- '/s" (6.3 mm) Headphone Input
 Banana-plug-compatible Speaker Posts with Easy Connection Setup

OTHER FEATURES

- Tone Controls (Bass/Treble) ±10 dB for All Channels
- Independent Crossover Adjustment for Each Channel (40/50/60/70/80/90/100/120/150/180/200 Hz)
- A/V Sync Control (Up to 500 ms in 5 ms Steps at 48 kHz) New Graphical Overlaid On-Screen Display (OSD) via HDMI with Quick Setup Function

 New Graphical Overlaid On-Screen Display (OSD) via HDMI with Quick Setup Function
- Hybrid Standby Function with HDMI Passthrough
- 40 FM/AM and 40 Internet Radio Station Presets
- RIHD (Remote Interactive Over HDMI) for System Control
- Aluminum Front Panel and Volume Control Knob
- Simple Remote Control

TX-RZ 3100

11.2-Channel Network A/V Receiver

Ultimate DTS: X^{TM} and Dolby Atmos® Home Theater

With 11.2 channels of instantaneous power from an uncommonly small body, the TX-RZ3100 enables the current

maximum Dolby Atmos® and DTS:X™ home-theater layout of 7.2.4 channels in a self-contained component for the ultimate in multidimensional objectbased surround-sound.



Upmixes Standard Surround Formats

DTS Neural: X^{m} retrieves spacial cues from standard multichannel formats and upmixes for 3D playback that's virtually identical to a native DTS:X™ source, giving your existing Blu-ray library a new lease on life.

THX®-Certified for Theater Reference Sound

THX® Select2™ Plus guarantees distortion-free Theater Reference Volume in your home. Certified products are subjected to the industry's toughest bench-tests to satisfy THX® requirements for audio performance.

Introducing Onkyo High-Current Digital Amplification

The TX-RZ3100 combines high-current driving architecture with sophisticated digital amplification and filtering technology. Noise-reduction hardware including a new custom low-hum

transformer delivers fast dynamics. thrilling power, and stunningly precise detail resolution. Painstakingly tuned for velvet-smooth and emotionally evocative audio reproduction, Onkyo High-Current Digital is where power meets control.



Cohesive Multidimensional Sound

AccuReflex—part of the AccuEO room calibration suite phase-matches height and floor-standing speakers for transparent and seamless reproduction of object-based sound. AccuEQ optimizes the entire system to suit your space without affecting front-speaker characteristics for pure stereo





Chromecast built-in, AirPlay®, Wi-Fi®, and Bluetooth®

Most smartphone and PC music apps let you mirror what's playing to your TX-RZ3100 with ease using Chromecast built-in. The receiver also features AirPlay, Bluetooth, and Wi-Fi® for universal wireless audio support, including DSD up to 11.2 MHz.

Spotify, Pandora®, Deezer, TIDAL, and TuneIn

Enjoy the music you want any time on your home theater via these popular smartphone and PC applications or via Onkyo remote app.

FireConnect™ Wireless Multi-room Solution

Cast anything playing through your receiver—including vinyl and streaming audio—to compatible speakers* around your home using $\mathsf{Fire}\mathsf{Connect}^{\scriptscriptstyle{\mathsf{TM}}}$ technology. Manage multi-zone playback with our free smartphone app.

* FireConnect*-compatible speakers are scheduled for www.onkyo.com for details on Onkyo wireless speakers. operability with all FireConnect*-compatible products. rs. Onkyo cannot guarantee





FireConnect™ by Blackfire Research Corp. is a stable wireless protocol that mirrors any audio source connected to the receiver—from vinyl to streaming audio.

Note: Audio sources supported by FireConnect™ are model-dependent

Housewide Playback of Any Source

Put extra speakers you have to good use—connect them to the receiver's Powered Zone 2 and Powered Zone 3 outputs. Dedicated DACs and smartphone control options let you manage content in any zone, making housewide sound a practical proposition.

Latest Dual-Zone HDMI®

Select HDMI terminals support HDR, 4:4:4 color-space, and HDCP 2.2 for next-generation UltraHD Blu-ray, streaming 4K video, and 4K/60 Hz PC-based gaming. Zone 2 output transmits 4K home theater sources to a second TV.

SPECIFICATIONS

Power Output	
All Channels	200 W/Ch (6 Ohms, 1 kHz, 0.9% THD,
	I-Channel Driven, FTC)
	140 W/Ch (8 Ohms, 1 kHz, 0.08% THD,
	2-Channels Driven, FTC)
Dynamic Power	320 W (3 Ohms, Front)
	270 W (4 Ohms, Front)
	160 W (8 Ohms, Front)
THD+N (Total Harmo	nic Distortion + Noise)
`	0.04% (1 kHz, 100 W)
Input Sensitivity and In	npedance
, , .	200 mV/82 k-ohms (Line)
	3.5 mV/47 k-ohms (Phono MM)
Rated RCA Output Le	vel and Impedance
	1.0 V/330 Ohms (Pre Out)
	1.0 V/330 Ohms (Subwoofer Pre Out)
	200 mV/1.2 k-ohms (Zone Out)
	2.0 V/1.2 k-ohms (Zone Pre Out)
Phono Overload	70 mV (MM, 1 kHz, 0.5%)
Tone Control	±10 dB, 100 Hz (Bass)
	+ I O dB I O kHz (Troble)
Signal-to-Noise Ratio	108 dB (Line, IHF-A)
	90 dB (Phono MM, IHF-A)

Speaker Impedance Video Section

Input Sensitivity/Output Level and Impedance

I.0 Vp-p/75 Ohms (Component Y) 0.7 Vp-p/75 Ohms (Component PB/CB, PR/CR) 1.0 Vp-p/75 Ohms (Composite)

4 Ohms – 16 Ohms

Component Video Frequency Response

5 Hz–100 MHz/+0 dB, -3 dB **Tuner Section**

Tuning Frequency Range		
FM	87.5 MHz-107.9 MHz	
AM	530 kHz-1,710 kHz	
FM/AM Preset Memory	40 Stations	
General		
Power Supply	AC 120 V~, 50/60 Hz	
Power Consumption	340 W	
Standby Power Consumption		
	0.15 W	
D:	17 1/-" > 7 15/" > 17 13/"	

	0.13 VV
Dimensions (W x H x D)	
	(435 × 201 × 453 mm)
\\/oight	43 O lbc (195 kg)

CARTON

	22 ¹ / ₄ " × 12 ¹³ / ₁₆ " × 21 ⁹ / ₁₆ " (565 × 325 × 547 mm)
Weight	48.5 lbs. (22.0 kg)

UPC CODE

889951000235

Supplied Accessories

- Indoor FM antenna AM loop antenna Speaker setup microphone
 Instruction manual Remote controller AA (R6) batteries x 2



Due to a policy of continuous product improvement. Only or reserves the right to change specifications and appearance without notice. THX. the THX logs, and Select2 are trademarks of THX Ltd. THX and the THX log are registered in the U.S. and other jurisdictions. All rights reserved. Manufactured under license from Dolby Laboratories. Dolby, Dobby Atmos, Dolby Surround, and the double-D symbol are trademarks of Dolby Laboratories. For DTS patents, see http://patents.dts.com. Manufactured under license from DTS, Inc., DTS, the Symbol, DTS in combination with the Symbol, the DTSX, DTS Neural/X, and DTS-HD logs, and DTS-HD Master Audio are registered trademarks or trademarks or trademarks or the United States and/or other countries. Dolby, Date and DTS-HD logs, and DTS-HD logs, and DTS-HD Master Audio are registered trademarks or HDM1 Licensing LLC in the United States and other countries. The Bilactorial word mark and logos are owned by the Bilactorial Sicility and LTD-Rope, Drop Logo Logo, Thop, Drop Countries, The Poly Ind. (Thop, 1-Poly Pol) Country, Though Bilactorial Through And That are trademarks of PApple Inc., registered in the U.S. and other countries. That see in Poly Thy Laboratorial States and other countries. The Bilactorial Poly Countries and Paper Inc., registered that the U.S. and other countries. The Bilactorial Poly Countries and Paper Inc., registered in the U.S. and other countries. That see in Poly Through And Thro

