

Rugged Mini

MOBILE DRIVE Data Sheet

Rugged Design. Mini Size.

- Shock-, rain-, and pressure-resistant
- USB 3.0: up to 4× faster than USB 2.0
- Works with iPad Connect your LaCie drive with USB-C
- Rescue Data Recovery Services

design by neil poulton

Product Overview

The LaCie Rugged Mini drive shares features with our popular Rugged drive, like shock resistance, drop resistance, and rubber sleeve for added protection. But the LaCie Rugged Mini is also rain- and pressure-resistant—you can drive over it with a 1-ton car, and it still works! Its small size makes it completely mobile, and its tough exterior provides protection against accidental drops, shock, or pressure. The Rugged Mini is the most compact member of the LaCie Rugged drive family and will appeal to a wide range of users.

Use Cases

- Students: Store music, video, and confidential school documents on a device that fits in a backpack.
- Travelers: Protect valuable data from loss or accident while on the road.
- Photographers: Small form factor and toughness make this product perfect for use in the field or to safely deliver large files to customers and partners
- Videographers: Perfect for shuttling dailies or other footage to the studio and transfering files quickly thanks to USB 3.0.

1 Determined by a test that approximates a real-world scenario in which the hard drive remained functional, despite aesthetic damage, after the product was driven over by an approximately 1-ton car (1000kg/2205 lbs).







Rugged Mini



MOBILE DRIVE

Specifications									
Capacity 1-2TB	Product Dimensions	Box Dimensions	Master Carton Dimensions	Pallet Dimensions					
Length(in/mm)	5.29in/134.6mm	7.32in/186mm	10.47in/266mm	40.94in/1040mm					
Width(in/mm)	3.385in/86mm	5.07in/129mm	7.40in/188mm	46.85in/1190mm					
Height(in/mm)	073in/18.73mm	1.37in/35mm	5.31in/135mm	42.51in/1080mm					
Weight(lb/kg)	0.66lb/0.3kg	0.66lb/0.3kg	5.512lb/2.5kg	826.7lb/375kg					
Quantities 1-2TB									
Boxes per Master Carton	9	9							
Master Cartons per Pallet	90	90							
Pallet Layers	6	6							
Capacity 4-5TB	Product Dimensions	Box Dimensions	Master Carton Dimensions	Pallet Dimensions					
Length(in/mm)	5.31in/135.1mm	7.32in/186mm	10.47in/266mm	41.33in/1050mm					
Width(in/mm)	3.385in/86mm	5.07in/129mm	7.40in/188mm	46.85in/1190mm					
Height(in/mm)	1.02in/26mm	2.04in/52mm	5.31in/135mm	40.94in/1040mm					
Weight(lb/kg)	0.881lb/0.4kg	1.102lb/0.5kg	5.512lb/2.5kg	722.7lb/327.8kg					
Quantities 4-5TB	· ·	· ·	· ·						
Boxes per Master Carton	5	5							
Master Cartons per Pallet	120	120							
Pallet Layers	6	6							

- Computer with a USB 3.0 or USB 2.0 port
- Compatible with most Windows and macOS systems. Visit lacie.com/os for details 1.2
 Minimum free disk space: 600MB recommended

- LaCie[®] Rugged Mini 3.0 drive
- Quick Install Guide
- Rescue Data Recovery Services

Region	Model Number	Capacity	Limited Warranty (years)	UPC Code	EAN Code	Multi-Pack UPC
ww	LAC301558	1TB	2	093053827984	3660619315581	10093053827981
ww	LAC9000298	2TB	2	093053003272	3660619005840	10093053003279
ww	LAC9000633	4TB	2	093053014117	3660619013814	10093053014114
ww	STJJ5000400	5TB	2	763649139578	3660619407927	10763649139575

LACIE.COM

© 2021 Seagate Technology LLC. All rights reserved. Seagate, Seagate Technology, LaCie, and the LaCie logo are trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one thousand billion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions and will not be available for data storage. Complying with all applicable copyright laws is the responsibility of the user. Seagate reserves the right to change, without notice, product offerings or specifications. DS1961.3-2108US