

## KM 7740 FR 36-inch induction cooktop, operated with its own controls with 5 round cooking zones



- Intuitive quick selection via number sequences Smart Select
- Versatile 5 cooking zones, 1 extra large with diameter of 11 in
- With a width of 36 1/8 (915) in (mm) and stainless steel frame for proud-mounting
- Shortest heating-up times TwinBooster
- Communication with the ventilation hood – automatic Con@ctivity function

EAN: 4002516611509 / Material number: 12074220 / Old Material Number: 26774000USA

| Heating type   |   |
|--|---|
| Fuel type  | Induction   |
| Design   |   |
| Independent of oven  | •   |
| Design   |   |
| Elegant glass ceramic surface  | •   |
| Ceramic surface color  | Black   |
| All-round stainless-steel frame  | •   |
| Proud installation   | •   |
| Cooking zone details   |   |
| No. of rings   | 5   |
| Number of cooking areas  | 0   |
| Maximum number of pans   | 5   |
| 1st cooking zone/cooking area  |   |
| Position   | front left  |
| Туре   | Variable cooking zone   |
| Size in mm   | Ø 100-160   |
| Max. Booster power rating in W   | 1700  |
| Max. rating in W   | 1400  |
| Max. TwinBooster power rating in W   | 2200  |
| 2nd cooking zone/cooking area  |   |
| Position   | rear left   |
| Туре   | Variable cooking zone   |
| Size in mm   | Ø 160-230   |
| Max. Booster power rating in W   | 3000  |
| Max. rating in W   | 2300  |
| Max. TwinBooster power rating in W   | 3700  |
| 3rd cooking zone/cooking area  |   |
| Position   | Centered  |
| Туре   | Variable cooking zone   |
|  |   |
| Size in mm   | Ø 180-280   |
| Size in mm  Max. Booster power rating in W   |   |
|  | Ø 180-280   |
| Max. Booster power rating in W   | Ø 180-280<br>3000   |
| Max. Booster power rating in W Max. rating in W  | Ø 180-280<br>3000<br>2600   |
| Max. Booster power rating in W Max. rating in W Max. TwinBooster power rating in W   | Ø 180-280<br>3000<br>2600   |
| Max. Booster power rating in W Max. rating in W Max. TwinBooster power rating in W 4th cooking zone/cooking area   | Ø 180-280<br>3000<br>2600<br>3700   |
| Max. Booster power rating in W Max. rating in W Max. TwinBooster power rating in W 4th cooking zone/cooking area Position  | Ø 180-280<br>3000<br>2600<br>3700<br>rear right   |
| Max. Booster power rating in W Max. rating in W Max. TwinBooster power rating in W 4th cooking zone/cooking area Position Type   | Ø 180-280 3000 2600 3700  rear right Variable cooking zone  |
| Max. Booster power rating in W Max. rating in W Max. TwinBooster power rating in W 4th cooking zone/cooking area Position Type Size in mm  | Ø 180-280 3000 2600 3700  rear right  Variable cooking zone Ø 140-190                             |
| Max. Booster power rating in W Max. rating in W Max. TwinBooster power rating in W 4th cooking zone/cooking area Position Type Size in mm Max. Booster power rating in W   | Ø 180-280 3000 2600 3700  rear right  Variable cooking zone Ø 140-190 2500                        |
| Max. Booster power rating in W Max. rating in W Max. TwinBooster power rating in W 4th cooking zone/cooking area Position Type Size in mm Max. Booster power rating in W Max. rating in W  | Ø 180-280  3000  2600  3700  rear right  Variable cooking zone  Ø 140-190  2500  1850             |
| Max. Booster power rating in W Max. rating in W Max. TwinBooster power rating in W 4th cooking zone/cooking area Position Type Size in mm Max. Booster power rating in W Max. rating in W Max. rating in W Max. TwinBooster power rating in W  | Ø 180-280  3000  2600  3700  rear right  Variable cooking zone  Ø 140-190  2500  1850             |
| Max. Booster power rating in W Max. rating in W Max. TwinBooster power rating in W 4th cooking zone/cooking area Position Type Size in mm Max. Booster power rating in W Max. rating in W Max. TwinBooster power rating in W 5th cooking zone/cooking area                                       | Ø 180-280 3000 2600 3700  rear right Variable cooking zone Ø 140-190 2500 1850 3000               |
| Max. Booster power rating in W Max. rating in W Max. TwinBooster power rating in W 4th cooking zone/cooking area Position Type Size in mm Max. Booster power rating in W Max. rating in W Max. rating in W Max. TwinBooster power rating in W 5th cooking zone/cooking area Position             | Ø 180-280 3000 2600 3700  rear right  Variable cooking zone Ø 140-190 2500 1850 3000  front right |
| Max. Booster power rating in W Max. rating in W Max. TwinBooster power rating in W 4th cooking zone/cooking area Position Type Size in mm Max. Booster power rating in W Max. rating in W Max. rating in W Max. TwinBooster power rating in W 5th cooking zone/cooking area Position Type        | Ø 180-280   3000   2600   3700  |
| Max. Booster power rating in W  Max. Tating in W  Max. TwinBooster power rating in W  4th cooking zone/cooking area  Position  Type  Size in mm  Max. Booster power rating in W  Max. rating in W  Max. TwinBooster power rating in W  5th cooking zone/cooking area  Position  Type  Size in mm | Ø 180-280   3000   2600   3700  |



## KM 7740 FR 36-inch induction cooktop, operated with its own controls with 5 round cooking zones




EAN: 4002516611509 / Material number: 12074220 / Old Material Number: 26774000USA

| Old Material Number: 2677400005A                        |                 |
|---|-----------------|
| User convenience  |                 |
| Networking with Miele@home                              | •               |
| Automatic function                                      | Con@ctivity 3.0 |
| Pan and pan size recognition                            | •               |
| Operation via touchpad sensors                          | Smart Select    |
| Display color   | Yellow          |
| Permanent pan recognition                               | •               |
| Stop & Go function                                      | •               |
| Wipe protection   | •               |
| Recall function   | •               |
| Minute minder   | •               |
| Automatic switch-off for all rings                      | •               |
| AutoBoost   | •               |
| Keep-warm function                                      | •               |
| Individual setting options (e.g. acoustic signal tones) | •               |
| Cleaning convenience                                    |                 |
| Easy to clean ceramic glass                             | •               |
| Safety  |                 |
| Safety cut-out  | •               |
| Lock function   | •               |
| System lock   | •               |
| Integrated cooling blower                               | <u> </u>        |
| Overheating protection                                  | <u> </u>        |
| Residual heat indicator                                 | •               |
| Technical data  |                 |
| Dimensions (width) in in. (mm)                          | 36 1/8 (915)    |
| Dimensions (height) in in. (mm)                         | 3 1/8 (78)      |
| Dimensions in mm (depth)                                | 21 1/2 (544)    |
| Cutout dimensions (width) in in. (mm)                   | 876             |
| Cutout dimensions (depth) in in. (mm)                   | 518             |
| Casing height incl. connection box in mm                | 2 7/8 (71)      |
| Weight in lbs. (kg)                                     | 46 (21)         |
| Total connected load in kW                              | 9.90-11.50      |
| Power cord length in in. (m)                            | 3 (1.2)         |
| Voltage in V  | 208-240         |
| Frequency in Hz   | 50-60           |
| Standard accessories                                    |                 |
| Power cord  | Yes             |



## KM 7740 FR 36-inch induction cooktop, operated with its own controls with 5 round cooking zones



 $\label{eq:KM7740FR} \textbf{KM7740FR}-\textbf{with frame, surface mounted overlying installation (*footnote)}-\textbf{drawing}$ 

? Front, ? Flexible metal hose with power cords, L = 4' (1,200 mm)