SONANCE

VISUAL EXPERIENCE DATA SHEET

VX46R SST

TECHNICAL SPECIFICATIONS

VX46R SST

|	
SKU	93682 - Each
Tweeter	0.75" (19mm) ceramic dome, Ferrofluid-cooled, acoustic back chamber, dual voice coil
Woofer	4.5" (114mm) Kevlar/Nomex cone, rubber surround, pivoting, dual voice coil
Frequency Response	58Hz - 20kHz +/-3dB
Impedance	8 ohms nominal; 6 ohms minimum
Power Handling (RMS)	5 watts minimum; 80 watts maximum
Sensitivity (2.83V/1m)	90dB SPL
Square Micro Trim Grille (WxH)	6.77" (171.8mm)
Square Trimless Grille (WxH)	6.42" (163mm)
Square Micro Trim Grille (WxH)	6.77" x 6.77" (171.8mm x 171.8mm)
Square Trimless Grille (WxH)	6.42" x 6.42" (163mm x 163mm)
Speaker Mounting Depth (D)	4.61" (117.1mm)
Mounting Depth + Retrofit Encl.	5.75" (146.1mm)
Cut-Out Dims (Dia)	5.875" (149mm)
Shipping Weight	3 lbs. (1.4kg)

DIMENSIONAL DRAWINGS

Cut-Out Height · Cut-Out Width
Front View

Mounting Depth (Open Back)
Side View

Mounting Depth + Retrofit Enclosure
Side View

VX 4" ROUND ACCESSORIES

VX4R-GRILLE-T 4" Micro Trim Round Grille / Pair	93573
VX4R-GRILLE-NT 4" Trimless Round Grille / Pair	93574
VX4SQ-T 4" Micro Trim Square Adapter / Pair	96029
VX4SQ-T-5PR 4" Micro Trim Square Adapter / 5xPair	96032
VX4SQ-NT 4" Trimless Square Adapter / Pair	93585
VX4SQ-NT-5PR 4" Trimless Square Adapter / 5xPair	93588
VX4-ENCL-R 4" Round Enclosure / Pair	96443
FLEXBRK-4-R 4" Round Flex Bracket / 5x Pair	92471