



**Lodge Solar Speaker 4 Series 2
Specification Sheet – 2025**

Feature	Description
Audio	
Amplifier	50 Watt Class-D Amplifier
Tweeter	¾" tuned dome tweeter for high frequencies
Midrange/Bass	4" tuned driver for midrange/bass
Subwoofer	4" passive radiator for deep bass
Sampling Rate	24-bit/96 KHz Sampling
Connectivity	
Bluetooth 5.3	100ft plus range for single speaker; 40-60ft for 2 or more speakers connected via lodgeLINK™ mode.
Stereo Mode	True Wireless Stereo when two speakers connected, and stereo mode activated.
Multiple Speakers	Connect unlimited number of speakers together within the lodgeLINK broadcast coverage range. Need to use lodgeLINK feature built in all lodge speakers.
Charging	
Solar Panels	4 panels on sides and top of speaker providing 180 square inches of solar capturing surface area.
Battery	7.4V - 10,000mAh (internal Li-ion Rechargeable)
USB-C input	Molex USB-C 16 Pin Connector. Rated IP68
Playtime	Daytime with full sunlight - Infinite non-stop playtime; Nighttime (after sunset) or indoor listening – 15-30 hours of playtime depending on volume
General	
What's in the box	Welcome card with set-up QR code; USB-C cable; lodge solar speaker; two piece in-ground speaker stake; round metal plate to attach speaker to stake.
Dimensions H X W X D (overpack)	16" X 10 ½" X 9 ¼"
Dimensions H X W X D (retail)	14" X 9 ¾" X 8 1/8"
Dimensions H X W X D (unit)	10.5" X 7" X 6"
Weight (inbox)	9.75 lbs
Weight (unit)	7.5 lbs
Operating temperature	32 -113 F
Storage temperature (ideal)	20 – 100 F (60-85 F)
Water and Dust Protection	Meets IP66 water and dust resistance standards