




1. Parts list



A Camera x 1



B Camera power extension cable (A) x 1



C Camera harness x 1



D Screw x 4



E User's manual x 1

2. Function introduction

Key features

High sensitive 1/4" DSP Color CMOS built-in

380 TVL Horizontal resolution

Remarkably True Color reproduction

Remarkable day/night performance of 0Lux at F2.0

Excellent Auto White Balance

Waterproof(IP67)

Reverse Image

*Beautiful design & anti-scratch coating

The camera design matches well with the products quality. It looks so elegant as much as the camera quality stands for. The unique face aims to best fit to the environment decorative to any place. It lasts its beautiful shape long time with scratch-free coating.

specification

Model	VTL200CIR/VTL300CIR
Image	1/4 DSP Color CMOS
Effective pixels	640(H)X480(V)
Horizontal resolution	380 TV Lines
Total number of pixels	300k
Min illumination	0Lux(IR ON)
Synchronizing system	Internal
Scanning system	2:1 interlaced
Video output	1Vp-p 75ohm
S/n ratio	More than 48db
Electronic iris	1/50 to 1/1000 sec
White balance	AUTO
Gain control	AUTO
Lens mount	2.1mm
Viewing Angle	140° wide angle of view
Power source	DC12V
Operating temp	-4° F~+122° F(-20° C~+50° C)
Storage temp	-40° F~+176° F(-40° C~+80° C)
Waterproof	Ip67
Led	6 PCS
IR distance	6 M

3. Dimension(mm)&wiring

