

CyberPower

GX1325U SINE WAVE BATTERY BACKUP

Protects high end electronics from power interruptions and power surges.

The CyberPower GX1325U Sine Wave Battery Backup delivers sine wave power — the highest level of power quality — to protect your high end computers, TVs, home theater equipment, gaming systems and network devices from harmful power interruptions and power surges. Equipped with 10 surge-protected outlets (5 outlets also provide battery backup), the GX1325U also features Automatic Voltage Regulation (AVR) for power stability, two USB charging ports, phone and network port protection, and an interactive LCD panel to monitor power conditions.

A Three-Year Warranty ensures that this UPS has passed our highest quality standards in design, assembly, material and workmanship, further protection is offered by a \$425,000 Connected Equipment Guarantee.

TYPICAL APPLICATIONS

- Desktop Computers
- Home Theater Equipment
- Gaming Systems
- Personal Electronics
- Home Networking
- Routers & Modems

Feature

- 1325VA / 810W
- Line Interactive Topology
- Active PFC Compatible
- ENERGY STAR® Qualified
- Full-time Surge Protection and Battery Backup
- Mini-Tower Form Factor
- 10 Outlets / USB / Network Ports
- PowerPanel® Personal Edition
- 3-Year Warranty



GX1325U SINE WAVE BATTERY BACKUP

SPECIFICATIONS

GENERAL

UPS Topology	Line Interactive
Energy Saving	GreenPower UPS™ Bypass
ENERGY STAR® Qualified	Yes
Active PFC Compatible	Yes

INPUT

Voltage	90Vac - 139Vac
Adjustable Voltage Range	78Vac - 142Vac
Frequency	57Hz - 63Hz
Plug Type	NEMA 5-15P
Plug Style	Right Angle, 45° Offset Right
Cord Length	5'

OUTPUT

VA	1325
Watts	810
On Battery Voltage	120Vac ± 5%
On Battery Frequency	60Hz ± 1%
Automatic Voltage Regulation	12%
On Battery Waveform	Sine Wave
Outlets - Total	10
Outlet Type	NEMA 5-15R
Outlets - Battery & Surge Protected	5
Outlets - Surge-Only Protected	5
USB Charging Ports	2
USB Charging Amperage	1.0A (shared)
Overload Protection	Internal circuitry limiting / circuit breaker
Transfer Time	4ms

BATTERY

Runtime at Half Load (min)	9
Runtime at Full Load (min)	3
Battery Type	Sealed Lead-Acid
Battery Size	12V/7AH
Hot-Swappable	No
Replacement Battery	RB1270X2A
Battery Quantity	2
User Replaceable	Yes
Typical Recharge Time	8 Hours



PROTECTIONS

Surge Suppression	1,030 Joules
Phone RJ11 / Ethernet RJ45	1-In, 1-Out (Combo)
Coax Protection RG6	1-In, 1-Out
EMI/RFI Filtration	Yes

MANAGEMENT & COMMUNICATIONS

Multifunction LCD Panel	Displays: Current/Load Level, Runtime, Battery Level, AVR In Use, Battery In Use, Input Voltage, Output Voltage, Output Frequency, Overload, Wiring Fault, Silent Mode
HID Compliant USB Port	Yes
Serial Port	Yes
EPO Port	No
Management Cable	USB Cable
LED Indicators	Power On, Wiring Fault
Audible Alarms	On Battery, Low Battery, Overload, Fault
Software	PowerPanel® Personal Edition

PHYSICAL

Form Factor	Mini-Tower
Dimensions (WxHxD) (in.)	3.9 x 10.4 x 14.2
Weight (lbs.)	20.3

ENVIRONMENTAL

Operating Temperature	32°F to 104°F / 0°C to 40°C
Operating Relative Humidity	0% - 90% (non-condensing)

CERTIFICATIONS

Safety	UL1778, cUL 107.3, FCC DOC Class B
Environmental	RoHS Compliant

WARRANTY

Product Warranty	3 Years Limited
Connected Equipment Guarantee	Lifetime
CEG Amount	\$425,000