



**Display:**

Type:	DLP LED
Resolution Type:	WVGA (854x480)
Resolution:	854 x 480
Brightness (Lumens):	120 LED (50 ANSI)
Display Size (in.):	24 - 100 in. / 0.6 - 2.54 m
Throw Distance:	2.1 – 8.7 ft / 0.6 - 2.7 m
Throw Ratio:	1.2
Keystone:	Vertical (+/- 40°)
Light Source (watt):	RGB LED
Light Source Life, Normal (hours):	30000
Color Depth:	1.07 Billion Colors
Dynamic Contrast Ratio:	120,000:1
Aspect Ratio:	16:9

**Video Signal:**

Frequency Horizontal:	15h-135kHz
Frequency Vertical:	23-120Hz

**Compatibility:**

PC Resolution (max):	1920 x 1080
PC Resolution (min):	640 x 480
Mac® Resolution (max):	1920 x 1080
Mac® Resolution (min):	640 x 480

**Connector:**

USB 2.0 Type A(1), USB 3.1 Type C(1), HDMI 1.4 (with HDCP 1.4)(1), Wifi(5 GHz), Bluetooth(Bluetooth 4.0)

**Audio:**

Internal Speakers:	2W (x1)
--------------------	---------

**Power:**

Voltage:	AC adapter 5V, 4A
Consumption (typical):	20W
Stand-by:	<0.5W

**Controls:**

On Screen Display:	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)
--------------------	--

**Operating Conditions:**

Temperature:	32-104° F (0 - 40° C)
Humidity (non-condensing):	0-90%

**Weight (imperial):**

Net (lbs):	0.7
------------	-----

**Weight (metric):**

Net (kg):	0.3
-----------	-----

**Dimensions (imperial) (WxHxD):**

Physical (in.):	4.3 x 4.1 x 1.1
-----------------	-----------------

**Dimensions (metric) (WxHxD):**

Physical (mm):	110.0 x 104.0 x 27.0
----------------	----------------------

**General:**

Regulations: FCC, cTUVus, ROHS

PACKAGE CONTENTS: M1 mini Plus projector, Swappable panels (Gray, Teal, Yellow), Wrist strap, USB A to Micro USB, Remote Control and Quick Start Guide

Warranty: One-year limited warranty on parts and labor, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

UPC: 766907006384

**Accessories:**

PGD-350, PJ-CASE-012, PJ-SCW-1001W, VC10, VCB10