

NVC-B12M

Smart 12MP PoE Bullet Camera with Powerful Spotlight



12MP

12MP UHD

Capture intricate details from facial features to license plates.



Color Night Vision

See through the night in full color with its spotlight on.



Smart Detection & Alerts

Get instant notifications once a person, vehicle or animal is detected.



Two-Way Audio

Speak directly to anyone who approaches your home.



Power over Ethernet

Get both power & data with a single network cable.



Remote Access

Access your live feed anytime anywhere via Reolink App/Client.



Weatherproof

Rated as IP66 to withstand the elements for year-round protection.



24/7 Recording

Work with Reolink NVRs to save days of your 24/7 footage.



Customized Motion Zone

Map out your detection to only get alerts about specific areas.




Next-Level Clarity in 12MP

Home security has entered the 12MP era. Get a clear and detailed view of your home, and see everything with incredible clarity.



Focus on True Threats

Differentiate people, vehicles, and animals from other objects and send alerts straight to your phone, so nothing important goes unnoticed.




Talk Like You're There

The built-in mic and speaker allow you to communicate clearly with arriving guests or deter intruders with a "Get Away" message.



See Through the Night in Colors

Fuzzy and pixelated night vision is now history. The powerful spotlight that keeps on all night makes the night as colorful as day.



PoE, Setup in Minutes

Transmit videos and be charged simultaneously via only one network cable. Setup is easier with no messy cables.

Gallery



One App/Client for All Control

Stay connected to your home or business anytime, anywhere.



Privacy in Your Hands

We made it a priority to ensure that your privacy is protected and your data is for your eyes only.



Model	NVC-B12M	
Note:	The cameras of the kit cannot work without the NVR.	
Video & Audio	Image Sensor	1/2.49" CMOS Sensor
	Video Resolution	Default: 4512X2512 (12 megapixels) at 20 fps
	Lens	f=4.0mm; F=1.6, with IR-cut filter
	Video Format	H.265
	Field of View	Horizontal: 93° Vertical: 49°
	Day & Night	Auto-switching with IR-cut filter
	Infrared Night Vision	30 meters (LED: 2pcs/28mil/850nm)
	Color Night Vision	Spotlight: 1pcs/4.3W/6500K/700 Lumens
	Audio	Two-way audio (via Reolink App/Client)
Power	POE	IEEE 802.3af, 48V Active
	DC Power	DC 12.0V=1A, <12W
Interface	Power	DC power port
	System	Reset button
	Ethernet	One 10M/100Mbps; RJ45
	Audio	Built-in microphone and speaker
Software Features	Frame Rate	Mainstream: 2fps - 20fps (default: 20fps) Substream: 4fps - 20fps (default: 10fps)
	Code Rate	Mainstream: 3072Kbps - 10240Kbps (default: 8192Kbps) Substream: 128Kbps - 1024Kbps (default: 768Kbps)
	Smart Alarm	Motion detection; person detection; vehicle detection; animal detection
Working Environment	Temperature	Operating temperature: -10°C~+55°C (14°F~131°F)
	Humidity	Operating humidity: 10% ~ 90%
	Waterproof	IP67
Size & Weight	Dimensions	67 x 187mm
	Weight	460g
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/ .



- | | | |
|-------------|------------------------|-------------------|
| 1 Mount | 2 Metal Aluminum Case | 3 Daylight Sensor |
| 4 Spotlight | 5 High Definition Lens | 6 IR LEDs |



- | | | |
|------------------|----------------|-----------|
| 1 Power | 2 Reset Button | 3 Network |
| 4 Waterproof Lid | | |

Best Companion



PoE Injector




Reolink NVR



Ethernet Cable



Waterproof Lid



Junction Box D20

Download Free Reolink App & Client

Learn more: <https://reolink.com/software-and-manual/>



Terms and Privacy

Terms and Privacy: Use of the product is subject to your agreement to the Terms of Service and Privacy Policy at reolink.com. Keep out of reach of children.

Limited Warranty

Limited Warranty: This product comes with a 2-year limited warranty. Learn more: <https://reolink.com/warranty-and-return/>

NVS8

8-Channel PoE NVR for 24/7 Reliable Recording



8-Channel

The NVR can connect up to 8 Reolink PoE/WiFi cameras.



Built-in 2TB HDD

Store videos locally on a pre-installed 2TB HDD (upgradable to 12TB).



24/7 Recording

Continuous recordings directly to your hard drive with expandable storage.

16MP

Support up to 16MP

Record up to 16MP ultra-clear videos on every channel.



All-Around Protection

Stand guard over every inch of your property with up to 8 cameras.



Centralized Security

Take full control of all cameras with centralized NVR management.



PoE

The plug-and-play setup saves you time and effort.



Remote Access

Easily check live feeds from anywhere via the Reolink App/Client.



Local Access

Access the live feeds offline via a monitor or an HD TV.



Centralize Your Security

Connect your Reolink cameras to the NVR for centralized management, all-round surveillance, and more. Everything is under your control.



24/7 Continuous Recording

Save days of your 24/7 footage securely and locally on a 2TB HDD (upgradable to 12TB). Never worry about data loss.




Your Personalized Security Solution

The 8-Channel NVR is compatible with all our IP cameras - up to 16MP PoE/WiFi cameras. Have fun customizing your own security system.



PoE - Easy Setup

Simply connect your cameras to the NVR with a network cable for both data & power transmission. No messy cables, ideal for DIY lovers.



Local and Remote Access & Control

Access the live streams of all cameras anywhere with the Reolink App/Client, or connect the NVR to a monitor for local monitoring.

Gallery



One App/Client for All Control

Stay connected to your home or business anytime, anywhere.



Privacy in Your Hands


We made it a priority to ensure that your privacy is protected and your data is for your eyes only.



Model	NVS8	
Hardware	Hardware	N7MB01
Video/Audio Input	IP Video Input Audio Input	PoE IP Camera x 8 Cameras with built-in mic
Video/Audio Output	HDMI Output Resolution VGA Output Resolution Audio output	3840x2160, 1920x1080, 1280x1024, 1280x720, 1024x768 1920x1080, 1280x1024, 1280x720, 1024x768 1-Channel, RCA
Decoding	Video Format Live View / Playback Resolution Synchronous Playback	H.264, H.265 7680×2160, 4608×1728, 4512×2512, 4096×3072, 3840×2160, 2560×2560, 2560×1920, 2560×1440, 2048×1536, 2304×1296, 1080p, 720p Up to 4 channels
HDD	SATA External HDD Capacity	1 x SATA interface (1 x 2TB HDD included) 1 eSATA Interface for HDD Up to 12TB (max. 6TB capacity for each HDD)
External Interface	USB Interface Network Interface	2 x USB 2.0 1, RJ-45 10/100 Mbps self-adaptive Ethernet interface for LAN/ WAN 8, RJ-45 10/100 Mbps self-adaptive PoE Ethernet interface for IP camera
PoE	Max. Power Per Port Supported Standard	25W IEEE 802.3af/at
Network	Network Protocols Browsers Supported OS Supported Max. User Access	HTTP, TCP/IP, UDP, DHCP, P2P, UPNP, RTSP, SMTP, SSL/TLS, DNS, DDNS, NTP, FTP Edge, Firefox, Chrome, Safari PC: Windows, Mac OS; smartphone: iOS, Android 20 users (1 admin account & 19 user accounts); supports up to 12 simultaneous video streams (10 substreams & 2 mainstreams)
General	Power Supply Power Consumption Working Environment Dimensions Weight	DC 48V~53V <10W (Without HDD&PoE) Temperature: -10°C~+45°C (14°F~113°F); humidity: 10%~90% 260 x 41 x 230mm 1.4kg
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/ .



- 1 Power LED/HDD LED
- 2 USB Port



- 1 On/Off Switch
- 2 eSATA
- 3 RJ45
- 4 Power Input
- 5 Audio Out
- 6 USB Port
- 7 HDMI Port
- 8 VGA Port
- 9 Network

Best Companion



Mouse

Download Free Reolink App & Client

Learn more: <https://reolink.com/software-and-manual/>



Terms and Privacy

Terms and Privacy: Use of the product is subject to your agreement to the Terms of Service and Privacy Policy at reolink.com. Keep out of reach of children.

Limited Warranty

Limited Warranty: This product comes with a 2-year limited warranty. Learn more: <https://reolink.com/warranty-and-return/>