



## Replacement LED Headlight for Motorcycles

**HE-BHL701 (Black Front Face)**

**HE-SHL701 (Silver Front Face)**

**Applications: Motorcycles with a 7"  
round headlight**

**Tools Needed** – Phillips Screwdriver

### **Instructions:**

Refer to the motorcycle's instructional manual for proper headlight removal.

For most applications follow these steps:

1. Remove trim ring (if applicable) by removing (1) Phillips screw at bottom of trim ring.
2. Remove (4) screws in the inner headlight retaining bracket and headlight. On 2013 and older Harleys this retaining ring will not be reused however the 4 screws will be reused.

3. On 2013 and older Harleys you must use the **HEISE HE-HB7** headlight bracket. Reuse the (4) screws taken out of the old headlight retaining bracket and install them with the new headlight retaining bracket. Plug the H4 harness into the new **HEISE** LED headlight.
4. Replace inner retaining ring.
5. Replace trim ring (if applicable).
6. Turn on headlight to ensure connections where properly made.
7. Adjust headlight pattern if needed.

### **Specifications:**

(2) 10 watt and (4) 5 watt CREE LEDs  
2000LM low beam, draws 1.8a @ 13.8v  
3000LM high beam, draws 2.6a @ 13.8v  
DOT approved for on-road use  
LED color temp: 6500K  
Polycarbonate lens  
H4 connector

Designed for use with most motorcycles using a 7" headlight



**1-800-221-0932**      [www.HeiseLED.com](http://www.HeiseLED.com)  
**460 Walker Street, Holly Hill, FL 32117**