

说明书

版式设计要求:

1. 字体: 标题为Myriad Pro SemiBold, 内容为 Myriad Pro light;
2. 上下页边距为9mm, 左右边距为8mm;;
3. 标注说明书长宽尺寸, 单位mm.

140mm

Waterdrop

— PLUS —

Model: WDP-F19

The WDP-F19 is a compatible replacement for the following water filters:

GE® filters

RPWF, RWF1063, RWF3600A, WSG-4, DWF-36, R-3600, MPF15350, OPFG3-RF300, WF277

* Claims of compatibility verified by manufactures internal testing.

Filter life: 6 months or 300 gallons (whichever comes first)



REPLACEMENT ELEMENT


Tested and Certified by NSF International against **NSF/ANSI Standards 42, 53 and 401** in model EFF-6019S for the reduction of the claims specified on the Performance Data Sheet, and to **NSF/ANSI 372 (≤0.25% lead)**.

Installation instructions

Before installation:

- Shut off the cold-water supply to the refrigerator before installation. Turn on the refrigerator water dispenser to release water pressure, letting water drain from the pipe completely.
- It is normal for black carbon fines (particles) to appear on the outside of your filter. This happens when the filter is jarred in shipping. It is safe to simply wipe it off.
- The filter connectors are larger to prevent leaks. You might have to twist the filter hard to make sure the connection is secure.

1. (a) Open filter compartment door and remove the old filter by lifting it upward until it can't move.
(b) Gently pull the old filter straight out of the cartridge holder (Do Not Twist Cartridge.) A small amount of water may drip down.
2. Remove protective cap from new replacement filter.
3. (c) Insert filter into the cartridge holder, and push until filter



is fully seated into position.

Note: Please pay attention to direction of the filter during installation. Refer to the picture for details.

(d) Gently swing the filter cartridge downward back into a vertical position. If the filter does not move downward easily, check the alignment on the top of the filter with the cartridge holder and ensure that it is fully seated.

4. Double check for any leaks.

5. Run water from the dispenser for 5 minutes at 0.5 gpm (about 2.5 gallons) to clean the system and prevent sputtering.



Resetting your filter indicator:

Note: These are the most common filter reset instructions. If the instructions don't work for your refrigerator brand, see the documentation that came with your refrigerator.

| Refrigerator brand | Instructions |
|--------------------|---|
| GE® systems | Press and hold the reset button on the dispenser for 3 seconds. |

Storage and maintenance:

- Replace your filter every 6 months or 300 gallons to prevent bacteria and fungus growth in your filter, supply lines, and storage tank.
- Keep your unused filters in a cool, dark, and dry place until you need them.
- If you do not use your water dispenser for more than four days, run two gallons of water before using it to prevent bad tasting water.

Frequently asked questions:

Q: Why is it difficult to twist the new filter into the filter housing?

A: The connector may expand because of water pressure. Therefore, it is recommended you push the new filter in with a little bit of force, but not too hard. Then turn it clockwise.

Q: Do I need to flush the filter after installation?

A: After installation, it is highly recommended you run water for a few minutes before using. Water filters are made from advanced coconut carbon block, so there are some carbon fines in the filter. Flushing removes the carbon fines to produce clean water.

210mm

Q: Must the filter be changed every 6 months?

A: Yes, you must replace the filter every six months or sooner if water flow is reduced or if there is heavy sediment / rust present. Over-used filters will degrade the filtration performance.

Warning:

To reduce the risk of property damage due to water leakage, this filter MUST be installed in accordance with the manufacturer's specifications and instructions. This filter unit must be replaced every 300 gallons or 6 months. Failure to follow instructions and operating specifications will void your warranty. Further, manufacturer assumes no responsibility or liability for damages arising out of misuse of the product. GE® is a registered trademark of General Electric Corp. GE® is used for reference purposes only.

*The service life mentioned above is subject to chlorine reduction. Actual result varies according to the local water quality.

Performance data sheet

System Model No.: **EFF-6019S**

Replacement Filter Cartridge Model No.: **WDP-F19**

Operating specifications:

Operating Temperature: 33-100°F/0.6-38°C

Working Pressure: 20-100 psi/140-689 kPa

Rated Capacity: 300 gallons/1,137 litres

Flow Rate: 0.5 gpm/1.9 lpm

SCAN ME!



Please scan the code to get detailed Performance Data sheet.

Manufacturer Technical Support

Tel: 1-888-352-3558 (U.S.)

E-mail: service@waterdropfilter.com

Made in China V041
Qingdao Ecopure Filter Co., Ltd.



图像颜色请依据数码稿印刷
请不要擅自变更来稿件, 如须修改, 请联系伊可普做有关决定

印刷品技术要求 IMPORTANT PRINTING CAUTION

1. 印刷要求 覆光膜 覆亚膜 UV油 吸塑油 过油 丝印
2. 材质要求 80g双胶纸, 双面印刷
3. 颜色要求 单黑印刷
4. 版面要求 印刷品文字线条印迹清晰、无重影;印刷品套印准确无偏色、溢墨、指痕等;印刷品上光层均匀、光亮、牢固无粘连;覆膜表面平整、无褶皱、光泽度好;纸张材质正确, 切边整齐、压线深浅适中、洁净、无斑点和条痕。

伊可普

青岛伊可普电器有限公司包材设计图纸

| | | | |
|-------------------|---|------------------|----------|
| 品牌 BRAND NAME | Waterdrop | 工厂型号 ITEM NO. | EFF-6019 |
| 物料编码 INNER CODE | 03070206019AP | 版本号 VERSION | V041 |
| 包材文件名称 FILE NAME | 03070206019AP WDP-F19-401-说明书-V041 | | |
| 规格 MEASURE | 210*140mm | 页数 PAGE | 4P |
| 设计负责人 DWG BY | 张鑫龙 | 审核日期 VERIFY DATE | |
| DCR变更 (变更日期+变更描述) | 2021.11.23 增加客服24H7D365信息 2023.06.07: 增加二维码替换认证部分的PDS表 | | |