# Polaroid I-2
# Instant Camera

polaroid



## Technical Specifications

| Product | Polaroid I-2 Instant Camera | | |
|---|---|---|---|
| **Color** | **PRD** | **EAN** | **GTIN** |
| Black | 009078 | 9120096774034 | 19120096774031 |
| **Launch Date** | 7 September 2023 | | |
| **RRP** | $599.99, €699.99, £599.99 | | |
| **HS or HTS Code** | 9006409000 (US)<br>9006400000 (EU) | | |
| **Country of Origin** | China (CN) | | |
| **Packaging Contents** | Polaroid I-2 Camera<br>Protective Lens Cap<br>USB-C Charging Cable (1.2m)<br>Handle Strap<br>Quick Start Guide<br>Safety & Compliance Leaflet | | |
| **Product Box** | 209 x 156 x 131 mm<br>8.23" x 6.1" x 5.1" | | |
| **Product Box Weight** | 343.3 grams<br>12.1 ounces | | |
| **Shipper** | 416 x 331 x 254 mm<br>16.4" x 13.0" x 10" | | |
| **Shipper Weight** | 925.7 grams<br>32.7 ounces | | |
| **Units per Shipper** | 6 | | |
| **Product Dimensions** | 149.9 x 119.3 x 91.2 mm<br>5.9" x 4.7" x 3.6" | | |
| **Product Weight** | 563 grams<br>19.9 ounces | | |

| | |
|---|---|
| **Battery** | Lithium-Ion Polymer Soft-Pack Battery |
| **Battery Report** | Available |
| **Outer Shell** | ABS, PC, PMMA, Aluminum Alloy, Stainless Steel |
| **Shutter System** | Fastest shutter speed 1/250, exposure time range is 1/250~30s., and Bulb mode (up to 99hrs.) |
| **Aperture** | Maximum f8 practical aperture, available apertures, f8, 11, 16, 22, 32, 45, 64 |
| **Lens** | 3-element lens with continuous autofocus system capable of f8 aperture across 0.4m (1.3') ~ ∞ range controlled via stepping motor |
| **Focal Length** | 98mm |
| **Field of View** | Horizontal 43°, vertical 44°<br>Center weighted single zone metering (60% metering coverage of optical FOV) |
| **Flash System** | Vacuum discharge tube strobe range 2.5m @f8 / 8.2' @f8 |
| **Compatible With** | i-Type Film<br>600 Film<br>SX-70 Film |
| **App Enabled** | Fully control your camera remotely For iOS & Android |
| **Device Interface Ports** | Type C charging input x1<br>2.5mm external flash sync. port. x1 |
| **Display** | Outer display and VF display for aperture, shutter speed, modes, film count, battery level, function display etc.<br>Outer: White(16 grayscale)<br>VF: Mono LCM, yellow display with black background |
| **Other** | Tripod mount<br>Build in lens filter thread mount |