PT7050SF

GE Profile[™] Series 30 in. Built-In Single Convection Wall Oven

DIMENSIONS AND INSTALLATION INFORMATION (IN INCHES)

MOST 30" WALL CABINETS CAN BE USED WITH THIS UNIT.

NOTE: These ovens are not approved for stackable installations. Cabinets installed adjacent to wall ovens must have an adhesion spec of at least a 194°F temperature rating.

Door handle protrudes 3" from door face. Cabinets and drawers on adjacent 45° and 90° walls should be placed to avoid interference with the handle.


Electric wall ovens are not approved for installation with a plug and receptacle. They must be hard wired in accordance with installation instructions.


INSTALLATION INFORMATION:

Before installing, consult installation instructions packed with product for current dimensional data.

Side-by-side installations require at least 2" between cutouts.


KW RATING			
240V	4.5		
208V	3.4		
BREAKER SIZE			
BREAK	ER SIZE		
BREAK 240V	ER SIZE 20 Amps		
	Г		





P	T7	70	5	O
P	T 7	0	5	O

Cabinet	30"
A – Overlap of oven at top of cutout	1"
B – Overlap of oven over side of edges of cutout	3/4"
C – Overlap of oven at bottom of cutout	1-1/4"
Oven	
D – Install depth	23-1/2"
E – Overall height with trim	28-5/8"
F – Overall width	29-3/4"



2 x 4 or equivalent runners level with bottom of cutout and flush with sides of cutout or solid bottom floor.

9-1/2" MAX.

Dimension and installation information are shown in inches.











PT7050SF

GE Profile[™] Series 30 in. Built-In Single Convection Wall Oven

OPTIONAL UNDERCOUNTER DIMENSIONS AND INSTALLATION INFORMATION


NOTE: 36" ribbon cooktop are approved for use over GE 30" single wall ovens and warming drawers. 30" ribbon cooktops are approved for use over 30" and GE 27" single wall ovens and warming drawers. Refer to cooktop and wall oven installation information packed with products for current dimensional data.

NOTE: Door handle protrudes 3" from door face. Cabinets and drawers on adjacent 45° and 90° walls should be placed to avoid interference with the handle.

INSTALLATION INFORMATION: Before installing, consult installation instructions packed with products for current dimensional data and for alternate installation options.

ELECTRIC WALL OVENS ARE NOT APPROVED FOR INSTALLATION WITH A PLUG AND RECEPTACLE. THEY MUST BE HARD WIRED IN ACCORDANCE WITH INSTALLATION INSTRUCTIONS.

Gas or electric cooktops may be installed over this oven. See cooktop installation instructions for cutout size. See label on top of oven for approved cooktop models.





PT7050SF

GE Profile[™] Series 30 in. Built-In Single Convection Wall Oven

FEATURES AND BENEFITS

True European Convection with Direct Air - Bakes evenly as warm air blows from the top in and around bakeware

Ten-pass bake element - Even baking is assured with heat that covers more surface area ${\bf r}$

Ten-pass dual broil element - Large and small dishes brown evenly with two, full-coverage elements

Self-clean heavy-duty roller rack - Easily access items with a rack that glides smoothly

Progressive halogen oven lighting - See what you're baking with lights that slowly illuminate the oven

Self-clean with steam clean option - Clean your oven the way you want

Glass touch controls - Set temperatures quickly and clean with little effort

 $5.0~\mathrm{cu}.$ ft. oven capacity - Cook more dishes at once

Black gloss oven interior - Enjoy a clean and sleek appearance

Hidden bake - Make cleanup easy by eliminating hard-toreach areas

Model PT7050SFSS - Stainless steel

GUARANTEED FIT

Replacing a similar wall oven from GE or another brand? GE wall ovens are guaranteed for an exact fit to make replacement easy

Visit geappliances.com for more info



