



thermaltake

TOUGHPower SERIES
POWER SUPPLY

TOUGHPower PF1 750W



TOUGHPower PF1 750W

DATASHEET



thermaltake

TOUGHPower SERIES POWER SUPPLY

TOUGHPower PF1 750W

Ultra Quiet

Hydraulic Bearing Fan

Smart Zero Fan

Low Ripple Noise

Fully Modular

Flat Cables

100% Japanese

Capacitors

10 YEAR
Warranty



Features

- Continuous output at 50°C/122°F operating environment.
- 80 PLUS Platinum Certified.
- 100% high quality Japanese capacitors.
- < 30mV low ripple noise design.
- Extremely strict voltage regulation < $\pm 2\%$
- Hold up time > 16 milliseconds.
- New Board Technology Offering Single side SMD.
- Fully modular low-profile flat black cables.
- Ultra Quiet 120mm Hydraulic Bearing Fan delivers excellent airflow.
- Smart Zero Fan: Minimizes undesired noise.
- High amperage single +12V rail design.
- Intel C6/C7 states & ErP ready
- Built-in industry grade protections: OCP, OVP, UVP, OPP, SCP, OTP
- Dimension: 150mm(W)x86mm(H)x140mm(D).
- Safety approvals: CE/UL/TÜV/FCC/BSMI/CCC/ EAC certifications.



thermaltake

TOUGHPower SERIES
POWER SUPPLY**TOUGHPower PF1 750W**

GENERAL INFO	
P/N	PS-TPD-0750FNFAPx-1
Model	TTP-750AH2FKP
Max. Output Capacity	750W
Peak Output Capacity	900W
Color	Black
Dimension (W/H/D)	150mm(W) x 86mm(H) x 140mm(D)
PFC	Active PFC
Power Good Signal	100-500 msec
Hold-Up Time	> 16msec at 100% of full load
AC INPUT	
Input Current	10A
Input Frequency Range	50Hz - 60Hz
Input Voltage	100V – 240V~
ENVIRONMENTAL	
Operating Temperature	5°C to + 50°C
Operating Humidity	20% to 85%,non-condensing
Storage Temperature	-40°C to + 55°C
Storage Humidity	10% to 95%, non-condensing
Cooling System	12cm hydraulic bearing fan
MISCELLANEOUS	
Efficiency	Meet 80PLUS®Platinum at 115Vac input.
MTBF	120,000 hrs minimum
Safety Approval	CE/UL/TÜV/FCC/BSMI/CCC/ EAC
PCI-E CONNECTOR	
PCI-E 6+2pin	4