

## KM 7730 FR

30-inch induction cooktop, operated with its own controls  
with 4 round cooking zones



- Intuitive quick selection via number sequences – Smart Select
- Versatile – 4 cooking zones, 1 extra large with diameter of 11 in
- With a width of 30 5/8 (775) in (mm) and stainless steel frame for proud-mounting
- Shortest heating-up times – TwinBooster
- Communication with the ventilation hood – automatic Con@ctivity function

EAN: 4002516611493 / Material number: 12074200 /  
Old Material Number: 26773000USA

|                                      |                       |
|--------------------------------------|-----------------------|
| <b>Heating type</b>                  |                       |
| Fuel type                            | Induction             |
| <b>Design</b>                        |                       |
| Independent of oven                  | •                     |
| <b>Design</b>                        |                       |
| Elegant glass ceramic surface        | •                     |
| Surface-mounted/flush-fit            | -/-                   |
| Ceramic surface color                | Black                 |
| All-round stainless-steel frame      | •                     |
| Proud installation                   | •                     |
| <b>Cooking zone details</b>          |                       |
| No. of rings                         | 4                     |
| Number of cooking areas              | 0                     |
| Maximum number of pans               | 4                     |
| <b>1st cooking zone/cooking area</b> |                       |
| Position                             | front left            |
| Type                                 | Variable cooking zone |
| Size in mm                           | Ø 180-280             |
| Max. Booster power rating in W       | 3000                  |
| Max. rating in W                     | 2600                  |
| Max. TwinBooster power rating in W   | 3700                  |
| <b>2nd cooking zone/cooking area</b> |                       |
| Position                             | rear left             |
| Type                                 | Variable cooking zone |
| Size in mm                           | Ø 100-160             |
| Max. Booster power rating in W       | 1700                  |
| Max. rating in W                     | 1400                  |
| Max. TwinBooster power rating in W   | 2200                  |
| <b>3rd cooking zone/cooking area</b> |                       |
| Position                             | rear right            |
| Type                                 | Variable cooking zone |
| Size in mm                           | Ø 140-190             |
| Max. Booster power rating in W       | 2500                  |
| Max. rating in W                     | 1850                  |
| Max. TwinBooster power rating in W   | 3000                  |
| <b>4th cooking zone/cooking area</b> |                       |
| Position                             | front right           |
| Type                                 | Variable cooking zone |
| Size in mm                           | Ø 140-190             |
| Max. Booster power rating in W       | 2500                  |
| Max. rating in W                     | 1850                  |
| Max. TwinBooster power rating in W   | 3000                  |
| <b>User convenience</b>              |                       |
| Networking with Miele@home           | •                     |
| Automatic function                   | Con@ctivity 3.0       |
| Pan and pan size recognition         | •                     |
| Operation via touchpad sensors       | Smart Select          |
| Display color                        | Yellow                |

## KM 7730 FR

30-inch induction cooktop, operated with its own controls  
with 4 round cooking zones



EAN: 4002516611493 / Material number: 12074200 /  
Old Material Number: 26773000USA

|   |                    |
|---|--------------------|
| Permanent pan recognition                               | •                  |
| Stop & Go function                                      | •                  |
| Wipe protection   | •                  |
| Recall function   | •                  |
| Minute minder   | •                  |
| Automatic switch-off for all rings                      | •                  |
| AutoBoost   | •                  |
| Keep-warm function                                      | •                  |
| Individual setting options (e.g. acoustic signal tones) | •                  |
| <b>Cleaning convenience</b>                             |                    |
| Easy to clean ceramic glass                             | •                  |
| <b>Safety</b>   |                    |
| Safety cut-out  | •                  |
| Lock function   | •                  |
| System lock   | •                  |
| Integrated cooling blower                               | •                  |
| Overheating protection                                  | •                  |
| Residual heat indicator                                 | •                  |
| <b>Technical data</b>                                   |                    |
| Dimensions (width) in in. (mm)                          | 30 5/8 (775)       |
| Dimensions (height) in in. (mm)                         | 3 1/8 (78)         |
| Dimensions in mm (depth)                                | 21 1/2 (544)       |
| Cutout dimensions (width) in in. (mm)                   | 28 5/8 in (724 mm) |
| Cutout dimensions (depth) in in. (mm)                   | 20 1/2 in (518 mm) |
| Casing height incl. connection box in mm                | 2 7/8 (71)         |
| Weight in lbs. (kg)                                     | 37 (17)            |
| Total connected load in kW                              | 6.60-7.60          |
| Power cord length in in. (m)                            | 3 (1.2)            |
| Voltage in V  | 208-240            |
| Frequency in Hz   | 50-60              |
| <b>Standard accessories</b>                             |                    |
| Power cord  | Yes                |

