

SONANCE

PATIO SERIES DATA SHEET

(4) SATELLITES | (4) GROUND STAKES | (1) SUBWOOFER | (1) UA 2-125 AMP

TECHNICAL SPECIFICATIONS

MODEL	SATELLITE SPEAKER	SUBWOOFER
Driver	3.5" (98mm) Anodized aluminum cone and Santoprene™ surround	8" (203mm) dual voice coil, polypropylene and Santoprene surround
Frequency Response	40Hz - 20kHz +/-3dB (System)	40Hz - 20kHz +/-3dB (System)
Crossover Frequency	125Hz	100Hz
Impedence	16 ohms nominal	8 ohms nominal per voice coil
System Impedence	8 ohms nominal	8 ohms nominal
Power Handling	50 watts minimum; 150 watts maximum	150 Watts
Sensitivity	85dB 2.83V / 1 meter	89dB Sensitivity @ 2.83V / 1 meter
Enclosure Material	High-heat ABS sealed enclosure, Non-corroding	High-heat ABS sealed enclosure, Non-corroding
Mounting Threads	1/2" NPS (National Pipe Standard)	-
Product Dims (WxHxD)	6.75" x 4.5" (171.35mm x 115mm)	21.4" x 12.4" (544mm x 315mm)
System Shipping Weight	52.8 lbs (24 kg)	52.8 lbs (24 kg)

MODEL: UA 2-125 AMPLIFIER

Number of Channels	2 (1 stereo pair)	AC Voltage	100-240Vac 50-60Hz
RMS per Channel @ 8 ohms	125 watts (8 channels driven)	Dims (WxHxD)	5.32" x 1.78" x 8.2" (135mm x 45mm x 208mm)
RMS per Channel @ 4 ohms	125 watts (8 channels driven)	Dims + Mounting Brackets (WxHxD)	5.32" x 1.78" x 8.86" (135mm x 45mm x 225mm)
Power Output - 4 ohms x1	250W (single channel)		
Frequency Response	20Hz - 20kHz		

DIMENSIONAL DRAWINGS

