



IMPORTANT SAFETY INFORMATION

- Ensure that the wall is strong enough to support the speaker.
- Ensure that wall anchors or screws are suited for the wall type and follows local practice.
- Install on a vertical wall only.
- Only use this product with Marshall Heston 120 TV soundbar.
- Installing the wall mount and the TV soundbar is a two-person job.

Packaging, and the manual, should not be mixed with general household waste.

INCLUDED IN THE BOX

- Wall mount brackets (left and right)
- Screws for fastening Heston 120 to the wall mount brackets
- Safety and installation Guide, including template - English
- Safety and installation Guide – translated

Not included: Marshall Heston 120 TV soundbar, wall anchors or screws for fastening the wall mount brackets to the wall.

BEFORE YOU START

- Purchase wall anchors or fixing screws appropriate for the kind of wall you have (plaster board, concrete, wood, etc.). If you have any doubts, seek advice from a professional.
- You will be needing tape that don't leave marks on your wall, a spirit level, pen, and a crosshead screwdriver, size 2 (Philips PH2).

At least two persons are required to install the wall mount and the TV soundbar.

STEPS

I. MEASURE AND MARK

Use the template (included in the box) on the opposite side together with a spirit level to mark the two holes for drilling. The soundbar should be mounted under the TV with at least 15 cm / 5.9 in of free space above and on each side.

II. DRILL AND MOUNT

As wall materials vary, screws for the wall are not included. Make sure wall anchors or screws must support a weight more than 30 kg. Do not tighten the screws yet!

III. ADJUST AND FASTEN

Use a spirit level to ensure that the brackets are on equal height and measure that they are exactly 688 mm / 27.1 in apart. Adjust their position if needed before tightening the screws.

IV. CONNECT CABLES

Connect all cables to Heston 120 and route the cable above or under the TV soundbar depending on where they are going.

V. FASTEN TV SOUNDBAR

Use the 4 included screws to fasten Heston 120 to the wall mount brackets using a crosshead screwdriver, size 2 (Philips PH2).