

说明书

版式设计要求:

1. 字体: 标题为Myriad Pro SemiBold, 内容为 Myriad Pro light;
2. 上下页边距为9mm, 左右边距为8mm;;
3. 标注说明书长宽尺寸, 单位mm.

140mm

Waterdrop

— Advanced —

Model: WDS-F45

The WDS-F45 is a compatible replacement for the following water filters:

Samsung®

DA97-17376B, DA97-08006C, HAF-QIN, HAF-QIN/EXP





Tested and Certified by NSF International against **NSF/ANSI Standards 42 and 53** in model EFF-6045S for the reduction of the claims specified on the Performance Data Sheet, and to **NSF/ANSI 372 (≤0.25% lead)**.

Installation instructions

Before installation:

- Shut off the cold-water supply to the refrigerator before installation. Turn on the refrigerator water dispenser to release water pressure, letting water drain from the pipe completely.
- It is normal for black carbon fines (particles) to appear on the outside of your filter. This happens when the filter is jarred in shipping. It is safe to simply wipe it off.
- The filter connectors are larger to prevent leaks. You might have to twist the filter hard to make sure the connection is secure.

1. Shut off the water supply to refrigerator.
2. Open the filter cover and turn the knob of the filter cartridge counterclockwise by 90 degrees to unlock the old filter. Then pull it out.
3. Insert the new filter cartridge and turn it clockwise to lock it into place.
4. Press and hold Filter Reset on the main panel for 3 seconds to reset the filter life.
5. Turn on the water valve to allow water to run through the dispenser for about 5 minutes (about 2.5 gallons) to expel any trapped air and clear the system.



Resetting your filter indicator:

Note: These are the most common filter reset instructions. If the instructions don't work for your refrigerator brand, check the documentation that came with your refrigerator.

Refrigerator brand	Instructions
Samsung® systems	Hold the ICE TYPE and CHILD LOCK buttons for three seconds. The water filter indicator should turn green. Note: Only hold these buttons for three seconds. Holding these buttons for five seconds cancels the reset. If you cancel the reset, repeat the procedure.

Storage and maintenance:

- Replace your filter every 6 months or 316 gallons to prevent bacteria and fungus growth in your filter, supply lines, and storage tank.
- Keep your unused filters in a cool, dark, and dry place until you need them.
- If you do not use your water dispenser for more than four days, run two gallons of water before using it to prevent bad tasting water.

Frequently asked questions:

- Q:** Why is it difficult to twist the new filter into the filter housing?
A: The connector may expand because of water pressure. Therefore, it is recommended you push the new filter in with a little bit of force, but not too hard. Then turn it clockwise.
- Q:** Do I need to flush the filter after installation?
A: After installation, it is highly recommended you run water for a few minutes before using. Water filters are made from advanced coconut carbon block, so there are some carbon fines in the filter. Flushing removes the carbon fines to produce clean water.
- Q:** Must the filter be changed every 6 months?
A: Yes, you must replace the filter every six months or sooner if water flow is reduced or if there is heavy sediment / rust present. Over-used filters will degrade the filtration performance.

⚠ Warning:

To reduce the risk of property damage due to water leakage, this filter **MUST** be installed in accordance with the manufacturer's specifications and instructions. This filter unit must be replaced every 316 gallons or 6 months. Failure to follow instructions and operating specifications will void your warranty. Further,

210mm

manufacturer assumes no responsibility or liability for damages arising out of misuse of the product. Samsung® is a registered trademark of Samsung Electronics Co., Ltd. Samsung® is used for reference purposes only.

*The service life mentioned above is subject to chlorine reduction. Actual result varies according to the local water quality.

Performance data sheet

System Model No.: **EFF-6045S**
Replacement Filter Cartridge Model No.: **WDS-F45**

Operating specifications:

Operating Temperature: 33°F - 100°F / 0.6°C - 38°C
Working Pressure: 20 psi - 100 psi / 140 kPa - 689 kPa
Rated Capacity: 316 gallons / 1,196 litres
Flow Rate: 0.5 gpm / 1.9 lpm

SCAN ME!



Please scan the code to get detailed Performance Data sheet.

Manufacturer Technical Support

Tel: 1-888-352-3558 (U.S.)
E-mail: service@waterdropfilter.com

Made in China V042
Qingdao Ecopure Filter Co., Ltd.



图像颜色请依据数码稿印刷
请不要擅自变更来稿件, 如须修改, 请联系伊可普做有关决定

印刷品技术要求 IMPORTANT PRINTING CAUTION

1. 印刷要求 覆光膜 覆亚膜 UV油 吸塑油 过油 丝印
2. 材质要求 80g双胶纸, 双面印刷
3. 颜色要求 单黑印刷
4. 版面要求 印刷品文字线条印迹清晰、无重影; 印刷品套印准确无偏色、溢墨、指痕等; 印刷品上层均匀、光亮、牢固无粘连; 覆膜表面平整、无褶皱、光泽度好; 纸张材质正确, 切边整齐、压线深浅适中、洁净、无斑点和条痕。

伊可普

青岛伊可普电器有限公司包材设计图纸

品牌 BRAND NAME		工厂型号 ITEM NO.	EFF-6045
物料编码 INNER CODE	03070206045BP00	版本号 VERSION	V042
包材文件名称 FILE NAME	03070206045BP00 WDS-6045S-53-说明书-V042		
规格 MEASURE	210*140mm	页数 PAGE	4P
设计负责人 DWG.BY	张鑫龙	审核日期 VERIFY DATE	
DCR变更 (变更日期+变更描述)	2022.8.19 EFF通版53说明书改为WDS专版说明书 2023.06.07 增加二维码替换认证部分的PDS表		