

## DAS 4940

### Built-in ventilation hood

for installation in narrow upper cabinets with EasySwitch controls



- Perfect combination with Con@ctivity-enabled cooktops
- Light design – transparent glass panel, 36 in (90 cm) wide
- LED strip for uniform lighting
- Efficient filtration- 10-ply stainless steel grease filters
- Recirculation mode – Active AirClean or Longlife AirClean filter

EAN: 4002516496335 / Material number: 11878570 /  
Old Material Number: 28S4940TUSA

<b>General information</b>	
<b>Design</b>	
Built-in ventilation hood	•
<b>Operating modes</b>	
Recirculated mode	Can be retrofitted
Recirculation conversion kit (order separately)	DUU 151
OdorFree charcoal filter (order separately)	DKF 31-P, DKF 31-R
<b>Design</b>	
Color	Transp. glass
<b>User convenience</b>	
Miele@home	•
Automatic function	Con@ctivity 3.0
Automatic function Con@ctivity	•
Electronic controls	•
EasySwitch	•
Booster levels	1
Delayed shutdown for 5 or 15 minutes	•
Grease filter saturation indicator	•
Active charcoal filter saturation indicator	•
<b>Efficiency and sustainability</b>	
AC motor	•
<b>Cleaning convenience</b>	
Easy-to-clean canopy interior – CleanCover	•
<b>Filter system</b>	
Number of dishwasher-safe stainless steel grease filters (10-ply)	2
<b>Lighting</b>	
Number x W	1 x 3 W
Light intensity in lx	285 lx
Color temperature in K	3500 Kelvin
Light dimmer function	•
<b>Blower</b>	
Dual-action blower	•
<b>Safety</b>	
Safety shut-off	•
Single-ply safety glass (ESG)	•
<b>Technical data</b>	
Canopy width in in.(mm)	34 (861)
Canopy height in in.(mm)	2 3/4 (68)
Canopy depth in in.(mm)	12 1/8 (307)
Net weight in lbs. (kg)	38 (17.0)
Length of electrical wire in ft (m)	2 (0.8)
Standard plug fitted	•
Minimum height above electric cooktops in mm	24 1/8 (610)
Number of phases	1
Total connected load in kW	0.35
Voltage in V	120
Fuse rating in A	15

DAS 4940

Built-in ventilation hood

for installation in narrow upper cabinets with EasySwitch controls



EAN: 4002516496335 / Material number: 11878570 /  
Old Material Number: 28S4940TUSA

Frequency in Hz 60

**Installation note**

Vent connection at top

•

Vent connection at rear

•

Vent connection at top and rear

•

Installation template

•

**Standard accessories**



Non-return flap

•

## DAS 4940



Built-in ventilation hood

for installation in narrow upper cabinets with EasySwitch controls



DAS4940, Installation drawings

1) Extraction, recirculation with conversion kit DUU 150., 2) Alternative ducting connection to the rear., 3) Accessory DSM module., 4) The wall unit can be fitted with a partition after installation. The slots for the grease filters and, in recirculation mode, for the odor filters must remain accessible., The height of the wall unit and the cut-out dimensions must take into account any accessories fitted (e.g. silencer, recirculation hood conversion kit, DSM module)



DAS4940, drawing – US

1) Exhaust air, recirculation with DUU 150 conversion kit., 2) Exhaust air connection alternatively to the rear., 3) DSM module accessory., 4) The wall unit can be fitted with a partition after installation. The slots for the grease filters and, in the case of recirculation mode, for the odor filters must remain accessible., Mounted accessories must be taken into account for the cabinet height and cut-out dimensions (e.g. silencer, recirculation air conversion kit, DSM module).