Overview

HP Chromebook x360 11 G3 EE



- 1. Webcam LED
- 2. Webcam
- 3. Internal Microphone
- 4. Touchpad
- 5. Microphone (Optional)
- 6. 5MP Webcam (Optional)
- 7. Webcam LED (Optional)

Left

- 8. Volume Button
 - 9. Power Light
- 10. Power Button
- 11. USB 3.1 Type-A[™] Gen 1
- 12. USB 3.1 Type-C™ Gen 1 support charging, power delivery, video, data
- 13. Nano Security Lock Slot

Overview



- 1. Lock Key
- USB 3.1 Type-C[™] Gen 1 Port (Support Charging, Power Delivery, Video, Data)
- 3. AC Adapter and Battery Light

Right

- 4. USB 3.1 Type-A™ Gen 1 Port
- 5. MicroSD™ Memory Card Reader
- 6. Stereo Headphone / Microphone Combo Jack

Overview

AT A GLANCE

- Corning® Gorilla® Glass damage-resistant cover glass
- Enjoy affordable, convenient mobile productivity with Latest Intel® Celeron® N4020 and N4120 processors
- Designed to pass MIL STD 810 G tests, 76 cm drop on concrete and 122 cm drop on plywood, and enhanced USB-C™ connectors to stand against daily uses of plug and unplug¹
- 2 USB-C[™] ports (supports Power Delivery, DisplayPort[™], data)
- Choice of up to 8GB memory and 64GB eMMc storage
- Spill and pick resistant keyboard with HP Improved Anchored Key Design
- All-day battery life and spend less time charging with HP Fast Charge technology²
- Flexible 360°hinge, 2nd 5MP world-facing camera (Optional) and HP EMR pen (Optional) support blended-learning in laptop, tablet, tent or stand mode
- Enjoy Android[™] Apps* on Chrome OS^{™3}
- Your Chromebook boots up within 10 seconds and you can be browsing online and working in Google Apps just moments later
- Intel® 2x2 AC WLAN with MU-MIMO and HP Extended Range Wireless Lan for stable connection in dense environment
- Keyboard that can be repeatedly wiped down with common household cleaning wipes.
- Easy for small hands to grip and handle with Unique textured surface
- Degrees of IP41 certified to against access to hazardous/solid foreign objects and ingress of water
- MIL-STD-810G testing is not intended to demonstrate fitness of U.S. Department of Defense (DoD) contract requirements
 or for military use. Test results are not a guarantee of future performance under these test conditions. Accidental damage
 requires an optional HP Accidental Damage Protection Care Pack.
- 2. Recharges up to 90% within 90 minutes when the system is off or in standby mode when used with the power adapter provided with the notebook. After charging has reached 90% capacity, charging speed will return to normal. Charging time may vary +/-10% due to System tolerance.
- 3. Sold separately or as an optional feature.

NOTE: See important legal disclosures for all listed specs in their respective features sections.



PRODUCT NAME

HP Chromebook x360 11 G3 EE

OPERATING SYSTEM

Preinstalled

Chrome OS™

PROCESSOR

Intel® Celeron® N4020 with Intel® UHD Graphics 600 (1.1 GHz base frequency, up to 2.8 GHz boost frequency, 4 MB cache, 2 cores)^{1,2}

Intel® Celeron® N4120 with Intel® UHD Graphics 600 (1.1 GHz base frequency, up to 2.6 GHz boost frequency, 4 MB cache, 4 cores)^{1,2}

Intel® Celeron® N4000 with Intel® UHD Graphics 600 (1.1 GHz base frequency, up to 2.6 GHz boost frequency, 4 MB cache, 2 cores)^{1,2}

Intel® Celeron® N4100 with Intel® UHD Graphics 600 (1.1 GHz base frequency, up to 2.4 GHz boost frequency, 4 MB cache, 4 cores)^{1,2}

Processor Family

Intel® Celeron® processor (N4020, N4120, N4100, N4000)

- 1. Multicore is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. Intel's numbering, branding and/or naming is not a measurement of higher performance.
- 2. Processor speed denotes maximum performance mode; processors will run at lower speeds in battery optimization mode.

CHIPSET

Chipset is integrated with processor

GRAPHICS

Integrated

Intel® UHD Graphics 6003

Supports

Support HD Decode, DX12, and HDMI 1.4b

3. HD content required to view HD images.



DISPLAY

Touch

29.46 cm (11.6") diagonal HD IPS eDP BrightView WLED-backlit TOP+ touch screen with Corning® Gorilla® Glass 3, 220 nits, 69% NTSC (1366 x 768)^{3,4,5}

29.46 cm (11.6") diagonal HD IPS eDP BrightView WLED-backlit TOP+ touch screen with Corning® Gorilla® Glass 3 and Digitizer, 220 nits, 69% NTSC (1366 x 768)^{3,4,5}

Display Size

11.6"

29.46 cm (11.6")

- 3. HD content required to view HD images.
- 4. Sold separately or as an optional feature.
- 5. Resolutions are dependent upon monitor capability, and resolution and color depth settings.

STORAGE AND DRIVES

Primary Storage

32 GB eMMC 5.06

64 GB eMMC 5.06

6. For storage drives, GB = 1 billion bytes. Actual formatted capacity is less. Up to 8.1 GB is not user available

MEMORY

Maximum Memory

8 GB LPDDR4-2400 SDRAM

Memory

8 GB LPDDR4-2400 SDRAM 4 GB LPDDR4-2400 SDRAM

Memory Slots

Memory soldered on board Dual channel support

NETWORKING/COMMUNICATIONS

WLAN

Intel® Dual Band Wireless-AC 9560 802.11 ac (2x2) Wi-Fi® and Bluetooth® 5.0 Combo, non-vPro™7 MU-MIMO supported
HP Extended Range Wireless Lan supported

Chromecast

Chromecast Support8

- 7. Wireless access point and Internet service required and sold separately. Availability of public wireless access points limited.
- 8. Chromecast must be purchased separately.



AUDIO/MULTIMEDIA

Audio

HD Audio Dual Speakers Integrated Microphone

Camera

720p HD camera³

5 MP Rear Camera (World Facing secondary camera, Fixed Focus)⁴

- 3. HD content required to view HD images.
- 4. Sold separately or as an optional feature.

KEYBOARD / POINTING DEVICES

Keyboard

Full Size Textured island-style Keyboard, spill-resistant & HP Improved Anchored Key Design

Pointing Device

Touchpad with multi-touch gesture support. Taps enabled as default

SOFTWARE AND SECURITY

Preinstalled Software

Store up to 100 GB with Google Drive (2-year subscription included)⁹ HP Classroom Manager¹⁰

Manageability Features

Chrome Enterprise Upgrade^{11, 12} Chrome Education Upgrade^{11, 12}

Security Management

Google H1 Security Chip Nano Security lock slot¹¹

- 9. Google Drive offer is tied to this device and is non-transferable. If this device is returned, the extra storage will be revoked. In order to redeem this offer, you will need to be on Chrome OS™ 23 or later. Internet access is required and not included. Additional information about storage plan refunds, renewals, cancellations and expiration is available at the Google website: https://support.google.com/chromebook/answer/2703646?hl=en.
- 10. HP Classroom Manager is sold separately. Control and device locking from the teacher's desktop requires purchase of HP Classroom Manager.
- 11. Sold separately.
- 12. Requires one-time setup, subscription, Google Admin Console, and your organization's domain. Please see https://support.google.com/a/answer/60216.



POWER

Power Supply

HP Smart 45 W Type-C[™] AC power adapter

Primary Battery

HP Long Life 2-cell, 47.36 Wh Li-ion polymer¹³ HP Fast Charge Technology (90% in 90 minutes)¹⁴

Power Cord

3-wire plug - 1m

Battery life

Up to 13 hours*

- 13. Battery is internal and not replaceable by customer. Serviceable by warranty.
- 14. Recharges up to 90% within 90 minutes when the system is off or in standby mode when used with the power adapter provided with the notebook. After charging has reached 90% capacity, charging speed will return to normal. Charging time may vary +/-10% due to System tolerance.
- * Testing conducted by HP using Google Chrome OS power_LoadTest. Battery life will vary and the maximum capacity of the battery will naturally decrease with time and usage. See http://www.chromium.org/chromium-os/testing/power-testing for test details. Full charge battery life will decrease after Adaptive Battery Optimizer activation.

ENVIRONMENTAL

Environmental Data	Eco-Label Certifications & declarations	This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks: • IT ECO declaration • US ENERGY STAR® • US Federal Energy Management Program (FEMP) • EPEAT "Silver registered in the United States. See http://www.epeat.net for registration status in your country. • TCO or TCO Certified Edge • China Energy Conservation Program (CECP) • China State Environmental Protection Administration (SEPA) • Taiwan Green Mark • Korea Eco-label • Japan PC Green label*
	System Configuration	The configuration used for the Energy Consumption and Declared Noise Emissions data for the Notebook model is based on a "Typically Configured Notebook".

100VAC, 50Hz

230VAC, 50Hz

QuickSpecs

Energy Consumption
(in accordance with US

ENERGY STAR® test

method)

Options and Accessories (sold separately and availability may vary by country)

115VAC, 60Hz

Normal Operation	3.108 W	3.288	W	3.012 W
(Sort idle)				
Normal Operation	0.888 W	1.068	la.	0.912 W
(Long idle)	U.000 W	1.066	vv	0.912 W
(Long late)				
Sleep	0.360 W	0.420	W	0.360 W
Off	0.336 W	0.396	\\	0.336 W
Oli	0.550 W	0.530	VV	0.550 W
		•	·	
	Note:			
	Note.			
	Energy efficiency data list	ed is for an ENER	GY STAR® com	npliant product if offere
	within the model family. H	HP computers ma	rked with the	ENERGY STAR® Logo ar
	compliant with the applica			
	STAR® specifications for	•	-	
	STAR® compliant configura			
	configured PC featuring a		a high efficie	ncy power supply, and
	Microsoft Windows® opera	ating system.		
Heat Dissipation*	115VAC, 60Hz	230VAC, !	50Hz	100VAC, 50Hz
Heat Dissipation* Normal Operation	115VAC, 60Hz	230VAC, !	50Hz	100VAC, 50Hz
Normal Operation	115VAC, 60Hz 10.63 BTU/hr	230VAC, ! 11.24 BT		100VAC, 50Hz 10.3 BTU/hr
Normal Operation (Short idle)				
Normal Operation (Short idle) Normal Operation	10.63 BTU/hr	11.24 BT	U/hr	10.3 BTU/hr
Normal Operation (Short idle)			U/hr	
Normal Operation (Short idle)	10.63 BTU/hr	11.24 BT	U/hr J/hr	10.3 BTU/hr
Normal Operation (Short idle) Normal Operation (Long idle)	10.63 BTU/hr 3.04 BTU/hr 1.23 BTU/hr	11.24 BT 3.65 BTU 1.44 BTU	U/hr J/hr J/hr	10.3 BTU/hr 3.12 BTU/hr 1.23 BTU/hr
Normal Operation (Short idle) Normal Operation (Long idle)	10.63 BTU/hr 3.04 BTU/hr	11.24 BT	U/hr J/hr J/hr	10.3 BTU/hr 3.12 BTU/hr
Normal Operation (Short idle) Normal Operation (Long idle)	10.63 BTU/hr 3.04 BTU/hr 1.23 BTU/hr 1.15 BTU/hr	11.24 BT 3.65 BTU 1.44 BTU 1.35 BTU	U/hr J/hr J/hr	10.3 BTU/hr 3.12 BTU/hr 1.23 BTU/hr 1.15 BTU/hr
Normal Operation (Short idle) Normal Operation (Long idle)	10.63 BTU/hr 3.04 BTU/hr 1.23 BTU/hr	11.24 BT 3.65 BTU 1.44 BTU 1.35 BTU calculated based	U/hr J/hr J/hr	10.3 BTU/hr 3.12 BTU/hr 1.23 BTU/hr 1.15 BTU/hr
Normal Operation (Short idle) Normal Operation (Long idle) Sleep Off	10.63 BTU/hr 3.04 BTU/hr 1.23 BTU/hr 1.15 BTU/hr *NOTE: Heat dissipation is service level is attained fo	11.24 BT 3.65 BTU 1.44 BTU 1.35 BTU calculated based r one hour.	U/hr J/hr J/hr d on the measu	10.3 BTU/hr 3.12 BTU/hr 1.23 BTU/hr 1.15 BTU/hr ured watts, assuming th
Normal Operation (Short idle) Normal Operation (Long idle) Sleep Off Declared Noise	10.63 BTU/hr 3.04 BTU/hr 1.23 BTU/hr 1.15 BTU/hr *NOTE: Heat dissipation is service level is attained fo	11.24 BT 3.65 BTU 1.44 BTU 1.35 BTU calculated based r one hour.	U/hr J/hr J/hr d on the measu	10.3 BTU/hr 3.12 BTU/hr 1.23 BTU/hr 1.15 BTU/hr ured watts, assuming th
Normal Operation (Short idle) Normal Operation (Long idle) Sleep Off Declared Noise Emissions	10.63 BTU/hr 3.04 BTU/hr 1.23 BTU/hr 1.15 BTU/hr *NOTE: Heat dissipation is service level is attained fo	11.24 BT 3.65 BTU 1.44 BTU 1.35 BTU calculated based r one hour.	U/hr J/hr J/hr d on the measu	10.3 BTU/hr 3.12 BTU/hr 1.23 BTU/hr 1.15 BTU/hr ured watts, assuming th
Normal Operation (Short idle) Normal Operation (Long idle) Sleep Off Declared Noise Emissions (in accordance with	10.63 BTU/hr 3.04 BTU/hr 1.23 BTU/hr 1.15 BTU/hr *NOTE: Heat dissipation is service level is attained fo	11.24 BT 3.65 BTU 1.44 BTU 1.35 BTU calculated based r one hour.	U/hr J/hr J/hr d on the measu	10.3 BTU/hr 3.12 BTU/hr 1.23 BTU/hr 1.15 BTU/hr ured watts, assuming th
Normal Operation (Short idle) Normal Operation (Long idle) Sleep Off Declared Noise Emissions	10.63 BTU/hr 3.04 BTU/hr 1.23 BTU/hr 1.15 BTU/hr *NOTE: Heat dissipation is service level is attained fo	11.24 BT 3.65 BTU 1.44 BTU 1.35 BTU calculated based r one hour.	U/hr J/hr J/hr d on the measu	10.3 BTU/hr 3.12 BTU/hr 1.23 BTU/hr 1.15 BTU/hr ured watts, assuming th
Normal Operation (Short idle) Normal Operation (Long idle) Sleep Off Declared Noise Emissions (in accordance with	10.63 BTU/hr 3.04 BTU/hr 1.23 BTU/hr 1.15 BTU/hr *NOTE: Heat dissipation is service level is attained fo	11.24 BT 3.65 BTU 1.44 BTU 1.35 BTU calculated based r one hour.	U/hr J/hr J/hr d on the measu	10.3 BTU/hr 3.12 BTU/hr 1.23 BTU/hr 1.15 BTU/hr ured watts, assuming th

Fixed Disk – Random writes		2.2	22		
Optical Drive – Sequential reads		4.8	42		
Longevity and Upgrading	This product can be upgraded, possibly extending its useful life by several year Upgradeable features and/or components contained in the product may include 3 USB ports 1 PC card slot (type I/II) 1 ExpressCard/54 slot 1 IEEE 1394 Port 2 SODIMM memory slots Optional expansion base docking station 1 multi-bay II storage port Interchangeable HDD?? Spare parts are available throughout the warranty period and or for up to "5"				
Batteries	This battery(he end of production. (s) in this product comply with ed in the product do not cont greater the1ppm by weight			
	Cadmium greater than 20ppm by weight Battery description: GH02047PL Battery type: Li-Ion/Li-Ion Polymer Battery description: 6-cell high capacity Lithium-Ion battery (optional 8 cell available) Battery type:				
Additional Information	 Substances (RoHS) directive - 2011/65/EC. This HP product is designed to comply with the Waste Electrica Electronic Equipment (WEEE) Directive - 2002/96/EC. This product is in compliance with California Proposition 65 (Sta California; Safe Drinking Water and Toxic Enforcement Act of 19 This product is in compliance with the IEEE 1680 (EPEAT) stand Silver level, see http://www.epeat.net Plastics parts weighing over 25 grams used in the product are reper IS011469 and IS01043. This product contains 11.6% post-consumer recycled plastic (baccording to IEEE 1680.1-2018 standard, criterion 4.2.1.1. This product is 97.2% recycle-able when properly disposed of a life. 		al and tate of 1986). dard at the marked by wt.)		
Packaging Materials	External:	PAPER/Corrugated		226 g	
	Internal:	PLASTIC/Polyethylene lov PAPER/Molded Pulp	v density - LDPE	7 g 121 g	
	The plastic		at least xx% recycled content		

	The corrugated paper packaging materials contains at least xx% recycled content.
RoHS Compliance	HP Inc. complies fully with materials regulations. We were among the first companies to extend the restrictions in the European Union (EU) Restriction of Hazardous Substances (RoHS) Directive to our products worldwide through the HP GSE. HP has contributed to the development of related legislation in Europe, as well as China, India, and Vietnam.
	We believe the RoHS directive and similar laws play an important role in promoting industry-wide elimination of substances of concern. We have supported the inclusion of additional substances—including PVC, BFRs, and certain phthalates—in future RoHS legislation that pertains to electrical and electronics products.
	We met our voluntary objective to achieve worldwide compliance with the new EU RoHS requirements for virtually all relevant products by July 2013, and we will continue to extend the scope of the commitment to include further restricted substances as regulations continue to evolve.
	To obtain a copy of the HP RoHS Compliance Statement, see HP RoHS position statement.
Material Usage	This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at http://www.hp.com/hpinfo/globalcitizenship/environment/supplychain/gen_specifications.html):
	 Asbestos Certain Azo Colorants Certain Brominated Flame Retardants – may not be used as flame retardants in plastics Cadmium Chlorinated Hydrocarbons Chlorinated Paraffins Bis(2-Ethylhexyl) phthalate (DEHP) Benzyl butyl phthalate (BBP) Dibutyl phthalate (DBP) Diisobutyl phthalate (DIBP) Formaldehyde Halogenated Diphenyl Methanes Lead carbonates and sulfates Lead and Lead compounds Mercuric Oxide Batteries Nickel – finishes must not be used on the external surface designed to be frequently handled or carried by the user. Ozone Depleting Substances Polybrominated Biphenyls (PBBs) Polybrominated Biphenyl Ethers (PBBEs) Polybrominated Biphenyl Oxides (PBBOs) Polychlorinated Biphenyl (PCB) Polychlorinated Terphenyls (PCT)

	 Polyvinyl Chloride (PVC) – except for wires and cables, and certain retail packaging has been voluntarily removed from most applications. Radioactive Substances Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)
Packaging Usage	 HP follows these guidelines to decrease the environmental impact of product packaging: Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials. Eliminate the use of ozone-depleting substances (ODS) in packaging materials. Design packaging materials for ease of disassembly. Maximize the use of post-consumer recycled content materials in packaging materials. Use readily recyclable packaging materials such as paper and corrugated materials. Reduce size and weight of packages to improve transportation fuel efficiency. Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.
End-of-life Management and Recycling	Hewlett-Packard offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: http://www.hp.com/go/reuse-recycle or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner. The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: http://www.hp.com/go/recyclers. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.
HP, Inc. Corporate Environmental Information	For more information about HP's commitment to the environment: Global Citizenship Report http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html Eco-label certifications http://www8.hp.com/us/en/hp- information/environment/ecolabels.html ISO 14001 certificates: http://h20195.www2.hp.com/V2/GetDocument.aspx?docname=c04755 842 and http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf

Options and Accessories (sold separately and availability may vary by country)

WEIGHTS & DIMENSIONS

Product Weight

Starting at 3.19 lb¹⁵ Starting at 1.45 kg¹⁵

Product Dimensions (w x d x h)

11.61 x 8.08 x 0.82 in 29.5 x 20.53 x 2.09 cm

15. Weight will vary by configuration.

PORTS/SLOTS

Ports

2 USB 3.1 Type-C[™] Gen 1 (supports Power Delivery, DisplayPort[™], data) 2 USB 3.1 Gen 1 1 Stereo headphone/microphone combo jack

Expansion Slots

1 Micro SD multi-format digital media reader Supports SD. SDHC. SDXC

SERVICE AND SUPPORT

HP Services offers 1-year limited warranties and 90 day software limited warranty options depending on country. Batteries have a default one year limited warranty except for Long Life batteries which will have same 1-year limited warranty as the platform. Refer to http://www.hp.com/support/batterywarranty/ for additional battery information. On-site service and extended coverage is also available. HP Care Pack Services are optional extended service contracts that go beyond the standard limited warranties. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at: http://www.hp.com/go/cpc.¹⁶

16. HP Care Packs are sold separately. Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. For details, visit http://www.hp.com/go/cpc. HP services are governed by the applicable HP terms and conditions of service provided or indicated to Customer at the time of purchase. Customer may have additional statutory rights according to applicable local laws, and such rights are not in any way affected by the HP terms and conditions of service or the HP Limited Warranty provided with your HP Product.

COMPATIBILITY

HP EMR Pen 2EB40AA
HP USB-C to RJ45 Adapter V7W66AA
HP USB-C to VGA Adapter N9K76AA
HP USB-C to DisplayPort Adapter N9K78AA



Options and Accessories (sold separately and availability may vary by country)

HP USB-C Dock G5 5TW10AA

CERTIFICATION AND COMPLIANCE

ENERGY STAR® certified EPEAT® 2019 Silver¹⁷ Low halogen¹⁸ TCO 8.0 Certified

17. Based on US EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. Status varies by country. Visit http://www.epeat.net for more information.

18. External power supplies, power cords, cables and peripherals are not Low Halogen. Service parts obtained after purchase may not be Low Halogen.

SYSTEM UNIT

Planned Industry Standard

Certifications

Stand-Alone Power	USB-C 45 W adapter
-------------------	--------------------

Requirements (AC Power) Nominal Operating Voltage 15 V

Average Operating Power <4.0 W with PLT test
Integrated Graphics HD Graphics 600 12EUs

HD Graphics 600 12EUs

Max Operating Power < 45 W

Temperature Operating41° to 95° F (5° to 35° C)

Non-operating -4° to 140° F (-20° to 60° C)

Relative Humidity Operating 10% to 90%

Non-operating 5% to 95%

Shock Operating 40 G, 2 ms, half-sine

Non-operating 240 G, 2 ms, half-sine

Random Vibration Operating 1.043 grms

Non-operating 3.5 grms

Altitude (unpressurized) Operating -50 to 10,000 ft (-15 to 3,048 m)

Non-operating -50 to 40,000 ft (-15 to 12,192 m)

UL Yes

FCC Compliance Yes
ENERGY STAR® Yes¹⁹

EPEAT® 2019 Yes, Silver in U.S.²⁰

ICES Yes
Australia / Yes
NZ RCM Compliance Yes
KC Yes
BSMI Yes
CE Marking Compliance Yes
EAC Yes



Options and Accessories (sold separately and availability may vary by country)

Saudi Arabian Compliance Yes (ICCP) SABS Yes

19. Configurations of the HP ChromeBook x360 11 G3 EE that are ENERGY STAR® qualified are identified as HP ChromeBook x360 11 G3 EE ENERGY STAR on HP websites and on http://www.energystar.gov.

20. Based on US EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. EPEAT® status varies by country. Visit http://www.epeat.net for more information.



Options and Accessories (sold separately and availability may vary by country)

DISPLAYS

Note: All specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

11.6 inch diagonal HD (1366 x 768) BrightView WLED UWVA 50% NTSC 220 nits eDP 1.2 w/o PSR slim TOP+ OBZ

 Outline Dimensions (W x H x D)
 284.85 X 189.84 (mm)

 Active Area
 256.125 x 144.0 (mm)

Weight 320 g max

Diagonal Size 11.6 (inch)

Thickness 4.2 max w PCBA

InterfaceeDP 1.2Surface TreatmentBrightView

Touch Enabled yes

Contrast Ratio 800:1 (typical)

Refresh Rate 60 HZ

Brightness 220 nit typical (Panel Only)

Pixel Resolution 1366 x 768 (HD)

Format of LCD Pixel Arrangement RGB Backlight LED

Color Gamut Coverage 50% of NTSC

Color Depth 6 bit

Viewing Angle UWVA 85/85/85

Options and Accessories (sold separately and availability may vary by country)

STORAGE AND DRIVES*

32 G eMMC Drive Weight 0.2 g

Rotation speed 32 GB / 64 GB **Cache Buffer** 1.4 mm

Height 11.5 x 13 mm

Width MMC protocol

Transfer Rate Up to 250 MB/s

Seek Time Up to 70 MB/s

Logical Blocks 32 GB (31,268,536,320 Bytes) / 64 GB (62,537,072,640 Bytes)

Operating Temperature0 to 70Security FeaturesHS400

64 G eMMC Drive Weight 0.2 g

Rotation speed 32 GB / 64 GB **Cache Buffer** 1.4 mm

NAND Type/Size 11.5 x 13 mm

Height MMC protocol
Interface Up to 250 MB/s

Transfer Rate Up to 70 MB/s

Seek Time 32 GB (31,268,536,320 Bytes) / 64 GB (62,537,072,640 Bytes)

Logical Blocks 0 to 70 **Operating Temperature** HS400

For storage drives, GB = 1 billion bytes. Actual formatted capacity is less. Up to 8.1 GB is not user available

Options and Accessories (sold separately and availability may vary by country)

NETWORKING/COMMUNICATIONS

Intel® 9560 **Wireless LAN Standards** IEEE 802.11a 802.11a/b/q/n/ac (2 x 2) IEEE 802.11b Wi-Fi® and Bluetooth® 5.0 IEEE 802.11q Combo¹ non-vPro IEEE 802.11n

IEEE 802.11ac IEEE 802.11d IEEE 802.11e IEEE 802.11h IEEE 802.11i IEEE 802.11k IEEE 802.11r IEEE 802.11v

Interoperability Wi-Fi certified •802.11b/q/n **Frequency Band**

> 2.402 - 2.482 GHz •802.11a/n/ac

4.9 - 4.95 GHz (Japan) 5.15 - 5.25 GHz 5.25 - 5.35 GHz 5.47 - 5.725 GHz 5.825 - 5.850 GHz

Data Rates •802.11b: 1, 2, 5.5, 11 Mbps

> •802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps •802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps •802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz)

•802.11ac: MCS0 ~ MCS9, (1SS, and 2SS) (20MHz, 40MHz & 80MHz)

Modulation Direct Sequence Spread Spectrum

BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM

Security³ •IEEE compliant 64 / 128 bit WEP encryption for a/b/g mode only

AES-CCMP: 128 bit in hardware

•802.1x authentication

•WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES.

IEEE 802.11 compliant roaming between access points

 WPA2 certification •IEEE 802.11i WAPI

Network Architecture

Roaming

Ad-hoc (Peer to Peer)

Models Infrastructure (Access Point Required)

Output Power² • 802.11b: +18.5dBm minimum

> • 802.11g: +17.5dBm minimum • 802.11a: +18.5dBm minimum

 802.11n HT20(2.4GHz): +15.5dBm minimum 802.11n HT40(2.4GHz): +14.5dBm minimum 802.11n HT20(5GHz): +15.5dBm minimum

802.11n HT40(5GHz): +14.5dBm minimum
802.11ac VHT80(5GHz): +11.5dBm minimum

• 802.11ac VHT160(5GHz): +11.5dBm minimum

Power Consumption •Transmit mode: 2.0 W

•Receive mode: 1.6 W

Idle mode (PSP) 180 mW (WLAN Associated)
 Idle mode: 50 mW (WLAN unassociated)
 Connected Standby/Modern Standby: 10 mW

•Radio disabled: 8 mW

Power Management ACPI and PCI Express compliant power management

802.11 compliant power saving mode

Receiver Sensitivity ³ 802.11b, 1Mbps: -93.5dBm maximum

802.11b, 11Mbps: -84dBm maximum 802.11a/g, 6Mbps: -86dBm maximum 802.11a/g, 54Mbps: -72dBm maximum 802.11n, MCS07: -67dBm maximum 802.11n, MCS15: -64dBm maximum 802.11ac, MCS0: -84dBm maximum 802.11ac. MCS9: -59dBm maximum

Antenna type High efficiency antenna with spatial diversity, mounted in the display

enclosure

Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications

Form Factor PCI-Express M.2 MiniCard with CNVi Interface

Dimensions 1. Type 2230: 2.3 x 22.0 x 30.0 mm

2. Type 1216: 1.67 x 12.0 x 16.0 mm

Weight 1. Type 2230: 2.8 g

2. Type 126: 1.3 g

Operating Voltage 3.3 v +/- 5%

Temperature Operating: 14° to 158° F (–10° to 70° C)

Non-operating: -40° to 176° F (-40° to 80° C)

Humidity Operating: 10% to 90% (non-condensing)

Non-operating: 5% to 95% (non-condensing)

Altitude Operating: 0 to 10,000 ft (3,048 m)

Non-operating: 0 to 50,000 ft (15,240 m)

LED Activity LED Amber – Radio OFF

LED OFF - Radio ON

HP Integrated Module with Bluetooth 4.0/4.1/4.2/5.0 Wireless Technology

Bluetooth Specification 4.0/4.1/4.2/5.0 Compliant

Frequency Band 2402 to 2480 MHz

Number of Available Legacy: 0~79 (1 MHz/CH)

Channels BLE: 0~39 (2 MHz/CH)

Signaling Data Rate Legacy: 3 Mbps signaling data rate¹ 2.17 Mbps

BLE: 1 Mbps signaling data rate 0.2 Mbps

1. Actual throughput may vary.

Legacy: Synchronous Connection Oriented links, 3, 64 kbps, voice

channels

Legacy: Asynchronous Connection Less links 2178.1 kbps/177.1 kbps

asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)

Transmit Power The Bluetooth component shall operate as a Class II Bluetooth device with

a maximum transmit power of + 4 dBm for BR and EDR.

Power Consumption Peak (Tx): 330 mW

Peak (Rx): 230 mW

Selective Suspend: 17 mW

Bluetooth Software

Supported Link Topology Linux kernel version

Power Management Intel CNVi/BRI HW power management

Certifications FCC (47 CFR) Part 15C, Section 15.247 & 15.249

Power Management Certifications

ETS 300 328, ETS 300 826 Low Voltage Directive IEC950

UL, CSA, and CE Mark

Bluetooth Profiles
Supported

BT4.1-ESR 5/6/7 Compliance

LE Link Layer Ping LE Dual Mode

LE Link Layer

LE Low Duty Cycle Directed Advertising LE L2CAP Connection Oriented Channels

Train Nudging & Interlaced Scan

BT4.2 ESR08 Compliance

LE Secure Connection- Basic/Full LE Privacy 1.2 —Link Layer Privacy

LE Privacy 1.2 - Extended Scanner Filter Policies

LE Data Packet Length Extension

FAX Profile (FAX)

Basic Imaging Profile (BIP)2 Headset Profile (HSP) Hands Free Profile (HFP)

Advanced Audio Distribution Profile (A2DP)

- 1. Wireless access point and Internet service is required. Availability of public wireless access point is limited.
- 2. The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.
- 3. Check latest software/driver release for updates on supported security features.
- 4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).



POWER

45 W PD AC adapter Dimensions $(H \times W \times D)$ 95 mm x 43 mm x 27.5 mm

> Weight 200 a +/-10%

> > Not including power cord. Power cord varies by country

Input 100 to 240 VAC

> **Input Efficiency** Average Efficiency of 25%, 50%, 75%, 100%

load condition with 115Vac/230Vac Spec:

5V: 81.5% 9V: 86.7% 12V: 87.41% 15V: 87.8%

Input frequency range 47 ~ 63Hz

Input AC current Max. 1.4 A at 90 Vac

Output **Output power** 5V/15W

9V/27W 12V/36W 15V/45W

DC output 5V/9V/12V/15V Hold-up time 5ms at 115 Vac input **Output current limit** <5.0A by each outputs

USB Type-C™ **Connector**

Environmental Design

Operating temperature

32°F to 95°F (0°C to 35°C)

temperature

Non-operating (storage) -4°F to 185°F (-20°C to 85°C)

Altitude 0 to 16,400 ft (0 to 5000m)

Humidity 20% to 95% 10% to 95% **Storage Humidity**

EMI and Safety CE Mark - full compliance with LVD and EMC directives

Certifications Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class

B, CISPR22 Class B, CCC, NOM-1 NYCE.

MTBF - over 200,000 hours at 25°C ambient condition.

HP 2-cell Long Life Li-Ion Dimensions (H x W x L)

(47 Whr)

5.2 x 240.8 x 76.4 mm (0.204 x 9.48 x 3 inch)

Weight 0.19 kg (0.418 lb)

Cells/Type 2cell Lithium-Ion Polymer cell / 4473A9

7.7 V Voltage **Amp-hour capacity** 6.15 Ah **Watt-hour capacity** 47.3 Wh

Operating (Charging) 32° to 113° F (0° to 45° C) Operating (Discharging) 14° to 122° F (-10° to 60° C)

Warrantv 1-vear **Optional Travel Battery** No

Available

Category	Description	Part Number
Cases	HP Business Slim Top Load	2SC65AA
	HP Essential Top Load Case (up to 15.6")	H2W17AA
	HP Essential Backpack (up to 15.6")	H1D24AA
	HP Reversible Neoprene Sleeve	7ZE81AA
Docking	HP USB-C Travel Dock G2	7PJ38AA
	HP E24d G4 Advanced Docking monitor	6PA50AA
	HP E27d G4 Advanced Docking monitor	6PA56AA
Input/output	HP 3-Button Laser Mouse	H4B81AA
	HP Ultra Mobile Wireless Mouse	H6F25AA
	HP USB Optical Travel mouse	G1K28AA
	HP Essential USB Mouse	2TK37AA
	HP Slim USB KB & Mouse	T6T83AA
	HP USB-C to HDMI 2.0 Adapter	1WC36AA
	HP USB-C to DisplayPort Adapter	N9K78AA
	HP USB-C to USB 3.0 Adapter	N2Z63AAA
	HP USB-C to RJ45 Adapter	V7W66AA
	HP USB-C to VGA Adapter	N9K76AA
	HP USB-C Travel Hub G2	7PJ38AA
	Stereo 3.5mm Headset	T1A66AA
	HP EMR Pen	2EB40AA
Power	HP 45W Type -C Straight Type	1MZ01AA
	HP USB-C Notebook Power Bank	2NA10AA
Storage	HP External USB Optical Drive	F2B56AA
Security	HP Nano Keyed Cable Lock	1AJ39AA
	HP Sure Key Cable lock	6UW42AA



Summary of Changes

Date of change:	Version History:		Description of change:
January 22, 2020	V1 to V2	Added	Environmental Tab
February 6, 2020	V2 to V3	Updated	Compatibility section (HP Pen)
February 21, 2020	V3 to V4	Updated	Docking Section
March 17, 2020	V4 to V5	Updated	Accessories Section
April 21, 2020	V5 to V6	Updated	At a glance Section

Copyright © 2020 HP Development Company, L.P. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Intel®, Core®, and Intel vPro™ are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries. DisplayPort™ and the DisplayPort™ logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries. USB Type-C™ and USB-C™ are trademarks of USB Implementers Forum. SD, SDHC and SDXC are registered trademarks of SD-3C in the United States, other countries or both. ENERGY STAR is a registered trademark of the U.S. Environmental Protection Agency. © 2019 Google LLC All rights reserved. Google and the Google Logo are registered trademarks of Google LLC.

