

MOVEMIC 88+ RECEIVER KIT

WIRELESS STEREO MICROPHONE WITH RECEIVER

OVERVIEW

The MoveMic 88+ has been designed to give creators one of the most versatile wireless microphones that can be configured to capture professional audio and video using the companion MOTIV Video app on iOS and Android devices. From field recording, to creating a film, or even capturing an interview, the MoveMic 88+ has customizable DSP allowing it to be configured to perform in almost any situation. Modeled from our renowned MV88 and MV88+ microphones; the MoveMic 88+ can connect directly to your mobile phone using the Shure MOTIV Video or MOTIV Audio app(s) without a receiver. Increase your connectivity options and record to cameras, computers and third-party apps using the included MoveMic Receiver.

FEATURES

- 4 selectable polar patterns for ultimate versatility (adjustable stereo, mono cardioid, mono bi-directional, raw mid-side).
- 5 Preset modes (speech, singing, flat, acoustic, loud).
- Connect to cameras, computers or third party mobile apps using the included MoveMic Receiver.
- Connect direct to your iOS or Android mobile device without a receiver using Shure MOTIV Video or Audio app(s).
- Configure and customize DSP settings such as polar pattern, gain, compressor, presets, EQ, monitor mix, L/R channel swap and newly-introduced noise reduction.
- 8 hour battery life on a full charge.
- Built-in headphone monitoring with adjustable monitor output.
- Instant re-connection to last device when powered on (phone or MoveMic receiver).

SPECIFICATIONS

Frequency Response (-10dB)	40Hz - 18kHz
Dynamic Range	96.5 dB
Equivalent Input Noise (Digital USB Out)	26dB
Max Sound Pressure Level (SPL)	122.4dB SPL
Sensitivity (Digital USB Out)	-34.5dBFS/Pa
Bit Rate Direct To Phone	16Bit
Bit Depth to MoveMic Receiver	24Bit
Sampling Rate	44.1kHz or 48kHz
Gain Adjustment Range	0 - 40dB
Minimum Load Impedance - HP	16Ω
Maximum Headphone Output Level	26.4mW @1% THD
Minimum Load Impedance - Camera Out	2kΩ
Maximum Camera Output Level (Mic Setting)	-26dBV
Maximum Camera Output Level (Line Setting)	-8.3dBV
Latency to 3.5mm (without NR)	17.6ms
Latency to 3.5mm (with NR)	19.6ms
Latency to USB	Device Dependent
Range	Up to 100ft (30m) line of sight

* Direct to phone is only recommended for use with the MOTIV Video and Audio App(s) only. Shure recommends using the MoveMic Receiver for additional compatibility with third party apps on mobile.

PHYSICAL SPECIFICATIONS (MICROPHONES)

Overall Dimensions (w/o windscreens)	28mm x 28mm x 89mm 1.1" x 1.1" x 3.51" (L x W x H)
Weight (w/o windscreens)	99g 3.5oz
Housing	Zinc Die Casting, black chrome plated
Antenna	Machined steel frame plus stainless-steel mesh, satin chrome plated

PHYSICAL SPECIFICATIONS (RECEIVER)

Overall Dimensions (with cold shoe mount fully extended)	65mm x 67mm x 19mm [2.55" x 2.64" x 0.75"]
Weight (w/o windscreens)	81 g [2.86 oz]
Housing	Black PC/ABS Thermoplastic
Antenna	Sheet metal (tin-plated steel)



MoveMic 88+ Receiver Kit
Wireless Stereo Microphone With Receiver