

PSS-SX01

Weather-Resistant Side-by-Side Sound System



PRODUCT OVERVIEW

This complete sound system combines the premium sound you've come to expect from Alpine as well as a unique design that will complement the look of your Side-by-Side. As an easy add-on for any existing Side-by-Side with 1.5"-2" rails, the PSS-SX01 includes everything you need for an exciting music experience, including two enclosed 6.5-inch speakers, a grille-mounted, 1-inch teteron dome tweeter, and one 4-channel amplifier all weather-resistant against the elements.

*Additional speaker and power wire may be required for installation

PRODUCT FEATURES

Music on Your Adventures – Stream music directly from your smartphone without a radio or head unit source with the included Bluetooth® adaptor.

Flexible Installation – With universal folding-style clamps that fit 1.5"-2" rails, the PSS-SX01 can be installed in just about any Side-by-Side or UTV.

Built for the Elements – The weather-resistant speakers and amplifier can withstand all of the elements for an uninterrupted music experience.



GO BEYOND UTILITY

PSS-SX01

Weather-Resistant Side-by-Side Sound System



PRODUCT DETAILS

WHAT'S INCLUDED:

- 6.5" 2-Way Mid Bass Drivers
- KTA-30FW 4-Channel Weather-Resistant Tough Power Pack Amplifier
- KCX-BT01 Weather-Resistant Bluetooth® Adaptor
- ASA 978 B+ Fiberglass Speaker Pod with Folding-Style Clamp

SPEAKERS:

- Enclosed 6.5" 2-Way Speakers
- 1" Teteron Dome Tweeter
- Rated IP55 Weather-Resistant
- Steel Frame

AMPLIFIER:

- Alpine's Class D Amplifier with Dynamic Peak Power (DPP)
- 4-Channel Power Pack Amplifier
- Rated IP66 Weather-Resistant

BLUETOOTH ADAPTER:

- 12V Weather-Resistant Bluetooth® Adaptor
- Complete Wireless Connections Bluetooth® 4.0
- Built-In Line Driver for 3x Voltage Output
- Music Signal Remote Trigger Output

SPEAKER PODS:

- ASA 978 B+ Fiberglass
- Pro-Style Folding Style Clamp that will fit 1.5"-2" Rails.
- Rotating Coated Aluminum Base
- 90-Degree Plug with 20AWG Pigtail
- Rated IP65 Weather-Resistant

SPEAKER SPECS

- **Material:** Santoprene
- **Frequency Response:** 50Hz - 22kHz
- **Power Handling:** 90W RMS / 225W Peak
- **Nominal Impedance:** 4Ω
- **Voice Coil Diameter:** 25 mm



AMPLIFIER SPECS

- CTA-2006-B Compliant
- 75W RMS x 4 (2Ω/4Ω, 14.4V, 1% THD+N)
- 150W DPP x 4 (2Ω/4Ω, 14.4V, 1% THD+N)
- Amplifier 2ch/4ch input (selectable)
- 85dB S/N (ref. 1W into 4Ω)
- >0.01% THD (ref. 1W into 4Ω)
- 20-20kHz Frequency response (+/- 1dB)
- Speaker/RCA inputs (Selectable, High range=0.5-10V, Low range=0.2-4V)
- Sound Control: Crossovers: Off/Hp/Lp, Fc=50-400Hz @ -12dB/Oct. (variable) Input gain settings (variable); 2ch/4ch input (selectable)

