



LED DISPLAY

XG3220

Key Features

4K & 32" | High Caliber Detail | HDR10
Enhancement | Bold Colour for Gaming |
Tear-free Visuals



Product Description

The ViewSonic® XG3220 enters the arena with 32 inches of 4K Ultra HD resolution and HDR content support. XG3220 comes equipped with wide gamut colour coverage and delivers visual enhancements to HDR10 games whether on PC, PS4 Pro, or Xbox One X. Utilising the monitor's AMD FreeSync keeps your gaming experience seamless and tear free. 87% NTSC colour coverage floods in-game visuals with realistic colour and vibrance. Highly customisable settings and gaming presets for FPS, MOBA, and more give you maximum flexibility for fine-tuning your in-game experience.

Visit Us ■ www.viewsonic.com

LCD PANEL

Monitor Size:	32" (31.5" / 80.01cm viewable)
Panel Technology:	VA type TFT LCD
Resolution:	3840 x 2160
Display Area:	698.4mm (H) x 392.85mm (V)
Aspect Ratio:	16:9
Brightness:	300 cd/m2 (Typ)
Contrast Ratio:	3000:1 (Typ)
Dynamic Contrast Ratio:	120,000,000:1
Viewing Angle:	178° / 178° (Typ)
Refresh Rate:	60Hz
Response Time:	5ms (GtG)
Colours:	1.07 Billion colours (8-bit+Hi-FRC)
Colour Gamut:	sRGB: 136.9% size / 99% coverage NTSC: 95% size / 86.93% coverage Adobe RGB: 101.7% size / 89.01% coverage
Pixel Size:	0.181mm (H) x 0.181mm (V)

INPUT SIGNAL

Frequency:	HDMI 2.0: Fh = 15 ~ 204KHz ; Fv = 40 ~ 60Hz DisplayPort 1.2: Fh = 135 ~ 135KHz ; Fv = 40 ~ 60Hz
Video:	HDMI 2.0: Timing Max support 3840 x 2160 @60Hz DisplayPort 1.2: Timing Max support 3840 x 2160 @240Hz

COMPATIBILITY

PC:	Windows 10 certified
Mac®:	Power Mac tested

CONNECTOR

Input:	HDMI 2.0 x 2 DisplayPort 1.2 x 1
Output:	Earphone out x 1 (3.5mm plug)

AUDIO

Speaker:	Amplifier: 6W Speaker: 5W x 2
----------	----------------------------------

USB

Upstream:	Type B x 1
Downstream:	Type A x 4

POWER

Power:	5.5 x 2.5 x 12 DC connector
Voltage:	AC 100-240V (Universal); 50/60Hz
Consumption:	50W (Typ)
Optimize:	42W
Conserve:	33W

ERGONOMICS

Tilt:	-5 ~ 15 degrees
Swivel:	-45 ~ 45 degrees
Pivot:	0 ~ 90 degrees
Height Adjustment:	100 mm

SPECIAL FEATURES

Eye Care:	Blue light filter & Flicker Free
-----------	----------------------------------

WALL MOUNT

VESA®:	100mm x 100mm
--------	---------------

OPERATING CONDITIONS

Temperature (° F / ° C):	32°F to 104°F (0°C to 40°C)
Humidity:	20% to 90% (no condensation)

DIMENSIONS (W X H X D) (MM)

Physical with stand (mm):	727.48mm (W) x 458.55mm (H) x 260.53mm (D)
Physical without stand (mm):	727.48mm (W) x 427.43mm (H) x 76.12mm (D)
Packaging (mm):	795mm (W) x 508mm (H) x 230mm (D)

WEIGHT

Net with stand:	8.26kg
Net without stand:	4.98kg
Gross:	11.4kg

REGULATIONS

CE, REACH, WEEE, EAC, UkrSEPRO, KC, e-Standby

PACKAGE CONTENTS

LCD Display AC/DC Adapter Power Cable DisplayPort Cable USB3.0 Cable Quick Start Guide
