


## Key Features

Bright Images in any Environment | Long Lamp Life | SuperColor:  
Amazing Color Accuracy



## Product Description


The ViewSonic® PG701WU WUXGA projector features 3,500 lumens, 1920x1200 native resolution, an intuitive, user-friendly design, and a sleek white chassis. Exclusive SuperColor™ technology offers a wide color gamut for beautiful image production in nearly any environment. With vertical keystone correction, and extensive connectivity options, the PG701WU provides flexible and quick set-up. What's more, an energy-saving SuperEco™ feature reduces power consumption and extends the lamp life by up to 20,000 hours. The PG701WU is the ideal projector for both high-definition presentations and vibrant multimedia entertainment.



1920 x 1200  
**RESOLUTION**



3,500 ANSI  
**LUMENS**



1.5-1.65  
**THROW RATIO**

### Contact Sales

- call: 888.881.8781
- email: [salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)
- visit: [viewsonic.com](http://viewsonic.com)

|  |  |  |                       |
|--|--|--|-----------------------|
| <b>Display:</b>  |  | <b>Weight (metric):</b>  |                       |
| Type:  | DLP Lamp   | Net (kg):  | 2.6                   |
| Resolution Type:   | WUXGA (1920x1200)  | Gross (kg):  | 3.7                   |
| Resolution:  | 1920 x 1200  | <b>Dimensions (imperial) (WxHxD):</b>  |                       |
| Brightness (Lumens):   | 3,500 ANSI   | Packaging (in.):   | 16.3 x 6.6 x 11.7     |
| Display Size (in.):  | 30 - 300 in. / 0.76 - 7.62 m   | Physical (in.):  | 12.3 x 8.7 x 4.3      |
| Throw Distance:  | 3.3 – 36.0 ft / 1.0 m – 11.0 m   | <b>Dimensions (metric) (WxHxD):</b>  |                       |
| Throw Ratio:   | 1.5-1.65   | Packaging (mm):  | 415.0 x 168.0 x 297.0 |
| Keystone:  | Vertical (+/- 40°)   | Physical (mm):   | 312.0 x 222.0 x 108.0 |
| Lens:  | 1.1x optical zoom  | <b>General:</b>  |                       |
| Light Source (watt):   | 203  | Regulations: FCC, cTUVus, ROHS   |                       |
| Light Source Life, Normal (hours):   | 5000   | PACKAGE CONTENTS: PG701WU projector, Power Cable, VGA Cable, Remote Control, Quick Start Guide   |                       |
| Light Source Life, Dynamic Eco-Mode (hours):   | 20000  | Warranty: Three-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange* service. (One year Express Exchange Service requires product registration). |                       |
| Color Depth:   | 1.07B Color (R/G/B 10bit)  | Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.   |                       |
| Aspect Ratio:  | 16:10  | UPC: 766907001747  |                       |
| <b>Video Signal:</b>   |  | <b>Accessories:</b>  |                       |
| Frequency Horizontal:  | 15K~102KHz   | HB10B, IFP2710, PGD-350, PJ-SCW-1001W, PJ-WMK-006, PJ-WMK-007, RLC-119, VC10, VCB10  |                       |
| Frequency Vertical:  | 23~120Hz   |  |                       |
| <b>Compatibility:</b>  |  |  |                       |
| PC Resolution (max):   | 1920 x 1200  |  |                       |
| PC Resolution (min):   | 640 x 480  |  |                       |
| Mac® Resolution (max):   | 1920 x 1200  |  |                       |
| Mac® Resolution (min):   | 640 x 480  |  |                       |
| <b>Connector:</b>  |  |  |                       |
| USB 2.0 Type A(1), 3.5mm Audio Out(1), 3.5mm Audio In(1), Control (RS232)(1), HDMI 1.4(1), HDMI 1.4 (with HDCP 1.4)(1) |  |  |                       |
| <b>Audio:</b>  |  |  |                       |
| Internal Speakers:   | 2W (x1)  |  |                       |
| <b>Power:</b>  |  |  |                       |
| Consumption (typical):   | 300W   |  |                       |
| Stand-by:  | <0.5W  |  |                       |
| <b>Controls:</b>   |  |  |                       |
| Physical Controls:   | Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source                  |  |                       |
| On Screen Display:   | Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality) |  |                       |
| <b>Operating Conditions:</b>   |  |  |                       |
| Temperature:   | 32-104° F (0 - 40° C)  |  |                       |
| Humidity (non-condensing):   | 0-90%  |  |                       |
| <b>Additional Hardware:</b>  |  |  |                       |
| Kensington Lock Slot:  | 1  |  |                       |
| <b>Weight (imperial):</b>  |  |  |                       |
| Net (lbs):   | 5.7  |  |                       |
| Gross (lbs):   | 8.2  |  |                       |