

2GIG-SMKT3-345

Wireless Smoke/Heat Alarm

2GIG Technologies is pleased to announce the new Wireless Smoke/Heat Alarm. The SMKT3, 2GIG's next generation in fire and freeze protection, offers the same reliable functionality and features as the SMKT2 but with the added benefit of freeze detection. It is more customizable than previous models by allowing separation of the smoke, heat, and freeze features enabling the alarm to detect one, two, or all three.

PRODUCT NAME

Wireless Smoke/Heat Alarm
UPC: 817082010199

PART NUMBER

SKU: 2GIG-SMKT3-345

FEATURES

- Smoke, heat, and freeze detection
- Ability to separate the three detection features
- Self-contained sounder
- Supervised transmitter and status LED
- Easy installation and programming



Please note that programming the SMKT3 is different than the SMKT2. Detailed programming instructions are included in each box and can also be found on the 2GIG dealer website.

PRICING

2GIG's price remains unchanged. The SMKT3 price is the same as SMKT2. Contact your 2GIG Distributor or Sales Representative for pricing details.

PRODUCT AVAILABILITY, ORDERING AND SHIPPING INFORMATION

Orders for the SMKT2 (2GIG-SMKT2-345) are expected to begin transitioning to SMKT3s (2GIG-SMKT3-345) this week. Please note that SMKT3 has a new SKU to reflect the additional features. Any order for the 2GIG-SMKT2-345 will automatically be filled with 2GIG-SMKT3-345 once shipping commences.

SYSTEM REQUIREMENTS

The Wireless Smoke/Heat Alarm (SMKT3) works with any Go!Control security panel. If using firmware prior to 1.8, installers can select SMKT2 as the equipment code for the new SMKT3 and the system will function properly. If running firmware 1.8 or newer, the SMKT3 equipment code is available in system programming.

WARRANTY

The SMKT3 ships with a standard two (2) year limited warranty. Please refer to the Installation Guide for specific warranty details.

FREQUENTLY ASKED QUESTIONS

Q. How do I program the SMKT3?

A. The SMKT3 is programmed differently than the SMKT2. For step-by-step instructions on how to program the SMKT3, please refer to the Guides and Manuals portion of the dealer website: [Wireless Smoke, Heat Alarm Install Instructions](#)

Q. On what loop should I set the SMKT3?

A. The SMKT3 was designed to separate the smoke, heat, and freeze features on three loops. This allows you to configure the SMKT3 to be any combination of a smoke, heat, and freeze detector.

Loop 1 – Smoke

Loop 2 – Heat

Loop 3 – Freeze

If you want the device to detect all three, configure the SMKT3 on three separate loops. For additional details on how to program the SMKT3, please refer to the Guides and Manuals portion of the dealer website: [Wireless Smoke, Heat Alarm Install Instructions](#)

Q. Why is the SMKT3 reporting a loss of supervision soon after installation?

A. This is most likely caused by a failure to properly test the SMKT3 with the panel after installation. If not properly tested, the panel will report a loss of supervision after four (4) hours. To ensure this does not happen or to fix it if it already has, properly test the SMKT3 as outlined in the [Wireless Smoke, Heat Alarm Install Instructions](#) under the heading "Testing."

Q. What are the differences between the SMKT2 and the SMKT3?

A. The primary differences are that the SMKT3 incorporates freeze detection and that each feature (heat, smoke, and freeze) can be separated if desired. Additionally the SMKT3 incorporates a new design that gives it a more uniform appearance with the rest of the 2GIG product family.

Q. How large of an area can one SMKT3 cover?

A. The 2GIG SMKT3 has a spacing rating of 70 ft.