

说明书

版式设计要求:

1. 字体: 标题为Myriad Pro SemiBold, 内容为 Myriad Pro light;
2. 上下页边距为9mm, 左右边距为8mm;;
3. 标注说明书长宽尺寸, 单位mm.

Installation instructions

Refrigerator water filter

A replacement for the following water filters:

Whirlpool®/EveryDrop®/Maytag®/Amana®/KitchenAid® filters

UKF8001, Filter 4, EDR4RXD1, EDR4XD1B, EDR4RXD2, 4396395, UKF8001-750, UKF8001AXX, UKF8001AXX-200, UKF8001AXX-750, UKF8001AXXP, UKF8001AXXT, UKF8001P, UKF8001T, UKF9001, 67002269, 67002671, 67003523, 67003591, 67003640, 67003727, 67006464, 67006467, 67006469, 67006470, 67006474, 67006475, 67006476, 67006477, 67006633, 67006634, 67006637, WF50, OWF50, WF51, OWF51, OWF50-NI300, WF50-KNI300, WF50-NI500, OWF50-WI500

Kenmore® filters

46-9005, 469005, 9005, 9005P, 46-9006, 469006, 9006, 9006P, 46-9992, 469992, 9992, 9992P, 469005750, 469005-750, 46-9005-750, 469006750, 469006-750, 46-9006-750, 04609005000, 04609006000

Puriclean II® filters

67003526, 67003527, 67003528



Tested and Certified by NSF International against NSF/ANSI Standard 42 in model EFF-6007S for the reduction of the claims specified on the Performance Data Sheet, and to NSF/ANSI 372 ($\leq 0.25\%$ lead).

Installation instructions

Before installation:

- Shut off the cold-water supply to the refrigerator before installation. Turn on the refrigerator water dispenser to release water pressure, letting water drain from the pipe completely.
- It is normal for black carbon fines (particles) to appear on the outside of your filter. This happens when the filter is jarred in shipping. It is safe to simply wipe it off.
- The filter connectors are larger to prevent leaks. You might have to twist the filter hard to make sure the connection is secure.


1. Locate the filter cartridge holder in the back upper right hand corner of the refrigerator. To open the cartridge cover, push in where indicated and the cover will drop down.
2. Remove old filter by slowly rotating it to the left. A small amount of water may drip down.

6007S | V040

3. Position the cartridge inside the cartridge holder and slowly rotate the cartridge to the right until it stops. When the cartridge is properly installed, you will feel it "click" as it locks into place. Do not over tighten.

4. Close the cartridge cover.

5. Run water from the dispenser for 5 minutes at 0.5 gpm (about 2.5 gallons) to clear the system and prevent spluttering.



Resetting your filter indicator:

Note: These are the most common filter reset instructions. If the instructions don't work for your refrigerator brand, see the documentation that came with your refrigerator.

Refrigerator brand	Instructions
Maytag® systems	Press and hold the lock and light buttons at the same time until the filter indicator flashes (about 4 seconds). On newer models, press and hold the lock and water buttons at the same time until the filter Indicator flashes (about 4 seconds).
Kenmore® systems	The filter reset for Kenmore refrigerators varies by model. See the documentation that came with your refrigerator.

Storage and maintenance:

- Replace your filter every 6 months or 300 gallons to prevent bacteria and fungus growth in your filter, supply lines, and storage tank.
- Keep your unused filters in a cool, dark, and dry place until you need them.
- If you do not use your water dispenser for more than four days, run two gallons of water before using it to prevent bad tasting water.

140mm

210mm

Frequently asked questions:

Q: Why is it difficult to twist the new filter into the filter housing?

A: The connector may expand because of water pressure. Therefore, it is recommended you push the new filter in with a little bit of force, but not too hard. Then turn it clockwise.

Q: Do I need to flush the filter after installation?

A: After installation, it is highly recommended you run water for a few minutes before using. Water filters are made from advanced coconut carbon block, so there are some carbon fines in the filter. Flushing removes the carbon fines to produce clean water.

Q: Must the filter be changed every 6 months?

A: Yes, you must replace the filter every six months or sooner if water flow is reduced or if there is heavy sediment / rust present. Over-used filters will degrade the filtration performance.

⚠ Warning:

To reduce the risk of property damage due to water leakage, this filter MUST be installed in accordance with the manufacturer's specifications and instructions. This filter unit must be replaced every 300 gallons or 6 months. Failure to follow instructions and operating specifications will void your warranty. Further, manufacturer assumes no responsibility or liability for damages arising out of misuse of the product.

Maytag® is a registered trademark of Maytag Corp., Delaware.

Maytag® is used for reference purposes only.

KitchenAid® is a registered trademark of Whirlpool Properties, INC..

KitchenAid® is used for reference purposes only.

Kenmore® is a registered trademark of KCD IP, LLC.

Kenmore® is used for reference purposes only.

*The service life mentioned above is subject to chlorine reduction. Actual result varies according to the local water quality.

Manufacturer Technical Support

Tel: 1-888-352-3558 (U.S.)

E-mail: service@water-filter.com

Performance data sheet

System Model No.: EFF-6007S

Operating specifications:

Operating Temperature: 33 - 100°F / 0.6 - 38°C

Working Pressure: 20 - 100 psi / 140 - 689 kPa

Rated Capacity: 300 gallons / 1,137 litres

Flow Rate: 0.5 gpm / 1.9 lpm

Substance reduction:

The system has been tested and certified by the NSF International according to NSF/ANSI Standard 42 for the reduction of the substances listed below. The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for the water leaving the system, as specified by NSF/ANSI Standard 42. While testing was performed under standard laboratory conditions, actual performance may vary.

Substance	Inf. Average	NSF Specified Challenge Concentration	Ave. % Reduction	Average Product Water Concentration	Max Permissible Product Water Concentration	NSF Reduction Requirements	NSF Test Report
Chlorine Taste and Odor	2.1 mg/L	2.0 mg/L ± 10%	97.0%	0.063 mg/L	N/A	≥50%	J-00295502

⚠

Do not use with water that is microbiologically unsafe or of unknown water quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used with disinfected water that may contain filterable cysts.



Made in China V040
Qingdao Ecopure Filter Co., Ltd.



图像颜色请依据数码稿印刷

⚠ 请不要擅自变更来稿件, 如须修改, 请联系伊可普做有关决定

印刷品技术要求 IMPORTANT PRINTING CAUTION

1. 印刷要求 覆光膜 覆亚膜 UV油 吸塑油 过油 丝印
2. 材质要求 80g双胶纸, 双面印刷
3. 颜色要求 单黑印刷
4. 版面要求 印刷品文字线条印迹清晰、无重影; 印刷品套印准确无偏色、溢墨、指痕等; 印刷品上光层均匀、光亮、牢固无粘连; 覆膜表面平整、无褶皱、光泽度好; 纸张材质正确, 切边整齐、压线深浅适中、洁净、无斑点和条痕。



青岛伊可普电器有限公司包材设计图纸

品牌 BRAND NAME		工厂型号 ITEM NO.	EFF-6007
物料编码 INNER CODE	03070006007542	版本号 VERSION	V040
包材文件名称 FILE NAME	03070006007542 EFF-6007S-42-说明书-V040		
规格 MEASURE	210*140mm	页数 PAGE	4P
设计负责人 DWG BY	张鑫龙	审核日期 VERIFY DATE	
变更日期 REVISIONS	2021.11.20		
变更描述 DESCRIPTION	1. 增加客服24H7D365信息		