



AMB362

Magnetic GPS Tracker



GPS+AGPS+LBS positioning

Accurate location on a map or satellite view



Real-time notifications

Receive movement and driver behavior alerts



5000mAh battery

High capacity Li-ion battery ensuring sufficient power supply



Geo-fence notifications

Create single or multiple geo-fencing



Voice monitor

Listen-in mode available for pre-registered numbers



IP65 dust and water proof

Water-resistant to ensure stable operation in tough environment



Powerful magnet


Device does not require installation



Live Tracking

Real-time tracking via app or web portal


Application



Container



Vehicle tracking



Valuables

GSM Specification

GSM frequency	850/900/1800/1900 MHz
GPRS	Class 12, TCP/IP
Memory	32+32Mb
Phase error	RMSPE<5,PPE<20
Max output	GSM850/GSM900:33±3dBm GSM1800/GSM1900:30±3dBm
Max frequency error	±0.1ppm

GPS Specification

GPS chipset	MTK high sensitivity chip
Frequency	L1,1575.42MHz C/A code
GPS channel	66
Location accuracy	<10 meters
Tracking sensitivity	-165dBm
Acquisition sensitivity	-148dBm
TTFF (open sky)	Avg. hot start ≤1sec Avg. cold start ≤35sec

Function & Package

Voice monitor range	≤5 meters	
Dust and Water Proof	IP65	
Button	1xPower On/Off	
Working voltage/current	3.7VDC/60mA	
Charger voltage/current	5VDC/1A	
Operating temperature	-20 ~ 70	
Battery	2500mAh/3.7V	5000mAh/3.7V
Charging period	4 hours	8 hours
Standby time (Deep sleep mode)	20 days	40 days
Working time (GPS working mode)	30 hours	58 hours
Dimension	91.5(L)*57.0(W)*24(H)mm	91.5(L)*57.0(W)*37.5(H)mm
Weight	100g	202g

Contact

Amber Connect Limited

Add: Unit 1-3, 6 Haining Road Kingston 5, Jamaica

Tel: +1 (876) 620-5255, +1 (876) 632-6737, +1 (305) 420-6361

Web: www.amberconnect.com

Email: info@amberconnect.com