

sTP4

NEW

TOUCH PANEL CONTROL

Enhanced Multi-Room Convenience.

The SpeakerCraft sTP4 wall mount touch panel brings added convenience and flexibility to your SpeakerCraft MRA-664 system. Its compact, stylish form factor makes it the perfect addition to expand zone controls in any SpeakerCraft system.

The sTP4 wakes with the approach of a hand and presents an intuitive user interface – just like the larger sTP7 – for quick access to music presets, volume and common controls.

The 4.7" sTP4 screen is bright and vibrant. It sits behind edge to edge ultra-sensitive capacitive sense touchscreen of edge-to-edge glass. And like the sTP7, the sTP4 is designer-friendly. Not much larger than a one gang wall plate, it can mount in either portrait or landscape direction for maximum flexibility, such as portrait mounting to match nearby light switches or landscape when mounted a little higher on the wall.

The sTP4 is designed for mounting with a standard US or UK 1 gang back box. A single security screw allows it to be placed in high traffic locations where theft may be a consideration. It makes use of ultra-efficient Power over Ethernet with its single wire connection. The sTP4 is available in white or black trim and is compatible with all systems driven by a SpeakerCraft MRA-664 controller.

FEATURES:

- 4.7" diagonal viewable area LCD touchscreen interface
- Contemporary, sleek industrial design
- Edge to edge glass
- Capacitive sense touchscreen
- Proximity sensor to wake from sleep without touching as hand approaches
- Portrait or landscape mounting
- Mounts into drywall, brick, stone, plaster, and wood, using a standard 1g US or UK junction box
- Supports TCP/IP communication
- Plug and play operation with the MRA-664
- Locally powered (optional)
- Available in white and black bezel



SpeakerCraft®

SPECIFICATIONS:

Dimensions	Overall 3.2" wide x 5.2" height, mounting depth 0.8"
Screen size	4.7-inch diagonal, 16:9 widescreen
Resolution	540 x 960
Microphone	Single Digital, Near Field Pickup
Speaker	1W integrated
Network	10/100/1000 Ethernet
USB	Micro AB

POWER REQUIREMENTS:

Direct	9-12V = 2A maximum
PoE	IEEE 802.3at, (power over Ethernet) 13W maximum draw (@48V = 270 mA max)
Included in box	(1) sTP4 touchpanel (1) Mounting bracket (3) Mounting screws



More Info:
www.SpeakerCraft.com

2 Years
Part & Labor
WARRANTY