

TECH SPECS

LCD PANEL

Panel Size
14-inch

Screen Dimensions (W x H, mm)
309.31 x 173.99 mm

Panel Type
In-Plane Switching

Backlight
WLED

Aspect Ratio
16:9

Resolution
1920 x 1080

Pixel Pitch (H x V, mm)
0.1611 x 0.1611 mm

Dot/Pixel Per Inch (DPI/PPI)
157

Viewing angle (H x V @ CR 10:1)
178° / 178°

Response Time (typical)
6ms with OD

Refresh Rate
60 Hz

Brightness (typical)
300 cd/m²

Contrast Ratio (typical)
700:1

Dynamic Contrast Ratio (typical)
3M:1

Colour Gamut NTSC (CIE 1931)
72%

Color Support (typical)
16.7 Million

Color Depth
8bit (6bit + FRC)

Anti-Glare
Yes

CONNECTIVITY

Video Input Signals
2 x USB 3.1 Type-C (DP1.2 Alt Mode)

POWER

Power Consumption (Typ./Max)
6 W / 7.5 W (Without USB Type-C output)

ENERGY STAR® Power Consumption (P_{on})
4.88 W

ENERGY STAR® Power Consumption (E_{TEC})
15.53 kWh

Power Consumption Sleep/Off Mode
< 0.3 W

Power Consumption Switch-Off Mode
< 0.3 W

USB Type-C/Power Delivery
Up to 65 W

Power Supply
External (no adapter bundle)

Voltage Required
DC 5 V to 20 V

MECHANICAL

Tilt Angle (front/back)
-5° / 90°

Mounting Support
Yes (100 mm)

Kensington™ Lock Slot
Yes

Cable Management
Yes

Bezel Color
Raven Black

Bezel Width (Side)
5.48mm

Bezel Width (top / bottom)
5.47 mm / 23.87 mm

DIMENSIONS

Size Packed (D x H x W) (mm / inch)
276 x 61 x 402 mm /
10.87 x 2.40 x 15.83 inches

Size Unpacked w/stand (D x H x W) (mm / inch) (Lowest position)
96.54 x 209.03 x 323.37 mm /
3.8 x 8.23 x 12.73 inches

Size Unpacked w/stand (D x H x W) (mm / inch) (Highest position)
96.54 x 220.03 x 323.37 mm /
3.8 x 8.66 x 12.73 inches

Stand base footprint area (mm²)
260.87 x 69.55 mm /
10.27 x 2.74 inches

Weight Packed (kg / lbs.)
1.67 kg / 3.67 lbs.

Weight Unpacked (kg / lbs.)
0.57 kg / 1.26 lbs.

WHATS IN THE BOX

1 x Monitor with stand
1 x ThinkVision M14 sleeve
1 x USB Type-C cable (1 m)
1 x QSG
1 x Pair of clips

ENVIRONMENTAL

Temperature - Operating
0° to 40°C

Temperature - Non-operating
-20° to 60°C

Humidity - Operating
30 to 80%

Humidity - Non-operating
30 to 90%

Altitude - Operating
0 to 5000 m

Altitude - Non-operating
0 to 40,000 ft

Arsenic-free Glass
Yes

PVC free
Yes

Mercury free
Yes

PCC % of plastic resins
85%

WARRANTY

Geography Availability
WW

Warranty
3 Years

CERTIFICATIONS

ENERGY STAR® Rating
7.1

CCC
Yes

EPEAT
Bronze

RoHS (EU 2002/95/EC)
Yes (Arsenic free / Pb free / Mercury free)

Windows Certification
Windows 7 / 10

Image Quality Capability
ISO 9241-307

China Energy Efficiency Standard
Tier 2

Low Blue Light / Eye Comfort
Yes (Low BlueLight)

