## Míele

#### G 7266 SCVi

Fully integrated dishwashers in standard size with 3D MultiFlex Tray for maximum convenience.



- QuickIntenseWash, superior cleaning and drying in under 60 min
- Completely dry Miele AutoOpen drying
- Incredibly low sound emissions of just 42 dB(a) dB(A)
- edi
- Very easy door opening and closing ComfortClose
- Fresh water dishwashers as little as ?? water consumed in Normal program
- Convenient, great results, and perfect for everyday use – ExtraComfort baskets

EAN: 4002516770817 / Material number: 12497140 / Old Material Number: 217266621154

Type	
Fully integrated dishwashers	•
24 inch dishwasher	•
Design	
Fascia color	Stainless Steel.
Fascia panel version	Fully integrated fascia
Control type	Programme selector buttons
Control panel	1-line display with plain text
Display color	White
MultiLingua	•
Convenience	
Networking with Miele@home	•
Door closing aid	AutoClose
Operating noise dB(A) re 1 pW	42
Countdown indicator	•
Delay start up to 24 hours	•
In-operation indication	optical and acoustic
Display language selection	•
Efficiency and sustainability	
Noise emissions in dB(A)	42
EcoPower Technology	•
Proven hygiene	•
Hot water connection	•
Half load	•
Energy Star	•
Quality of results	
Fresh water dishwasher	•
AutoOpen drying	•
SensorDry	•
Active condensation drying	+
Perfect GlassCare	•
Wash programs	
QuickIntenseWash	•
ComfortWash	•
Pots & Pans	•
SaniWash	•
Extra Quiet 39 dB(A)	•
Appliance care	•
Rinse out salt	•
Rinse & Hold	•
Dishwashing options	
BottleClean	
Quick	•
IntenseZone	•
Extra Clean	•
Extra dry	•



### G 7266 SCVi

Fully integrated dishwashers in standard size with 3D MultiFlex Tray for maximum convenience.




EAN: 4002516770817 / Material number: 12497140 / Old Material Number: 21726662USA

Old Material Number: 21726662USA  Baskets	
Cutlery loading	3D MultiFlex Tray
FlexCare glass holder	2
FlexCare cup rack	
Basket design	ExtraComfort
9	• Extracomion
MultiClip FlexCare Glass & Bottle	•
XI -Assist	<u>.</u>
	·
Safety	
Waterproof system	<del>`</del>
Check filter saturation indicator	•
Technical data	
Niche width min in in.(mm)	23 5/8 (600)
Niche width max in in.(mm)	23 5/8 (600)
Niche height min in in.(mm)	33 3/4 (855)
Niche height max in in.(mm)	36 1/4 (920)
Niche depth in in.(mm)	21 3/4 (550)
Appliance width in in.(mm)	23 5/8 (598)
Appliance height in in.(mm)	33 3/4 (855)
Appliance depth in in.(mm)	21 3/4 (550)
Appliance depth with door open in in.(cm)	47 1/2 (120.5)
Net weight in lbs. (kg)	109 (49.0)
Total connected load in kW	1.40
Voltage in V	120
Fuse rating in A	15
Number of phases	1
Electrical frequency standard	_60
Length of water inlet hose in ft (m)	5 (1.50)
Length of water drain hose in ft (m)	5 (1.50)
Length of electrical wire in ft (m)	4 (1.20)
Min. front panel weight in kg	4.0
Max. front panel weight in kg	12.0
Standard accessories	
Voucher for 1 x box of UltraTabs (20 tabs) or 3 boxes (60 tabs in each) at a reduced price	•
Available display languages	
Available display languages via MultiLingua	deutsch, english (US), español, français (CA), português, ????

# Míele

#### G 7266 SCVi

Fully integrated dishwashers in standard size with 3D MultiFlex Tray for maximum convenience.



G7000, fully integrated dishwasher, XXL, 60cm (installation drawing)  $\,$ 

1) Plinth height 35-155 mm, 2) Plinth height 100-220 mm, 3) Appliance height max. 970 mm with plinth height conversion kit (Mat.-Nr. 6.394.761),