Key **Features**

16:9 Widescreen | sRGB Color Correction | Enhanced Viewing Comfort

Product **Description**

The ViewSonic® VA1901-a is a 19" (18.5" viewable) widescreen monitor that delivers value and performance for both home offices and small businesses. Equipped with crisp 1366x768 resolution, a fast 5ms response time, and rich color performance, the VA1901-a is great for a variety of applications ranging from viewing office documents to surfing the web. Featuring a matte finish, this 19" monitor looks great on any desktop. An exclusive ViewMode™ feature provides intuitive presets for optimized screen performance in different applications. In addition, Flicker-Free technology and a Blue Light Filter help to eliminate eye strain from extended viewing periods for improved productivity. An energy-saving Eco-mode reduces cost of ownership, making the VA1901-a a great choice for both government and education.

17.4" | 13.7" | 18.5" | 10.6" | 1.9" | 7.2"

01 VESA Compatible Wall Mount (100 x 100 mm)
02 Menu Control Panel
03 AC In
04 Kensington® Lock Slot
05 VGA

19"
DISPLAY

TN
PANEL

1366 x 768
RESOLUTION

Contact Sales

call: 888.881.8781

email: salesinfo@viewsonic.com

visit: viewsonic.com

Display:

Display Size (in.):	19
Viewable Area (in.):	18.5
Panel Type:	TN
Resolution:	1366 x 768
Resolution Type:	WXGA (1280x800)
Static Contrast Ratio:	600:1
Dynamic Contrast Ratio:	50,000,000:1
Light Source:	LED
Brightness:	200 cd/m2
Colors:	16.7M
Color Space Support:	6 bit + 2 bit Hi FRC
Aspect Ratio:	16:9
Response Time (Typical GTG):	5ms
Viewing Angles:	90º horizontal, 65º vertical
Backlight Life (Hours):	30,000
Panel Surface:	Anti-glare, Hard coating (3H)

Compatibility:

PC Resolution (max):	1366 x 768
Mac® Resolution (max):	1366 x 768

Connector:

VGA(1)

Power:

Eco Mode (Conserve):	7W
Eco Mode (optimized):	9W
Consumption (typical):	11W
Consumption (max):	13W
Voltage:	AC 100-240V (universal), 50-60Hz
Stand-by:	0.5W
Power Supply:	Internal

Additional Hardware:

Kensington Lock Slot:	1

Controls:

Physical Controls:	Key Buttons 1, 2, 3, 4, 5 (Power)
On Screen Display:	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)

Operating Conditions:

Temperature:	32-104º F (0 - 40º C)
Humidity (non-condensing):	20-90%

Mount:

VESA Compatible:	100 x 100 mm

Video Signal:

Frequency Horizontal:	24 ~ 82KHz
Frequency Vertical:	50 ~ 75Hz

Video Input:

Analog Sync:	Separate Sync

Ergonomics:

Tilt (Forward/Back):	5° / 23°

Weight (imperial):

Net (lbs):	4.4
Net Without Stand (lbs):	3.8
Gross (lbs):	5.7

Weight (metric):

Net (kg):	2.0
Net Without Stand (kg):	1.7
Gross (kg):	2.6

Dimensions (imperial) (WxHxD):

Packaging (in.):	19.6 x 13.9 x 4.5
Physical (in.):	17.4 x 13.7 x 7.2
Physical Without Stand (in.):	17.4 x 10.6 x 1.9

Dimensions (metric) (WxHxD):

Packaging (mm):	498.0 x 352.0 x 114.0
Physical (mm):	441.9 x 348.0 x 181.9
Physical Without Stand (mm):	441.9 x 268.3 x 48.2

General:

PACKAGE CONTENTS: VA1901-a Display, Power Cable, VGA Cable, Quick Start Guide

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

Warranty: Three-year limited warranty on parts, labor and backlight

UPC: 766907846218

Accessories:

LCD-DMA-001, LCD-DMA-002, LCD-WMK-001