

## New Design More Easily

### Wireless N300 Easy Setup Router N301V2

The N301V2 Wireless N300 Easy Setup Router is designed to setup more easily for the home user. It complies with IEEE802.11n, delivers wireless speeds of up to 300Mbps, making it perfect for everyday web activities like email, chat, streaming videos, online gaming and more. The N301V2 can also work as a client router to connect ISP network wirelessly or uplink AP to share the Internet to every corner, eliminating the dead point.



### Easy to Setup

With just three easy steps, get your secure wireless network up and running in minutes.



### Secure WiFi at a push of WPS button

Compatible with WI-FI Protected Setup™ (WPS), N301V2 features WPS that allows users to almost instantly setup their security simply by pressing the "WPS" button automatically establishing a secure connection. Not only is this faster than normal security setups but more convenient in that you don't need to remember a password.



### Advanced Wireless Security

N301V2 offers multi-level wireless encryption options to prevent unauthorized access and protect your important data.


1. 64/128bit WEP、WPA-PSK、WPA2-PSK

2. Wireless Access Control based on the mac address of wireless adapter

### Wireless WAN

N301V2 can work as client mode to connect to ISP network or uplink AP wirelessly to share the Internet to every corner, eliminating the dead point.





## Parental Control

Support parental control function like IP/MAC filter, you can limit the time to access the internet and block the websites.



## How it Works

How to make wireless magic, start with Internet service and a modem then connect a Linksys router. The router broadcasts a wireless signal that lets you easily connect your devices and smart appliances.

## Specifications

Hardware Features	
Compliant Standard	IEEE 802.3/3U IEEE 802.11n/g/b
Wired Interface	1 10/100Mbps WAN Port 3 10/100Mbps LAN Ports
Antennas	2 fixed 5dbi Omni Directional antennas
Button	1 Reset/WPS Button
Item dimensions(L*W*H)	127.4mm*90.5mm*26mm
Wireless Features	
Frequency Range (GHz)	2.412GHz-2.472GHz
Wireless Link Rate	IEEE 802.11n: up to 300Mbps IEEE 802.11g: up to 54Mbps IEEE 802.11b: up to 11Mbps
Wireless Security	64/128bit WEP WPA-PSK WPA2-PSK WPS support
Working Mode	AP WISP WDS Bridge
Wireless Function	Enable/Disable Wireless Radio Wireless Access Control
Reception Sensitivity	b mode: 1M -92dBm@8% 11M -87dBm@8% PER; g mode: 54M -72dBm@8% PER; n mode: 72.2M -68dBm@8% PER; 150M -68dBm@8% PER;

Software Features	
Internet Connection Type	Dynamic IP、PPPOE、Static IP、L2TP、PPTP
DHCP	Built-in DHCP server DHCP Client List Address Reservation
Virtual Server	Port Forwarding DMZ Host
Parental Control	Client Filter Mac Filter Websites Filter
Dynamic DNS	No-IP dyndns
VPN Pass-Through	PPTP L2TP
Other Advanced Function	Bandwidth Control Mac Address Clone Remote Web Management System Log
Others	
Package Contents	Wireless N300 Easy Setup Router N301V2 Quick Installation Guide Ethernet cable Power adapter Resources CD
Environment	Operating Temperature: 0°C~40°C Storage Temperature: -40°C~70°C Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing
Certificates	FCC, CE, RoHs

Shenzhen Tenda Technology Co.,Ltd  
 No. 34-1 Shilong Road  
 Shiyuan Town, Baoan District  
 Shenzhen 518108,China  
 Phone: (86 755) 2765 7180  
 Fax: (86 755) 2765 7178  
 Email: sales@tenda.com.cn

©2013 SHENZHEN TENDA TECHNOLOGY CO.,LTD, the Tenda logo is registered trademark of Shenzhen Tenda Technology Co.,Ltd in China and/or other countries. Other brand and product names are trademarks or registered trademarks of their respective holders. Information is subject to change without notice. ALL rights reserved.