

Public - Datasheet NVMe™ SSD



Highlights

- PCle[®] Gen 4.0, NVMe[™] SSD
- Sequential read speeds up to 7,100 MB/s and sequential write speeds up to 6,700 MB/s¹ (1TB-2TB² models)
- Random read speeds up to 1M IOPS and random write speeds up to 1.3M IOPS¹ (1TB-2TB² models)
- 500GB, 1TB, and 2TB2
- SANDISK® QLC 3D CBA NAND
- SANDISK® nCache™ 4.0 Technology
- 5-year limited warranty.4

WD Blue® SN5100 NVMe™ SSD

Designed for creators and professionals

The WD Blue® SN5100 NVMe™ SSD with PCle® Gen 4.0 delivers read speeds up to 7,100 MB/s,¹ (1TB-2TB² models), 30% faster than our prior generation.³ Create and store more with capacities up to 2TB² on M.2 2280, and fly through projects with our next generation SANDISK® 3D CBA NAND technology. Copy large files or project folders in blistering speeds thanks to our SANDISK® nCache™ 4.0 technology. Engineered for creators and professionals with Al-enabled workflows, the WD Blue® SN5100 NVMe™ SSD makes editing 8K videos and high-resolution images a breeze.

Speed up your projects

Accelerate your Al-enabled workflow and load assets quicker with PCle® Gen 4.0 read speeds up to 7,100 MB/s,¹ (1TB-2TB² models), which is 30% faster than our prior generation.³

Create and store more

Make more room for your masterpieces with capacities from $500GB^2$ to $2TB^2$ on M.2 2280 deploying next generation SANDISK® 3D CBA NAND technology.

Work faster, wait less

Copy large files or project folders in blistering speeds thanks to our SANDISK® nCache™ 4.0 technology.

Create confidently

Your new drive comes with a 5-year limited warranty, giving you peace of mind that your hard work isn't wasted. 4

Free Acronis® True Image™ software

Download Acronis $^{\circ}$ True Image $^{\circ}$ for SANDISK $^{\circ}$ data migration software to transfer your files to your new SSD. 5

Monitor your new drive

Monitor your SSD's performance and check for updates with the downloadable SANDISK® Dashboard application.6

WD Blue® SN5100 NVMe™ SSD

Datasheet NVMe[™] SSD

Specifications

Capacities ²	500GB	1TB	2TB
Model Numbers	WDS500G5B0E-00CPE0	WDS100T5B0E-00CPE0	WDS200T5B0E-00CPE0
Form Factor		M.2 2280	
Interface ⁷	PCle® Gen 4.0 x4, NVMe™		
NAND Type	SANDISK® QLC 3D CBA NAND		
Performance ¹			
Sequential Read 1MB (MB/s) up to (Queue Depth=8, Threads=1)	6,600	7,100	7;100
Sequential Write 1MB (MB/s) up to (Queue Depth=8, Threads=1)	5,600	6,700	6,700
Random Read 4KB (IOPS) up to (Queue Depth=32, Threads=16)	660K	1M	1M
Random Write 4KB (IOPS) up to (Queue Depth=32, Threads=16)	1.1M	1.3M	1.3M
Power ⁸			
Average Power - Read	3.8W	3.9W	4.1W
Average Power - Write	3.8W	3.9W	4.1W
Idle (Sleep)		4mW	
Reliability			
Endurance (TBW) ⁹	300	600	900
MTTF (hours) ⁹		1.75M	
Warranty⁴	5 year limited		
Environmental			
Operating Temerature ¹⁰	32°F to 185°F (0°C to 85°C)		
Non-operating Temperature ¹⁰	-40°F to 185°F (-40°C to 85°C)		
Operating Vibration	5 gRMS, 10-2000 Hz, 3 axes		
Non-operating Vibration	4.9 gRMS, 7-800 Hz, 3 axes		
Shock	1,500G @0.5 ms half-sine		
Regulatory			
Certifications	BSMI, CAN ICES-3(B)/NMB-3(B), CB-Scheme, CE, FCC, KCC, Morocco, RCM, TÜV, UL, VCCI, UKCA		
RoHS Compliant	Yes		
Security	TCG F	Pyrite 2.01, ATA Security passthrough over	NVMe™
Dimensions ¹¹			
Length	80mm		
Width	22mm		
Height	2.38mm		
Weight	5.7g		

- 1 MB/s = 1 million bytes per second. Based on internal testing; performance may vary depending upon host device, usage conditions, drive capacity and other factors. IOPS = input/output operations per second.
- ² 1GB = 1 billion bytes. 1TB = one trillion bytes. Actual user capacity may be less depending on operating environment. ³ As compared to the WD Blue* SN5000 SSD (TTB and 2TB models)
- 4 5 years or Max Endurance (TBW) limit, whichever occurs first. See sandisk.com/support for region-specific warranty details.
 5 Download and installation required. Includes 5-year license for your compatible drive. Redeem within 90 days of purchase. May not be combined with other offers. Limited time offer; see sandisk.com/support website for more details.
- Offer subject to change

- A wallable for download at sandisk.com/support

 A Wallable for download at sandisk.com/support

 PCIe* Gen4 storage technology requires a compatible motherboard. Backwards compatible with PCIe* Gen3 x4, PCIe* Gen3 x2, PCIe* Gen3 x1, PCIe* Gen2 x4, PCIe* Gen2 x2 and PCIe* Gen2 x1.

 A Average Power Read and Average Power Write are measured using IOMeter 11.0 during a burst sequential read and write operation (measured separately) and represent a moving average over a 10 second period. Performance may vary depending on test setup, configuration and firmware version.
- a TBW (terabytes written) values calculated using JEDEC client workload (JESD219) and vary by product capacity. MTTF = Mean Time To Failure based on internal testing using Telcordia™ stress part testing (Telcordia SR-332, GF, 25°C). MTTF is based on a sample population and is estimated by statistical measurements and acceleration algorithms. MTTF does not predict an individual drive's reliability and does not constitute a warranty.

 ¹Operational temperature is defined as temperature reported by the drive. Note that drive temperature readings are expected to be higher than ambient temperature when the SSD is placed inside a system. The SSD box package is rated up to 60°C. Non-operational storage temperature does not guarantee data retention.
- 11 . Physical product dimensions for length and width may vary by \pm 0.10mm and product weight may vary by \pm 10%.



SANDISK, the SANDISK logo, and nCache are registered trademarks or trademarks of Sandisk Corporation or its affiliates in the U.S. and/or other countries, WD Blue is a registered trademark or trademark of Western Digital Corporation or its affiliates in the U.S. and/or other countries. Acronis and True Image are registered marks of Acronis International GmbH in the United States and other countries. The NVMe word mark is a trademark of NVM Express, Inc. PCle® is a registered trademark of PCI-SIG. Windows is a registered trademark of the Microsoft group of companies. All other marks are the property of their respective owners. Product specifications subject to change without notice. Pictures shown may vary from actual products. ©2025 Sandisk Corporation or its affiliates. All rights reserved.